

ENVIRONMENTAL COMPLIANCE APPROVAL

NUMBER 7095-BYBRVR
Issue Date: March 18, 2021

Service Corporation International (Canada) ULC
1835 Hastings Street East
Vancouver, British Columbia
V5L 1T3

Site Location: Dignity Memorial
3-46 North Queen Street, Etobicoke
Toronto City
M8Z 2C4

You have applied under section 20.2 of Part II.1 of the Environmental Protection Act, R.S.O. 1990, c. E. 19 (Environmental Protection Act) for approval of:

a new crematorium, performing up to fifteen (15) cremations per day between 7:00 am and 11:00 pm, consisting of three (3) cremation units:

- two (2) new natural gas fired multi-chamber cremation units (Source S1 and S2, Pyrox model X-3000), each equipped with CEM System, a primary burner rated at 1,055,000 kilojoules per hour and a secondary burner rated at 2,110,000 kilojoules per hour, each discharging into the atmosphere at a nominal volumetric flow rate of 2.2 actual cubic metres per second at the actual temperature of 580 degrees Celsius through a stack, each having an exit diameter of 0.56 metre, each extending 6.5 metres above the roof and 12.7 metres above grade;
- one (1) new natural gas fired multi-chamber cremation unit (Source S3, Pyrox model X-3000-OS), equipped with CEM System, a primary burner rated at 1,055,000 kilojoules per hour and a secondary burner rated at 2,110,000 kilojoules per hour, discharging into the atmosphere at a nominal volumetric flow rate of 2.2 actual cubic metres per second at the actual temperature of 580 degrees Celsius through a stack, having an exit diameter of 0.56 metre, each extending 6.5 metres above the roof and 12.7 metres above grade;

all in accordance with the Environmental Compliance Approval Application submitted by Service Corporation International (Canada) ULC, dated July 21, 2020 and signed by Jayson B. Gordon, President, the letters from Tu Duong (Beaulier, Division de Environnement) and dated February 24, 2021 and March 10, 2021, the letter from Jay Branton, Managing Director - Ontario South (Service Corporation International (Canada) ULC dated March 16, 2021, and all other supporting information and documentation submitted in support of the application.

For the purpose of this environmental compliance approval, the following definitions apply:

1. "Approval" means this Environmental Compliance Approval, including the application and all supporting documentation listed above;
2. "CEM System" means the continuous monitoring and recording systems and associated control systems used to optimize the operation of the Equipment to minimize the emissions from the Equipment, as described in the Company's application, this Approval and in the supporting documentation referred to herein, to the extent approved by this Approval, as specified in the attached Schedule "A", "B", and "C";
3. "Commissioning Letter" means the letter dated March 16, 2021 and signed by Jay Branton, Managing Director - Ontario South (Service Corporation International (Canada) ULC);
4. "Company" means Service Corporation International (Canada) ULC operating as Dignity Memorial that is responsible for the construction or operation of the Facility and includes any successors and assigns in accordance with section 19 of the EPA;
5. "Director" means a person appointed by the Minister pursuant to section 5 of the EPA;
6. "District Manager" means the appropriate local district office of the Ministry, where the Facility is geographically located;
7. "EPA" means the Environmental Protection Act, R.S.O. 1990, c.E.19;
8. "ESDM Report" means the Emission Summary and Dispersion Modelling Report prepared in accordance with section 26 of O. Reg. 419/05 and the Procedure Document by Nghiep Tu Duong (Beaulier Inc.) and dated November 3, 2020 submitted in support of the application including any addendum submissions made during the Ministry's review of the Company's application;
9. "Equipment" means the three (3) cremation units, described in the Company's application, this Approval and in the supporting documentation submitted with the application, to the extent approved by this Approval;
10. "Facility" means the entire operation located on the property where the Equipment is located;
11. "Manager" means the Manager, Technology Standards Section, Standards Development Branch, or any other person who represents and carries out the duties of the Manager, Technology Standards Section, Standards Development Branch, as those duties relate to the conditions of this Approval;
12. "Manual" means a document or a set of documents that provide written instructions to staff of the Company;

13. "Ministry" means the ministry of the government of Ontario responsible for the EPA and includes all officials, employees or other persons acting on its behalf;
14. "O. Reg. 419" means the Ontario Regulation 419/05, Air Pollution – Local Air Quality, as amended;
15. "Performance Requirements" means the performance requirements and emission limits specified in the sections of this Approval titled "Operating Parameters", "Emission Concentration Limit", and "Noise";
16. "Point of Impingement" has the same meaning as in section 2 of O. Reg. 419;
17. "Pre-Test Plan" means a plan for the Source Testing including the information required in Section 5 of the Source Testing Code;
18. "Publication NPC-300" means the Ministry Publication NPC-300, "Environmental Noise Guideline, Stationary and Transportation Sources – Approval and Planning, Publication NPC-300", August 2013, as amended;
19. "Schedules" means the following schedules attached to this Approval and forming part of this Approval namely:
 - Schedule A - Continuous Temperature Monitoring System.
 - Schedule B - Continuous Oxygen Monitoring System.
 - Schedule C - Continuous Carbon Monoxide Monitoring System.
 - Schedule D - Test Contaminants.
 - Schedule E -Targeted Sources and Test Contaminants.
 - Schedule F - Source Testing Procedures;
20. "Source Testing" means sampling and testing to measure emissions resulting from operating the Equipment under conditions which yield the worst case emissions, as practically possible, within the approved operating range of the Equipment and satisfies paragraph 1 of subsection 11(1) of O. Reg. 419, as determined in consultation with the Manager;
21. "Source Testing Code" means the Ontario Source Testing Code, dated June 2010, prepared by the Ministry, as amended;
22. "Targeted Sources and Test Contaminants" means Targeted Sources and Test contaminants listed in Schedule F; and
23. "Test Contaminants" means the contaminants listed in Schedule "D".

You are hereby notified that this environmental compliance approval is issued to you subject to the terms and conditions outlined below:

TERMS AND CONDITIONS

1. OPERATING PARAMETERS

1. The Company shall ensure that the Equipment is designed and operated to comply, at all times, with the following performance requirements:
 - a. the residence time of the combustion gases in the secondary combustion chamber shall be at a minimum one second at a temperature of at least 1,000 degrees Celsius;
 - b. the temperature in the secondary combustion chamber, as recorded by the CEM System, shall be at least 1,000 degrees Celsius before the primary combustion chamber is loaded and thereafter throughout each cremation; and
 - c. the temperature at the outlet of the primary combustion chamber, as recorded by the CEM System, shall be at least 800 degrees Celsius for at least 30 minutes during the last part of each cremation.

2. EMISSION CONCENTRATION LIMIT

1. The Company shall ensure that the Equipment is designed and operated to comply, at all times, with the following performance requirements:
 - a. the concentration of oxygen in the undiluted flue gas leaving the secondary chamber, as recorded by the CEM System, shall not be less than 6 percent by volume on a dry basis, calculated as a 10-minute average;
 - b. the half-hour average concentration of carbon monoxide in the undiluted flue gases leaving the secondary combustion chamber, as recorded by the CEM System, shall not exceed 100 parts per million by volume, on a dry basis normalized to 11 percent oxygen at a reference temperature of 25 degrees Celsius and a reference pressure of 101.3 kilopascals;
 - c. the concentration of organic matter having a carbon content, expressed as equivalent methane, being an average of ten measurements taken at approximately one minute intervals, shall not be greater than 100 parts per million by volume, measured on an undiluted basis.

3. NOISE LIMIT

1. The Company shall, at all times, ensure that the noise emissions from the Facility comply with the limits set out in Ministry Publication NPC-300.

4. OPERATION AND MAINTENANCE

1. The Company shall ensure that the Equipment is properly operated and maintained at all times. The Company shall:
 - a. prepare, before commencement of operation of the Equipment, and update, as necessary, an Operational and Maintenance Manual outlining the operating procedures and a maintenance program for the Equipment, including:
 - i. the routine and emergency operating and maintenance procedures in accordance with good engineering practice, including annual inspection procedures as recommended by the Equipment and CEM System suppliers;
 - ii. emergency procedures;
 - iii. procedures to control all discharges from the Equipment in the event of loss or failure of power source to the Equipment;
 - iv. procedures for any record keeping activities relating to the operation and maintenance of the Equipment;
 - v. procedures for operator training which is to be provided by an individual experienced with the Equipment;
 - vi. procedures for optimizing the operation of the Equipment to minimize the emissions from the Equipment; and
 - vii. the procedures for recording and responding to complaints regarding the operation of the Equipment;
 - b. implement the recommendations of the Operational and Maintenance Manual.
2. The Company shall ensure that the primary combustion chamber is not loaded unless the associated CEM System is fully operational.
3. The Company shall make all reasonable efforts to ensure that all hardware is removed from the caskets before they are loaded into the Equipment.
4. The Company shall install and maintain visual and audible alarm systems to alert the Equipment operators of any potential deviation from the above Performance Requirements for parameters that are continuously monitored by applicable CEM System and shall forthwith take all reasonable actions to bring the Equipment into compliance with all Performance Requirements.

5. COMPLAINTS RESPONSE PROCEDURE

1. If at any time, the Company receives any environmental complaints from the public regarding the operation of the Facility, the Company shall respond to these complaints according to the following procedure:

- a. The Company shall record each environmental complaint and notify the District Manager, in writing within two (2) business days of the receipt of a complaint, including the following information:
 - i. nature of the complaint;
 - ii. weather conditions and wind direction at the time of the complaint;
 - iii. name and address of the complainant (if provided); and
 - iv. time and date of the complaint and incident to which the complaint relates.
- b. The Company shall forthwith take appropriate steps to determine all possible causes of the complaint and to eliminate the cause of the complaint. A written reply shall be provided to the District Manager and the complainant, if known and if requested by the complainant, within three (3) business days of receipt of the complaint by the Company.

6. SOURCE TESTING

1. The Company shall perform Source Testing in accordance with the procedures outlined in the attached Schedule "F" to determine the rate of emission of the Test Contaminants from the Targeted Sources listed in Schedule "E".

7. CONTINUOUS MONITORING

1. The Company shall, prior to the commencement of operation of the Equipment, install and subsequently conduct and maintain a program to continuously monitor:
 - a. the temperature at the outlet of the primary chamber of the Equipment;
 - b. the temperature at the location in the secondary chamber of the cremator where the minimum retention time of the combustion gases at a minimum temperature of 1000 degrees Celsius for at least one second is achieved; and
 - c. the concentration of carbon monoxide and the concentration of oxygen in the undiluted gases leaving the secondary chamber of the Equipment.

The CEM System shall be equipped with continuous recording devices and shall comply with the requirements outlined in the attached Schedule "A", "B", and "C".

8. RECORD RETENTION

1. The Company shall maintain and retain for a minimum of two (2) years from the date of their creation, all records and information related to or resulting from the operation of the Equipment, and monitoring and recording activities required by this Approval. These records shall be made available to staff of the Ministry upon request in a timely manner. The Company shall retain:

- a. number of daily cremations;
- b. records of each load processed by the Equipment including:
 - i. a description of the material of construction of the casket;
 - ii. type of finish on the casket;
 - iii. description of any hardware not removed from the casket;
 - iv. estimated weight of the body and casket; and
 - v. start and finish time of the cremation;
- c. all original records produced by the Source Testing and the recording devices associated with the CEM System;
- d. records of all excursions from the applicable Performance Requirements as measured by the CEM System, duration of the excursions, reasons for the excursions and corrective measures taken to eliminate the excursions;
- e. all records on maintenance, repair and inspection of the Equipment and the CEM System;
- f. description of any upset conditions associated with the operation of the Equipment and remedial action taken;
- g. all records on operator training, including:
 - i. date of training;
 - ii. name and signature of person who has been trained; and
 - iii. description of the training provided;
- h. all records on the environmental complaints, including:
 - i. a description, time and date of the incident;
 - ii. wind direction at the time of the incident; and
 - iii. a description of the measures taken to address the cause of the incident and to prevent a similar occurrence in the future.

SCHEDULE "A"

Continuous Temperature Monitoring System

PARAMETER:

Temperature

LOCATION:

The sample point for the Continuous Temperature Monitor shall be located in:

1. the outlet of the primary chamber; and
2. the secondary chamber where the minimum retention time of the combustion gases at a minimum temperature of 1,000 degrees Celsius for at least one second is achieved.

PERFORMANCE:

The Continuous Temperature Monitor shall meet the following minimum performance specifications for the following parameters:

PARAMETERS	SPECIFICATION
Type	shielded "K" type thermocouple, or equivalent
Accuracy	± 1.5 percent of the minimum gas temperature

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitor without a significant loss of accuracy and with a time resolution of 1 minutes or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 95 percent of the time for each calendar quarter.

SCHEDULE "B"

Continuous Oxygen Monitoring System

PARAMETER:

Oxygen

INSTALLATION:

The Continuous Oxygen Monitor shall be installed at an accessible location where the measurements are representative of the actual concentration of oxygen in the undiluted gases leaving the secondary chamber of the *Equipment* and shall meet the following installation specifications:

PARAMETERS	SPECIFICATION
Range (percentage)	0 to 20 or 0 to 25
Calibration Gas Ports	close to the sample point

PERFORMANCE:

The Continuous Oxygen Monitor shall meet the following minimum performance specifications for the following parameters.

PARAMETERS	SPECIFICATION
Span Value (percentage)	80 to 100% of full scale
Relative Accuracy	≤ 10 percent of the mean value of the reference method test data
Calibration Error	0.5 percent O ₂
System Bias	≤ 4 percent of the mean value of the reference method test data
Procedure for Zero and Span Calibration check	all system components checked
Zero Calibration Drift (24-hour)	≤ 0.5 percent O ₂
Span Calibration Drift (24-hour)	≤ 0.5 percent O ₂
Response Time (90 percent response to a step change)	≤ 180 seconds

Operational Test Period

≥ 168 hours without corrective maintenance

CALIBRATION:

Daily calibration drift checks on the monitor shall be performed and recorded in accordance with the requirements of Report EPS 1/PG/7.

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitor with an accuracy of 0.5 percent of a full scale reading or better and with a time resolution of 2 minutes or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 90 percent of the time for each calendar quarter during the first full year of operation, and 95 percent, thereafter.

SCHEDULE "C"
Continuous Carbon Monoxide Monitoring System

PARAMETER:
 Carbon Monoxide

INSTALLATION:
 The Continuous Carbon Monoxide Monitor shall be installed at an accessible location where the measurements are representative of the actual concentration of carbon monoxide in the undiluted gases leaving the secondary chamber of the *Equipment* and shall meet the following installation specifications:

PARAMETERS	SPECIFICATION
Range (parts per million, ppm)	0 to ≥ 100
Calibration Gas Ports	close to the sample point

PERFORMANCE:
 The Continuous Carbon Monoxide Monitor shall meet the following minimum performance specifications for the following parameters:

PARAMETERS	SPECIFICATION
Span Value (nearest ppm equivalent)	80 to 100% of full scale
Relative Accuracy	≤ 10 percent of the mean value of the reference method test data or ± 5 ppm whichever is greater
Calibration Error	≤ 2 percent of actual concentration
System Bias	≤ 4 percent of the mean value of the reference method test data
Procedure for Zero and Span Calibration Check	all system components checked
Zero Calibration Drift (24-hour)	≤ 5 percent of span value
Span Calibration Drift (24-hour)	≤ 5 percent of span value
Response Time (90 percent response to a step change)	≤ 180 seconds
Operational Test Period	≥ 168 hours without corrective maintenance

CALIBRATION:

Daily calibration drift checks on the monitor shall be performed and recorded in accordance with the requirements of Report EPS 1/PG/7.

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitor with an accuracy of 0.5 percent of a full scale reading or better and with a time resolution of 2 minutes or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 90 percent of the time for each calendar quarter during the first full year of operation, and 95 percent, thereafter.

SCHEDULE "D"

Test Contaminants

- Total Suspended Particulate Matter
- Total Hydrocarbons Compounds (Total Gaseous Non-Methane Organics)
- Hydrogen Chloride

List of Metals:

- Antimony
- Arsenic
- Barium
- Beryllium
- Cadmium
- Chromium
- Cobalt
- Copper
- Lead
- Mercury
- Molybdenum
- Nickel
- Selenium
- Silver
- Thallium
- Vanadium
- Zinc

List of Dioxins, Furans and Dioxin-like PCBs

- 2,3,7,8-Tetrachlorodibenzo-p-dioxin [2,3,7,8-TCDD]
- 1,2,3,4,6,7,8,9-Octachlorodibenzo-p-dioxin [1,2,3,4,6,7,8,9-OCDD]
- 1,2,3,7,8,9-Hexachlorodibenzo-p-dioxin [1,2,3,7,8,9-HxCDD]
- 2,3',4,4',5- Pentachlorobiphenyl [2,3',4,4',5-pentaCB (PCB 118)]
- 3,3',4,4'-Tetrachlorobiphenyl [3,3',4,4'-tetraCB (PCB 77)]
- 2,3,3',4,4'- Pentachlorobiphenyl [2,3,3',4,4'-pentaCB (PCB 105)]
- 3,3',4,4',5,5'- Hexachlorobiphenyl [3,3',4,4',5,5'-hexaCB (PCB 169)]
- 1,2,3,4,6,7,8-Heptachlorodibenzo-p-dioxin [1,2,3,4,6,7,8-HpCDD]
- 2,3,3',4,4',5- Hexachlorobiphenyl [2,3,3',4,4',5-hexaCB (PCB 156)]
- 1,2,3,4,6,7,8,9-Octachlorodibenzofuran [1,2,3,4,6,7,8,9-OCDF]
- 1,2,3,4,7,8-Hexachlorodibenzo-p-dioxin [1,2,3,4,7,8-HxCDD]
- 2,3,3',4,4',5,5'- Heptachlorobiphenyl [2,3,3',4,4',5,5'-heptaCB (PCB189)]
- 1,2,3,7,8-Pentachlorodibenzo-p-dioxin [1,2,3,7,8-PeCDD]
- 2,3,7,8-Tetrachlorodibenzofuran [2,3,7,8-TCDF]
- 2,3',4,4',5,5'- Hexachlorobiphenyl [2,3',4,4',5,5'-hexaCB (PCB 167)]
- 1,2,3,4,7,8,9-Heptachlorodibenzofuran [1,2,3,4,7,8,9-HpCDF]
- 2,3,4,7,8-Pentachlorodibenzofuran [2,3,4,7,8-PeCDF]
- 1,2,3,7,8-Pentachlorodibenzofuran [1,2,3,7,8-PeCDF]
- 1,2,3,6,7,8-Hexachlorodibenzofuran [1,2,3,6,7,8-HxCDF]
- 3,3',4,4',5- Pentachlorobiphenyl (PCB 126) [3,3',4,4',5-pentaCB (PCB126)]
- 1,2,3,6,7,8-Hexachlorodibenzo-p-dioxin [1,2,3,6,7,8-HxCDD]
- 2,3,4,6,7,8-Hexachlorodibenzofuran [2,3,4,6,7,8-HxCDF]
- 2',3,4,4',5- Pentachlorobiphenyl [2',3,4,4',5-pentaCB (PCB 123)]
- 1,2,3,4,6,7,8-Heptachlorodibenzofuran [1,2,3,4,6,7,8-HpCDF]
- 2,3,3',4,4',5'- Hexachlorobiphenyl [2,3,3',4,4',5'-hexaCB (PCB 157)]
- 3,4,4',5- Tetrachlorobiphenyl [3,4,4',5-tetraCB (PCB 81)]
- 1,2,3,4,7,8-Hexachlorodibenzofuran [1,2,3,4,7,8-HxCDF]
- 1,2,3,7,8,9-Hexachlorodibenzofuran [1,2,3,7,8,9-HxCDF]
- 2,3,4,4',5- Pentachlorobiphenyl [2,3,4,4',5-pentaCB (PCB 114)]

List of Polycyclic Organic Matter:

- Benzo(a)pyrene [as a surrogate of total Polycyclic Aromatic Hydrocarbons (PAHs)]
- Naphthalene

SCHEDULE "E"

Targeted Sources and Test Contaminants

TARGETED SOURCES	TEST CONTAMINANTS
One Pyrox model X-3000 or Pyrox model X-3000-OS cremation unit (source S1, or S2 or S3)	All contaminants listed in Schedule "D"

1. Tested unit shall comply with the requirements outlined in the Commissioning Letter.

SCHEDULE "F"

Source Testing Procedures

1. The Company shall submit to the Manager a test protocol including the Pre-Test Plan required by the Source Testing Code, at least two (2) months prior to the scheduled Source Testing date. The Company shall finalize the Pre-Test Plan in consultation with the Manager.
2. The Company shall not commence the Source Testing required under this Approval until the Manager has approved the Pre-Test Plan.
3. The Company shall complete the Source Testing no later than three (3) months after commencement of operation of the Equipment or two (2) months after the Manager has approved the Pre-Test Plan, whichever occurs later.
4. The Company shall notify the Manager and the District Manager in writing of the location, date and time of any impending Source Testing required by this Approval, at least fifteen (15) days prior to the Source Testing.
5. The Company shall submit a report (hard copy and electronic format) on the Source Testing to the Manager and the District Manager not later than three (3) months after completing the Source Testing. The report shall be in the format described in the Source Testing Code, and shall also include, but not be limited to:
 - a. an executive summary;
 - b. all records of the operating conditions at the time of *Source Testing*, including but not limited to the following:
 - i. description of the material of construction of the casket
 - ii. type of finish on the casket

- iii. description of any hardware not removed from the casket
 - iv. estimated weight of the cremated body as per the information obtained from the funeral home
 - a. estimated maximum daily average weight of the cremated body
 - v. start and finish time of each cremation
 - c. all records produced by the CEM System;
 - d. all records of the cremator settings during the cremation;
 - e. the results of Source Testing, including the emission rate and emission concentration, and relevant emission factors of the Test Contaminants from the Targeted Sources;
 - f. a tabular comparison of Source Testing results for the Targeted Sources and Test Contaminants to original emissions described in the Company's application and the ESDM Report;
 - g. if the Source Testing results are higher than the emission estimates in the Company's ESDM Report, the Company shall update their ESDM Report in accordance with Section 26 of O. Reg. 419/05 with the result from the Source Testing report and make these records available for review by staff of the Ministry upon request. The updated Emission Summary Table from the updated ESDM Report shall be submitted with the report on the Source Testing.
 - h. results of the calculation of the residence time of the combustion gases in the secondary combustion chamber at a minimum temperature of 1000 degrees Celsius; and
 - i. recommendations for optimizing the operation of the Equipment to minimize the emissions from the Equipment.
6. The Director may not accept the results of the Source Testing if:
- a. the Source Testing Code or the requirements of the Manager were not followed;
 - b. the Company did not notify the Manager, the District Manager and the Director of the Source Testing; or
 - c. the Company failed to provide a complete report on the Source Testing.
7. If the Director does not accept the results of the Source Testing, the Director may require re-testing. If re-testing is required, the Pre-Test Plan strategies need to be revised and submitted to the Manager for approval. The actions taken to minimize the possibility of the Source Testing results not being accepted by the Director must be noted in the revision.

The reasons for the imposition of these terms and conditions are as follows:

1. Conditions No. 1, 2, and 3 are included to provide the minimum performance requirements considered necessary to prevent an adverse effect resulting from the operation of the Facility/Equipment.
2. Condition No. 4 is included to emphasize that the Equipment must be operated and maintained according to a procedure that will result in compliance with the EPA, the regulations and this Approval.
3. Condition No. 5 is included to require the Company to notify staff of the Ministry so as to assist the Ministry with the review of the site's compliance.
4. Conditions No. 6 and 7 are included to require the Company to gather accurate information so that the environmental impact and subsequent compliance with the EPA, the regulations and this Approval can be verified.
5. Condition No. 8 is included to require the Company to keep records and provide information to the Ministry so that the environmental impact and subsequent compliance with the EPA, the regulations and this Approval can be verified.

In accordance with Section 139 of the Environmental Protection Act, you may by written Notice served upon me, the Environmental Review Tribunal and in accordance with Section 47 of the Environmental Bill of Rights, 1993, the Minister of the Environment, Conservation and Parks, within 15 days after receipt of this Notice, require a hearing by the Tribunal. The Minister of the Environment, Conservation and Parks will place notice of your appeal on the Environmental Registry. Section 142 of the Environmental Protection Act provides that the Notice requiring the hearing shall state:

- a. The portions of the environmental compliance approval or each term or condition in the environmental compliance approval in respect of which the hearing is required, and;
- b. The grounds on which you intend to rely at the hearing in relation to each portion appealed.

The Notice should also include:

1. The name of the appellant;
2. The address of the appellant;
3. The environmental compliance approval number;
4. The date of the environmental compliance approval;
5. The name of the Director, and;
6. The municipality or municipalities within which the project is to be engaged in.

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

The Secretary*
Environmental Review Tribunal
655 Bay Street, Suite 1500
Toronto, Ontario
M5G 1E5

AND

The Minister of the Environment,
Conservation and Parks
777 Bay Street, 5th Floor
Toronto, Ontario
M7A 2J3

AND

The Director appointed for the purposes of
Part II.1 of the Environmental Protection Act
Ministry of the Environment,
Conservation and Parks
135 St. Clair Avenue West, 1st Floor
Toronto, Ontario
M4V 1P5


*** Further information on the Environmental Review Tribunal's requirements for an appeal can be obtained directly from the**

Tribunal at: Tel: (416) 212-6349, Fax: (416) 326-5370 or www.ert.gov.on.ca

This instrument is subject to Section 38 of the Environmental Bill of Rights, 1993, that allows residents of Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek leave to appeal within 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry at <https://ero.ontario.ca/>, you can determine when the leave to appeal period ends.

The above noted activity is approved under s.20.3 of Part II.1 of the Environmental Protection Act.

DATED AT TORONTO this 18th day of March, 2021



Rudolf Wan, P.Eng.

Director

appointed for the purposes of Part II.1 of the
Environmental Protection Act

JK/

c: District Manager, MECP Toronto District Office
Nghiep Tu Duong, Beaulier Inc.