

ENVIRONMENTAL COMPLIANCE APPROVAL

NUMBER 8038-CY3HJ6
Issue Date: January 25, 2024

London Beloved Pet Cremation Inc.
2470 Cromarty Drive, Putnam
Thames Centre, Ontario
N0L 2B0

Site Location: 2470 Cromarty Drive, Putnam
Thames Centre Municipality, County of Middlesex

You have applied under section 20.2 of Part II.1 of the Environmental Protection Act, R.S.O. 1990, c. E. 19 (Environmental Protection Act) for approval of:

- one (1) natural gas fired pet cremation unit Matthews Environmental Solutions IEB-26, identified as Source Stack 1, processing up to 91 kilograms per hour of Non-Infectious Remains of Companion Pets, having a maximum heat input of 3,165,168 kilojoules per hour, exhausting into the atmosphere at a volumetric flow rate of 1.18 cubic metres per second, through a stack, having an exit diameter of 0.51 metre, extending 0.91 metres above the roof and 7.92 metres above grade;
- one (1) natural gas fired pet cremation unit Matthews Environmental Solutions IEB-26, identified as Source Stack2, processing up to 91 kilograms per hour of Non-Infectious Remains of Companion Pets, having a maximum heat input of 3,165,168 kilojoules per hour, exhausting into the atmosphere at a volumetric flow rate of 1.18 cubic metres per second, through a stack, having an exit diameter of 0.51 metre, extending 0.91 metres above the roof and 7.92 metres above grade; and
- one (1) cremains processor that grinds the cremains in an enclosed ventless chamber with a processing hood;

all in accordance with the Application for Approval (Air) submitted by London Beloved Pet Cremation Inc. and signed by Jeff Bushell, Owner, the supporting information, including the Emission Summary and Dispersion Modelling Report, submitted by WSP E&I Canada Limited. dated September 19, 2023, and signed by Akhter Iqbal; an email update provided by Akhter Iqbal of WSP E&I Canada Limited on December 11, 2023, January 03, 2024, January 08, 2024 and January 23, 2024.

For the purpose of this environmental compliance approval, the following definitions apply:

1. "Approval" means this entire Environmental Compliance Approval, including the application and all supporting documentation listed above;
2. "Companion Pets" means animals that were kept by humans for company, amusement or psychological support;
3. "Company" means London Beloved Pet Cremation Inc. that is responsible for the construction or operation of the Facility and includes any successors and assigns in accordance with section 19 of the EPA;
4. "Continuous Monitoring System" means the continuous monitoring system consisting of continuous monitors and recording devices;
5. "Director" means a person appointed for the purpose of section 20.3 of the EPA by the Minister pursuant to section 5 of the EPA;
6. "District Manager" means the District Manager of the appropriate local district office of the Ministry, where the Facility is geographically located;
7. "EPA" means the *Environmental Protection Act*, R.S.O. 1990, c.E.19;
8. "Equipment" means the [2] pet cremation unit(s), described in the Company's application, this Approval and in the supporting documentation submitted with the application, to the extent approved by this Approval;
9. "ESDM Report" means the Emission Summary and Dispersion Modelling Report which was prepared in accordance with section 26 of O. Reg. 419/05 and the Procedure Document by Akhter Iqbal, WSP E&I Canada Limited and dated September 19, 2023, submitted in support of the application, and includes any changes to the report made up to the date of issuance of this Approval;
10. "Facility" means the entire operation located on the property where the Equipment is located;
11. "Infectious Substance" means a disease listed in
 - Schedule VII of the Health of Animals Regulations made under the Health of Animals Act (Canada), as amended; or
 - the Reportable Diseases Regulations made under the Health of Animals Act (Canada), as amended;

12. "Manager" means the Manager, Technology Standards Section, Technical Assessment and Standards Development Branch, or any other person who represents and carries out the duties of the Manager, Technology Standards Section, Technical Assessment and Standards Development Branch, as those duties relate to the conditions of this Approval;
13. "Manual" means a document or a set of documents that provide written instructions to staff of the Company;
14. "Minister" means the Minister of the Environment, Conservation and Parks or such other member of the Executive Council as may be assigned the administration of the EPA under the Executive Council Act;
15. "Ministry" means the ministry of the Minister;
16. "Non-Infectious Remains of Companion Pets" means whole carcasses or parts from carcasses of Companion Pets and are not contaminated with any Infectious Substance;
17. "O. Reg. 419/05" means Ontario Regulation 419/05: Air Pollution – Local Air Quality, made under the EPA;
18. "Point of Impingement" has the same meaning as in section 2 of O. Reg. 419/05;
19. "Pre-Test Plan" means a plan for the Source Testing including the information required in Section 5 of the Source Testing Code;
20. "Procedure Document" means Ministry guidance document titled "Procedure for Preparing an Emission Summary and Dispersion Modelling Report" dated March 2018, as amended;
21. "Publication NPC-300" means the Ministry Publication NPC-300, "Environmental Noise Guideline, Stationary and Transportation Sources – Approval and Planning, Publication NPC-300", August 2013, as amended;
22. "Report EPS 1/PG/7" means the document titled "Protocols and Performance Specifications for Continuous Monitoring of Gaseous Emissions from Thermal Power Generation - Report EPS 1/PG/7" published by Environment Canada in December 2005, as amended;
23. "Schedules" means the following schedules attached to this Approval and forming part of this Approval namely:
 - Schedule A - Source Testing Procedures;
 - Schedule B - Test Contaminants;
 - Schedule C - Continuous Temperature Monitoring System;
 - Schedule D - Continuous Oxygen Monitoring System; and
 - Schedule E - Continuous Carbon Monoxide Monitoring System;

24. "Source Testing" means site-specific sampling and testing to measure emissions resulting from operating a representative unit of the Equipment under operating conditions that will derive an emission rate that, for the relevant averaging period of the contaminant, is at least as high as the maximum emission rate that the source of contaminant is reasonably capable of, or a rate approved by the Manager within the approved operating range of the representative unit of the Equipment which satisfies paragraph 1 of subsection 11(1) of O. Reg. 419/05;
25. "Source Testing Code" means the Ontario Source Testing Code, dated June 2010, prepared by the Ministry, as amended; and
26. "Test Contaminants" means the contaminants listed in Schedule B.

You are hereby notified that this environmental compliance approval is issued to you subject to the terms and conditions outlined below:

TERMS AND CONDITIONS

1. OPERATING PARAMETERS

1. The Company shall ensure that the Equipment is designed and operated to comply, when the Equipment is operating, with the following performance requirements:
 - a. the burner flame in the secondary chamber shall be established before the primary chamber is fired;
 - b. the temperature in the secondary chamber, as measured by the Continuous Monitoring System, shall be maintained at minimum of 1,000 degrees Celsius at all times when the primary chamber is loaded and incineration is in progress;
 - c. the residence time of the combustion gases in the secondary combustion chamber shall be at a minimum one second at a temperature of at least 1,000 degrees Celsius; and
 - d. the burner in the primary chamber shall shut off automatically if the secondary chamber burner fails.
2. The Company shall ensure that only Non-Infectious Remains of Companion Pets are burned in the Equipment.

2. EMISSION CONCENTRATION LIMITS

1. The Company shall ensure that the Equipment is designed and operated to comply, when the Equipment is operating, with the following performance requirements:

- a. the concentration of oxygen in the undiluted flue gas leaving the secondary combustion chamber of the Equipment, as recorded by the Continuous Monitoring System, shall not be less than 6 percent by volume on a dry basis, calculated as a 10-minute average;
- b. the half-hour average concentration of carbon monoxide in the undiluted flue gases leaving the secondary combustion chamber of the Equipment, as recorded by the Continuous Monitoring System, shall not exceed 100 parts per million by volume, on a dry basis normalized to 11 percent oxygen; and
- c. the concentration of organic matter in the combustion gases leaving the secondary chamber of the Equipment, expressed as equivalent methane (Total Hydrocarbon Compounds), being an average of ten measurements taken at approximately one minute intervals, shall not exceed 100 parts per million by volume, on an undiluted basis.

3. NOISE

1. The Company shall, at all times, ensure that the noise emissions from the Facility comply with the limits set out in Ministry Publication NPC-300.

4. OPERATION AND MAINTENANCE

1. The Company shall ensure that the Facility/Equipment is properly operated and maintained at all times. The Company shall:
 - a. prepare not later than three (3) months after the date of this Approval, and update, as necessary, a Manual outlining the operating procedures and a maintenance program for the Equipment, including as a minimum:
 - i. procedures to ensure that only Non-Infectious Remains of Companion Pets are processed in the Equipment;
 - ii. operating and maintenance procedures in accordance with good engineering practice, including annual inspection procedures as recommended by the Equipment and Continuous Monitoring System suppliers;
 - iii. emergency procedures;
 - iv. procedures to control all discharges from the Equipment in the event of loss or failure of power source to the Equipment;
 - v. procedures for any record keeping activities relating to the operation and maintenance of the Equipment and the Continuous Monitoring System;

- vi. procedures for operator training which is to be provided by an individual experienced with the Equipment;
 - vii. procedures for recording and responding to complaints regarding the operation of the Equipment; and
 - viii. all appropriate measures to minimize noise, fugitive dust and odorous emissions from all potential sources at the Facility;
- b. implement the recommendations of the Manual.

5. SOURCE TESTING

1. The Company shall perform Source Testing in accordance with the procedure outlined in Schedule A, to determine the rate of emission of Total Suspended Particulate Matter and Total Hydrocarbon Compounds from the representative unit of the Equipment.
2. In the event that the results of the Source Testing required by Condition 5.1 indicate that the concentration of Total Suspended Particulate Matter in the undiluted gas emitted from the Equipment exceeds 20 milligrams per cubic metre on a dry basis, normalized to 11% oxygen at a reference temperature of 25 degrees Celsius and a reference pressure of 101.3 kilopascals, the Company shall perform a second Source Testing in accordance with the procedure outlined in Schedule A, to determine the rate of emissions of the Test Contaminants listed in Schedule B from the Equipment.

6. CONTINUOUS MONITORING

1. The Company shall, prior to the commencement of operation of the Equipment, install and subsequently conduct and maintain a program to continuously monitor:
 - a. the temperature at the location in the secondary chamber of the Equipment where the minimum retention time of the combustion gases at a minimum temperature of 1,000 degrees Celsius for at least one second is achieved; and
 - b. the carbon monoxide and oxygen concentration in the undiluted flue gas leaving the secondary chamber of the Equipment.
2. The Continuous Monitoring System shall be equipped with continuous recording devices and shall comply with the requirements outlined in the attached Schedules C, D, and E.

7. RECORD RETENTION

1. The Company shall retain, for a minimum of two (2) years from the date of their creation, all records and information related to or resulting from the recording activities required by this Approval. These records shall be made available to staff of the Ministry upon request. The Company shall retain:
 - a. all records on maintenance, repair and inspection of the Equipment and the Continuous Monitoring System;
 - b. all records produced by the Continuous Monitoring System;
 - c. all records of operator training;
 - d. all records on the environmental complaints, including:
 - i. a description, time and date of the incident;
 - ii. wind direction at the time of the incident; and
 - iii. a description of the measures taken to address the cause of the incident and to prevent a similar occurrence in the future;
 - e. daily records of each load processed by the Equipment; and
 - f. description of any upset conditions associated with the operation of the Equipment and remedial action taken.

8. NOTIFICATION OF COMPLAINTS

1. The Company shall notify the District Manager, in writing, of each environmental complaint and the measures taken to address the complaint within two (2) business days of the complaint. The notification shall include:
 - a. a description of the nature of the complaint; and
 - b. the time and date of the incident to which the complaint relates.

SCHEDULE A

Source Testing Procedures

1. The Company shall submit, not later than three (3) months after the commencement of operation of the Equipment, to the Manager a Pre-Test Plan for the Source Testing required under this Approval.
2. Should a second Source Testing be required, the Company shall submit, not later than three (3) months after the completion of the first Source Testing, or a date agreed upon in consultation with the District Manager, to the Manager a Pre-Test Plan for the Source Testing required under this Approval.
3. The Company shall finalize the Pre-Test Plan in consultation with the Manager.
4. The Company shall complete the Source Testing, no later than three (3) months after the Manager has approved the Pre-Test Plan, or a date agreed upon in consultation with the District Manager.
5. The Company shall notify the Manager, the District Manager and the Director in writing of the location, date and time of any impending Source Testing required by this Approval, at least fifteen (15) days prior to the Source Testing.
6. The Company shall submit a report (electronic format) on the Source Testing to the Manager, District Manager and the Director not later than three (3) months after completing the Source Testing. The report shall be in the format described in the Source Testing Code, and shall also include, but not be limited to:
 1. an executive summary;
 2. records of operating conditions at the time of Source Testing, including but not limited to the following:
 - a. production data; and
 - b. Facility/process information related to the operation of the Equipment;
 3. all records produced by the Continuous Monitoring System;
 4. all records of the cremator settings during cremation;
 5. results of the Source Testing, including the emission rate and emission concentration of the Test Contaminants; and
 6. a tabular comparison of calculated emission rates based on Source Testing results for the Test Contaminants to relevant estimates described in the ESDM Report.

7. The Director may not accept the results of the Source Testing if:
 1. the Source Testing Code or the requirements of the Manager were not followed; or
 2. the Company did not notify the Manager, the District Manager and the Director of the Source Testing; or
 3. the Company failed to provide a complete report on the Source Testing.
8. If the Director does not accept the results of the Source Testing, the Director may require re-testing. If re-testing is required, the Pre-Test Plan strategies need to be revised and submitted to the Manager for approval. The action taken to minimize the possibility of the Source Testing results not being accepted by the Director must be noted in the revision.
9. The Company shall update their ESDM Report in accordance with Section 26 of O. Reg. 419/05 and the Procedure Document with the results from the Source Testing if any of the calculated emission factors or calculated emission rates are higher than the predicted rates in the ESDM Report, not later than three (3) months after the submission of the Source Testing report and make these records available for review by staff of the Ministry upon request.

SCHEDULE B

Test Contaminants

- Total Hydrocarbon Compounds
- Hydrogen Chloride
- Total Suspended Particulate Matter
- Benzo(a)pyrene
- Naphthalene
- Acrolein

List of Dioxins, Furans and Dioxin-like PCBs

- 2,3,7,8-Tetrachlorodibenzo-p-dioxin [2,3,7,8-TCDD]
- 1,2,3,7,8-Pentachlorodibenzo-p-dioxin [1,2,3,7,8-PeCDD]
- 1,2,3,4,7,8-Hexachlorodibenzo-p-dioxin [1,2,3,4,7,8-HxCDD]
- 1,2,3,6,7,8-Hexachlorodibenzo-p-dioxin [1,2,3,6,7,8-HxCDD]
- 1,2,3,7,8,9-Hexachlorodibenzo-p-dioxin [1,2,3,7,8,9-HxCDD]
- 1,2,3,4,6,7,8-Heptachlorodibenzo-p-dioxin [1,2,3,4,6,7,8-HpCDD]
- 1,2,3,4,6,7,8,9-Octachlorodibenzo-p-dioxin [1,2,3,4,6,7,8,9-OCDD]
- 2,3,7,8-Tetrachlorodibenzofuran [2,3,7,8-TCDF]
- 2,3,4,7,8-Pentachlorodibenzofuran [2,3,4,7,8-PeCDF]
- 1,2,3,7,8-Pentachlorodibenzofuran [1,2,3,7,8-PeCDF]
- 1,2,3,4,7,8-Hexachlorodibenzofuran [1,2,3,4,7,8-HxCDF]
- 1,2,3,6,7,8-Hexachlorodibenzofuran [1,2,3,6,7,8-HxCDF]
- 1,2,3,7,8,9-Hexachlorodibenzofuran [1,2,3,7,8,9-HxCDF]
- 2,3,4,6,7,8-Hexachlorodibenzofuran [2,3,4,6,7,8-HxCDF]
- 1,2,3,4,6,7,8-Heptachlorodibenzofuran [1,2,3,4,6,7,8-HpCDF]
- 1,2,3,4,7,8,9-Heptachlorodibenzofuran [1,2,3,4,7,8,9-HpCDF]
- 1,2,3,4,6,7,8,9-Octachlorodibenzofuran [1,2,3,4,6,7,8,9-OCDF]
- 3,3',4,4'-Tetrachlorobiphenyl [3,3',4,4'-tetraCB (PCB 77)]
- 3,4,4',5- Tetrachlorobiphenyl [3,4,4',5-tetraCB (PCB 81)]
- 3,3',4,4',5- Pentachlorobiphenyl (PCB 126) [3,3',4,4',5-pentaCB (PCB 126)]
- 3,3',4,4',5,5'- Hexachlorobiphenyl [3,3',4,4',5,5'-hexaCB (PCB 169)]
- 2,3,3',4,4'- Pentachlorobiphenyl [2,3,3',4,4'-pentaCB (PCB 105)]
- 2,3,4,4',5- Pentachlorobiphenyl [2,3,4,4',5-pentaCB (PCB 114)]
- 2,3',4,4',5- Pentachlorobiphenyl [2,3',4,4',5-pentaCB (PCB 118)]
- 2',3,4,4',5- Pentachlorobiphenyl [2',3,4,4',5-pentaCB (PCB 123)]
- 2,3,3',4,4',5- Hexachlorobiphenyl [2,3,3',4,4',5-hexaCB (PCB 156)]
- 2,3,3',4,4',5'- Hexachlorobiphenyl [2,3,3',4,4',5'-hexaCB (PCB 157)]
- 2,3',4,4',5,5'- Hexachlorobiphenyl [2,3',4,4',5,5'-hexaCB (PCB 167)]
- 2,3,3',4,4',5,5'- Heptachlorobiphenyl [2,3,3',4,4',5,5'-heptaCB (PCB 189)]

SCHEDULE C

Continuous Temperature Monitoring System

PARAMETER:

Temperature

LOCATION:

The sample point for the Continuous Temperature Monitor shall be located in the secondary chamber where the minimum retention time of the combustion gases at a minimum temperature of 1,000 degrees Celsius for at least one second is achieved.

PERFORMANCE:

The Continuous Temperature Monitor shall meet the following minimum performance specifications for the following parameters:

PARAMETERS	SPECIFICATION
Type	shielded "K" type thermocouple, or equivalent
Accuracy	± 1.5 percent of the minimum gas temperature

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitoring system without a significant loss of accuracy and with a time resolution of 1 minute or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 95 percent of the time for each calendar quarter.

SCHEDULE D

Continuous Oxygen Monitoring System

PARAMETER:

Oxygen

INSTALLATION:

The Continuous Oxygen Monitor shall be installed at an accessible location where the measurements are representative of the actual concentration of oxygen in the undiluted gases leaving the secondary chamber of the Equipment and shall meet the following installation specifications:

PARAMETERS	SPECIFICATION
Range (percentage)	0 to 20 or 0 to 25
Calibration Gas Ports	close to the sample point

PERFORMANCE:

The Continuous Oxygen Monitor shall meet the following minimum performance specifications for the following parameters:

PARAMETERS	SPECIFICATION
Span Value (percentage)	80 to 100 percent of full scale
Relative Accuracy	the greater of less than or equal to 10 percent of the mean value of the reference method test data or 0.5 percent O ₂ average absolute difference
Calibration Error	0.5 percent O ₂
System Bias	the greater of less than or equal to 4 percent of the mean value of the reference method test data or 0.5 percent O ₂ average absolute difference
Procedure for Zero and Span Calibration Check	all system components checked
Zero Calibration Drift (24-hour)	less than or equal to 0.5 percent O ₂
Span Calibration Drift (24-hour)	less than or equal to 0.5 percent O ₂
Response Time (90 percent response to a step change)	less than or equal to 180 seconds
Operational Test Period	at least 168 hours without corrective maintenance

CALIBRATION:

Daily calibration drift checks on the monitor shall be performed and recorded in accordance with the requirements of Report EPS 1/PG/7.

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitor with an accuracy of 0.5 percent of a full scale reading or better and with a time resolution of 2 minutes or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 90 percent of the time for each calendar quarter during the first full year of operation, and 95 percent, thereafter.

SCHEDULE E

Continuous Carbon Monoxide Monitoring System

PARAMETER:

Carbon Monoxide

INSTALLATION:

The Continuous Carbon Monoxide Monitor shall be installed at an accessible location where the measurements are representative of the actual concentration of carbon monoxide in the undiluted gases leaving the secondary chamber of the Equipment and shall meet the following installation specifications:

PARAMETERS	SPECIFICATION
Range (parts per million, ppm)	0 to \geq 200
Calibration Gas Ports	close to the sample point

PERFORMANCE:

The Continuous Carbon Monoxide Monitor shall meet the following minimum performance specifications for the following parameters:

PARAMETERS	SPECIFICATION
Span Value (nearest ppm equivalent)	80 to 100 percent of full scale
Relative Accuracy	the greater of less than or equal to 10 percent of the mean value of the reference method test data or 5 ppm average absolute difference
Calibration Error	less than or equal to 2 percent of the actual concentration
System Bias	the greater of less than or equal to 4 percent of the mean value of the reference method test data or 5 ppm average absolute difference
Procedure for Zero and Span Calibration Check	all system components checked
Zero Calibration Drift (24-hour)	less than or equal to 5 percent of span value
Span Calibration Drift (24-hour)	less than or equal to 5 percent of span value
Response Time (90 percent response to a step change)	less than or equal to 180 seconds
Operational Test Period	at least 168 hours without corrective maintenance

CALIBRATION:

Daily calibration drift checks on the monitor shall be performed and recorded in accordance with the requirements of Report EPS 1/PG/7.

DATA RECORDER:

The data recorder must be capable of registering continuously the measurement of the monitor with an accuracy of 0.5 percent of a full scale reading or better and with a time resolution of 2 minutes or better.

RELIABILITY:

The monitor shall be operated and maintained so that accurate data is obtained during a minimum of 90 percent of the time for each calendar quarter during the first full year of operation, and 95 percent, thereafter

The reasons for the imposition of these terms and conditions are as follows:

1. OPERATING PARAMETERS, EMISSION CONCENTRATION LIMITS, AND NOISE

Conditions No. 1, 2 and 3 are included to provide the minimum performance requirements considered necessary to prevent an adverse effect resulting from the operation of the Facility/Equipment.

2. OPERATION AND MAINTENANCE

Condition No. 4 is included to emphasize that the Equipment must be operated and maintained according to a procedure that will result in compliance with the EPA, the regulations and this Approval.

3. SOURCE TESTING AND CONTINUOUS MONITORING

Conditions No. 5 and 6 are included to require the Company to gather accurate information so that the environmental impact and subsequent compliance with the EPA, the regulations and this Approval can be verified.

4. RECORD RETENTION

Condition No. 7 is included to require the Company to keep records and provide information to the Ministry so that the environmental impact and subsequent compliance with the EPA, the regulations and this Approval can be verified.

5. NOTIFICATION OF COMPLAINTS

Condition No. 8 is included to require the Company to notify staff of the Ministry so as to assist the Ministry with the review of the site's compliance.

In accordance with Section 139 of the *Environmental Protection Act*, you may by written notice served upon me, the Ontario Land Tribunal and in accordance with Section 47 of the *Environmental Bill of Rights, 1993*, the Minister of the Environment, Conservation and Parks, within 15 days after receipt of this notice, require a hearing by the Tribunal. The Minister of the Environment, Conservation and Parks will place notice of your appeal on the Environmental Registry. Section 142 of the *Environmental Protection Act* provides that the notice requiring the hearing ("the Notice") shall state:

- a. The portions of the environmental compliance approval or each term or condition in the environmental compliance approval in respect of which the hearing is required, and;
- b. The grounds on which you intend to rely at the hearing in relation to each portion appealed.

The Notice should also include:

1. The name of the appellant;
2. The address of the appellant;
3. The environmental compliance approval number;
4. The date of the environmental compliance approval;
5. The name of the Director, and;
6. The municipality or municipalities within which the project is to be engaged in.

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

Registrar*
Ontario Land Tribunal
655 Bay Street, Suite 1500
Toronto, Ontario
M5G 1E5
OLT.Registrar@ontario.ca

and

The Minister of the Environment,
Conservation and Parks
777 Bay Street, 5th Floor
Toronto, Ontario
M7A 2J3

and


The Director appointed for the purposes of
Part II.1 of the *Environmental Protection Act*
Ministry of the Environment,
Conservation and Parks
135 St. Clair Avenue West, 1st Floor
Toronto, Ontario
M4V 1P5

* **Further information on the Ontario Land Tribunal's requirements for an appeal can be obtained directly from the Tribunal at: Tel: (416) 212-6349 or 1 (866) 448-2248, or www.olt.gov.on.ca**

This instrument is subject to Section 38 of the *Environmental Bill of Rights*, 1993, that allows residents of Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek leave to appeal within 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry at <https://ero.ontario.ca/>, you can determine when the leave to appeal period ends.

The above noted activity is approved under s.20.3 of Part II.1 of the *Environmental Protection Act*.

DATED AT TORONTO this 25th day of January, 2024



Nancy E Orpana, P.Eng.

Director

appointed for the purposes of Part II.1 of the
Environmental Protection Act

TC/

c: District Manager, MECP London - District
Akhter Iqbal, WSP E&I Canada Limited