

Guideline for Quantification, Reporting and Verification of Greenhouse Gas Emissions

March 2024

Guideline for Quantification, Reporting and Verification of Greenhouse Gas Emissions

Ministry of the Environment, Conservation and Parks

Guideline Version March 2024. This Guideline is only available in English.

Cette publication hautement spécialisée *Guideline for Quantification, Reporting and Verification of Greenhouse Gas Emissions* n'est disponible qu'en anglais conformément au Règlement 671/92, selon lequel il n'est pas obligatoire de la traduire en vertu de la *Loi sur les services en français*. Pour obtenir des renseignements en français, veuillez communiquer avec le ministère de l'Environnement, de la Protection de la nature et des Parcs au ghgreporting@ontario.ca.

TABLE OF CONTENTS

1. INTRODUCTION	4
2. DEFINITIONS	4
3. STANDARD QUANTIFICATION METHODS	15
4. TECHNICAL REFERENCE DOCUMENTS	16
5. APPLICABILITY	21
6. ACTIVITY COMPONENTS AND EPS PARAMETERS	21
7. PARTIAL YEAR ADJUSTMENT TO VERIFICATION AMOUNT	32
ON.50 ADIPIC ACID PRODUCTION	36
ON.70 ALUMINIUM PRODUCTION	42
ON.80 AMMONIA PRODUCTION	46
ON.260 BASE METAL PRODUCTION	49
ON.180 CARBONATE USE	51
ON.90 CEMENT PRODUCTION	55
ON.110 CO ₂ CAPTURE, CO ₂ TRANSPORT, CO ₂ INJECTION AND CO ₂ STORAGE.....	57
ON.100 COAL STORAGE.....	60
ON.40 ELECTRICITY AND HEAT GENERATION	63
ON.60 ELECTRICITY IMPORTATION	64
ON.20 FUEL COMBUSTION AND FLARING	68
ON.140 GLASS PRODUCTION	82
ON.120 HCFC-22 PRODUCTION AND HFC-23 DESTRUCTION	87
ON.130 HYDROGEN PRODUCTION	88
ON.150 IRON, STEEL AND FERROALLOY PRODUCTION	90
ON.170 LIME PRODUCTION	103
ON.290 MAGNESIUM PRODUCTION	105
ON.310 NITRIC ACID PRODUCTION	110
ON.230 OPERATION OF EQUIPMENT FOR A TRANSMISSION SYSTEM OR A DISTRIBUTION SYSTEM (ELECTRICITY)	114
ON.350 OPERATION OF A NATURAL GAS PIPELINE SYSTEM.....	121
ON.190 OTHER EMISSIONS	163
ON.300 PETROCHEMICAL PRODUCTION	165
ON.200 PETROLEUM REFINING	172
ON.340 PHOSPHORIC ACID PRODUCTION	179
ON.210 PULP AND PAPER PRODUCTION	180
ON.220 SODA ASH PRODUCTION	182
ON.270 WASTE WATER PROCESSING	183

1. Introduction

Where the Regulation requires the use of standard quantification methods to quantify greenhouse gas emissions from an activity, those standard quantification methods are set out in the table in Section 3 of this Guideline.

Section 4 of the Guideline lists the technical reference documents referred to within the standard quantification methods.

Section 5 of the Guideline describes the applicability of the Guideline.

Section 6 of the Guideline sets out the activity components and EPS parameters that a covered facility may be required to report and sets out the applicable sampling, analysis and measurement requirements.

Section 7 of the Guideline describes the requirements for calculations of the verification amount for the purposes of subsections 12 (7) and (8) of the Regulation.

2. Definitions

For the purposes of this Guideline:

"Abrasives" means paper that is coated with resin mixture and sand, that is subsequently shipped from the facility.

"Act" means the *Environmental Protection Act, R.S.O. 1990, Chapter E.19*.

"Activity component" has the same meaning as the Regulation.

"Aluminium poured" means aluminium poured to make parts in a non-ferrous metal die-casting foundry.

"Aluminium alloys" means aluminium alloys produced through remelting of recycled scrap aluminium.

"Ammonia" means ammonia produced through the reaction of nitrogen with hydrogen that has been produced by steam hydrocarbon reforming or gasification of solid or liquid raw material.

"Annealed steel" or **"Finished steel - annealed"** means steel shapes that are held at a controlled temperature where crystallization occurs followed by cooling at a controlled rate.

"Annual electrical energy output from the cogeneration system" means the gross electricity generation from the cogeneration system, expressed in gigajoules (GJ) per year.

"Annual electricity generated" means the gross electricity generation expressed in gigawatt hours (GWh) per year.

"Annual total energy output from the cogeneration system" means the sum of:

- a) gross electricity generation from the cogeneration system, expressed in gigajoules (GJ) per year, plus
- b) the useful thermal energy that is generated from a cogeneration system, expressed in gigajoules (GJ) per year.

“Annual useful thermal energy that is generated from a combustion device and transferred” means useful thermal energy that is generated from a combustion device and transferred to any other covered facility or non-covered facility.

“Annual useful thermal energy output from the cogeneration system” means the useful thermal energy that is generated from a cogeneration system, expressed in gigajoules (GJ) per year.

"Baked goods" means finished baked food products including bread, English muffins, bagels, rolls, and tortillas.

“Barrel” (“bbl”) means a volume equal to 42 U.S. gallons.

"Beans and seeds crushed" means canola and soybeans crushed to produce finished oilseeds products for human or animal consumption.

“Beverage ethanol” means ethanol produced by distillation for use in the production of alcoholic beverages.

“Cal-85” means a high calcium byproduct generated during the production of quicklime or lime.

“Calcined byproduct/waste type” means Cal-85, lime kiln dust, waste lime and other partially calcined materials and co-products generated during the production of quicklime or lime.

“CAN-CWB” means direct Canadian Complexity Weight Barrel.

“Canada’s Greenhouse Gas Quantification Requirements” or “GGQR” means the document entitled “Canada’s Greenhouse Gas Quantification Requirements”, Greenhouse Gas Reporting Program, published by Environment and Climate Change Canada, as amended from time to time.

"Canned food items" means canned food items including tomato paste, crushed tomatoes, pasta sauces, pizza sauces, ketchup, whole/diced tomatoes and beans.

"Capsules" means enclosing of chemical active ingredients, adhesives in capsules.

"Carbon and alloy steel cast billets" means carbon and alloy steel billets cast from liquid steel produced at the facility.

"Carbon and alloy steel ingots" means carbon and alloy steel ingots produced from liquid steel produced at the facility.

“Carbon black” means carbon pellets, powders or other products produced by the pyrolysis of hydrocarbon feedstock.

“Cement kiln dust” (“CKD”) means the fine-grained, solid, highly alkaline waste consisting of partly calcined kiln feed material, dust from cement kilns and bypass systems, including bottom ash and bypass dust removed from cement kiln exhaust gas by air pollution control devices.

“Citric acid” means citric acid produced by fermentation at a facility.

“Clinker” means the mass of fused material produced in a cement kiln from which finished cement is manufactured by milling and grinding.

“Coal tar distillation products” means products calculated as the difference between the mass of coal tar feedstock and final residues such as coal tar pitch.

“Coils” means coils of finished steel wire.

“Cogeneration system” means individual cogeneration components including the prime mover (heat engine), generator, heat recovery, and electrical interconnection, configured into an integrated system that provides sequential generation of multiple forms of useful energy (usually electrical and thermal), and where at least one form of the useful thermal energy is consumed on-site for an end use other than electricity generation or is made available to other users for an end-use other than electricity generation.

“Combustion emissions” means greenhouse gas emissions occurring during the exothermic reaction of a fuel with oxygen.

“Confectionery products” means manufactured confectionery food products including Nutella, Nutella and Go, Rocher and Tic Tac Mints.

“Consensus Based Standards Organization” means ASTM International, the American Gas Association (AGA), the American Petroleum Institute (API), the CSA Group, the Gas Processing Association of Canada (GPAC), GPA Midstream Association, the Canadian General Standards Board, GPSA Midstream Suppliers, the American National Standards Institute (ANSI), the American Society of Mechanical Engineers (ASME), the American Petroleum Institute (API), the North American Energy Standards Board (NAESB), International Organization for Standardization (ISO), Environment and Climate Change Canada, United States Environmental Protection Agency, British Standards Institution, or Measurement Canada.

“Continuous emissions monitoring system (CEMS)” means the total equipment required to obtain a continuous measurement of a gas concentration or emission rate from combustion or industrial processes.

“Corn germ processed” means corn germ processed to expel and refine corn oil at a facility.

“Corn milled” means corn wet-milled or ground at a facility.

“Direct Reduction Furnace” means a high temperature furnace typically fired with natural gas to produce solid iron from iron ore or iron ore pellets and carbonaceous materials.

“Direct reduced iron” means iron produced from a direct reduction furnace.

“Direct strip steel” means steel produced by direct strip casting, expressed as tonnes.

“Director” has the same meaning as in the Regulation.

“Dolomitic quicklime or dolomitic lime” means a lime product containing 50 to 65 per cent calcium oxide and 35 to 46 per cent magnesium oxide and is derived from dolomitic limestone.

“Double burnt lime” means a specially sintered or double-burned form of dolomitic quicklime fines and pelletized fine that are further stabilized by the addition of iron.

“Drivers” means an electric motor, reciprocating engine or turbines used to drive a compressor.

“Electricity generated at LSP” means electricity generated from equipment at the facility with GHG ID 1042, which is located in the portion of the facility that is formerly associated with GHG ID 1014 (Lake Superior Power).

“Emission factors” (“EF”) means the rate at which a pollutant is released into the atmosphere (or captured) as a result of some process activity or unit throughput.

“Engineering estimates” means estimating emissions from engineering principles and judgment, using knowledge of the chemical and physical processes involved, the design features of the activity, and an understanding of the applicable physical and chemical laws.

“EPS parameter” has the same meaning as the Regulation.

“EPS Regulation” means O. Reg. 241/19 - Greenhouse Gas Emission Performance Standards made under the Act

“Equipment leak” means fugitive greenhouse gas emissions from equipment including valves, pump seals, flanges, compressors, sampling connections, and open-ended lines and excluding storage tank emissions.

“Ethylene” means the ethylene produced from the processing of natural gas liquids or feedstock from the refining of crude oil and its derivatives.

“Evaporated salt” means commercial, agricultural, and industrial salt products produced through solution mining.

"Expanded polystyrene" means polystyrene produced by heating polystyrene beads with heat or steam.

"Finished metal product" means metal which is processed through different combinations of finishing processes at the Ingersoll site of the facility with GHG ID 1527, including machining, banding, heat treating, cleaning and painting.

"Finished metal – heat treated" means metal shapes that are held at a controlled temperature followed by cooling at a controlled rate at the Port Robinson site with GHG ID 1527.

"Finished oilseed products" means products derived from oilseeds for human or animal consumption.

"Finished product(s)" means the production of pulp, paper or other product derived directly from pulp or pulping process.

- a) in the case of pulp:
 - i. if the moisture content exceeds 10 per cent, the weight of the pulp after it is adjusted so that its moisture content does not exceed 10 per cent, or
 - ii. if the moisture content is equal to or less than 10 per cent, the weight of the pulp without adjustment.
- b) in the case of a product derived directly from pulp or the pulping process, the weight of the product or, if it has been machine dried, its weight after it has been dried.

"Finished steel - heat treated" means steel shapes that are held at a controlled temperature followed by cooling at a controlled rate, excluding the amount that is annealed.

"Finished steel product" means the following:

- a) At the facility with GHG ID 1148, the total steel that is processed through annealing, cold rolling and/or zinc coating;
- b) At the facility with GHG ID 1149, the steel that is pickled;
- c) At the facility with GHG ID 1136, the steel that is processed through annealing, tempering, drawing, cold rolling, galvanizing, zinc coating or pickling;
- d) At the facility with GHG ID 1084, the steel that is processed through annealing, drawing, or cleaning and shipped; and
- e) At the facility with GHG IDs 1005 and 1225, pickled and cold rolled steel.

"Flexigas" means a low heat content gaseous fuel produced through the gasification of coke.

“Fluid coking” means a thermal cracking process utilizing the fluidized-solids technique to remove carbon (coke) for continuous conversion of heavy, low-grade oils into lighter products.

“Forged steel” means steel produced by shaping of steel and metals using localized compressive forces.

“Forged metal” means shaping of metals using localized compressive forces at the Port Colborne site of the facility with GHG ID 1527.

“Fuel analytical data” means any data collected about the mass, volume, flow rate, heat content, or carbon content of a fuel.

“Fuel ethanol” means ethyl alcohol used as automotive fuel that is biomass derived from a grain, starch or cellulosic material feedstock and denatured in accordance with Canadian Excise Tax Act or, where it originates in the United States denatured in accordance with the criteria specified in ASTM D4806.

“Fuel gas system” means a system of compressors, piping, knock-out pots, mix drums, sulphur removal units and flaring units that collects fuel gas from one or more sources for treatment, and transports it to a stationary combustion unit.

“Fumaric acid” means fumaric acid produced for use as an industrial or food additive.

“Galvanized steel” means application of a zinc coating by immersion of the steel in a zinc bath, expressed as tonnes.

“GGQM” means the quantification methods in GGQR.

“GJ” means gigajoules or billion joules.

“Gold bearing ore” means the mass of naturally occurring material that is extracted from the ground for the purpose of gold mining activities and is processed by a mill.

“Gold mined and milled” means the production of gold from the mining and milling of ore.

“Gold produced” is defined as the production of gold from the mining or milling of ore.

“Grey cement” means a mix composed of clinker, gypsum and limestone, where the clinker:

- a) contains more than 0.5 per cent by weight of ferric oxide; and
- b) is produced at the covered facility in the year it is mixed with gypsum and limestone.

“Guideline” has the same meaning as in the Regulation.

“Gypsum panels” means gypsum panels made of gypsum plaster pressed between sheets of paper or fibreglass mat.

“Heat-treated steel tubing” means steel tubing that is processed by heating steel shapes at a controlled temperature followed by cooling at a controlled rate.

“High calcium hydrated lime”, means a lime product produced by combining quicklime with a sufficient quantity of water.

“High calcium quicklime or lime”, means a lime product containing 75 to 98 per cent calcium oxide and 0 to 5 per cent magnesium oxide.

“High heat value” (“HHV”) means the amount of heat energy released by the combustion of a unit quantity of a fuel, including the latent heat of vaporization of water embedded in the fuel.

“Hot rolled steel” means hot rolled steel produced from the reheat furnace at the facility.

“Hot rolled steel at the facility with GHG ID 1042” means hot rolled steel produced from the reheat furnace(s) at the facility, excluding steel produced by direct strip steel casting, expressed as tonnes.

“Hydrogen produced” means hydrogen produced using steam hydrocarbon reforming or partial oxidation of hydrocarbon at a facility dedicated to the production of hydrogen gas, and not at a covered facility that carries out an activity described in items 4, 13, 13.1, 13.2, 13.3, 13.4, 13.5 and 24 of Schedule 2 of the EPS Regulation.

“Hydrogen produced at a petroleum refinery” means hydrogen produced using steam hydrocarbon reforming or partial oxidation of hydrocarbon at a covered facility that carries out the activity described in item 4 of Schedule 2 of the EPS Regulation.

“Industrial ethanol” means all distilled ethyl alcohol (C₂H₅OH) other than fuel ethanol, produced and distributed in the form of pure ethyl alcohol, beverage grade alcohol, completely denatured alcohol, specially denatured alcohol and proprietary solvent blends.

“Intermediate clinker” means clinker that is produced at the covered facility in the year and is not mixed at the covered facility in the same year it is produced with gypsum and limestone to produce grey cement.

“Internal combustion engine” means internal combustion engines including engines that are hybrids.

“Iron coated dolime” is less than one centimeter dolomitic lime impregnated with a hard layer of iron oxide as a flux in steel making.

“Kiln” means thermally insulated chambers, or ovens, in which controlled temperature regimes are produced, used in the production of clinker, lime

and other products, and which includes any associated preheater or precalciner devices.

“**LABS**” refers to litres of absolute alcohol (excluding water, additives and denaturants).

“**Lime kiln dust**” (“**LKD**”) means lime dust generated during the production of quicklime or lime.

“**Lime type**” means the following types of quicklime or lime derived from limestone containing varying percentages of magnesium carbonate:

- a) Dolomitic quicklime or dolomitic lime;
- b) Double burnt lime;
- c) High calcium hydrated lime;
- d) High calcium quicklime or high calcium lime; and
- e) Iron coated dolime.

“**Low Heat Value**” (“**LHV**”) means the heat energy released through the combustion of a unit quantity of fuel, excluding the latent heat of vaporization of water embedded in the fuel.

“**Mass balance**” means the application of the law of conservation of mass to a facility, process or piece of equipment to determine emissions based on the difference in the input and output of a unit operation, where the accumulation and depletion of a substance are included in the calculations.

“**Malic acid**” means malic acid produced for use as an industrial or food additive.

“**Masking tape**” means tape that is marketed as masking tape.

“**Medical tape**” means tape that is marketed as for medical use.

“**Megawatt hours of work**” means the sum of production of drivers expressed in megawatt hours at the facility calculated in accordance with the Quantification of Production requirements for Natural Gas Transmissions under the Canada’s Output Based Pricing System Regulation and including drivers used to generate electricity.

“**Mined material**” is defined as the mass of naturally occurring material that is extracted from the ground for the purpose of gold mining activities.

“**Mineral wool**” means fibers produced from basalt rock and slag melted in a cupola at the facility but does not include glass wool.

“**MJ**” means mega joules or one million joules.

“**MPMD**” means 2-methylpentamethylenediamine.

"Nepheline syenite" means production of nepheline syenite from the mining or milling of nepheline ore where nepheline syenite is an inert granite-like rock which contains no free-silica.

"Nickel matte" means nickel matte produced from pyrometallurgical smelting.

"Nitric acid" means nitric acid that is 30 to 70 per cent in strength produced using the catalytic oxidation of ammonia.

"Non-calcined calcium oxide" means calcium oxide that remains in the clinker or CKD in the form of CaCO_3 and calcium oxide in the clinker or CKD that entered the kiln as a non-carbonate species.

"Non-calcined magnesium oxide" means magnesium oxide that remains in the clinker or CKD in the form of MgCO_3 and magnesium oxide in the clinker or CKD that entered the kiln as a non-carbonate species.

"Nylon 6 resins chips" means nylon 6 resin in the form of chips made from pure, recycled, and recovered caprolactam.

"Nylon resins" means resins of Nylon 6 or Nylon 6,6.

"Nylon fibres" means fibres of Nylon 6 or Nylon 6,6.

"On-site transportation emissions" means emissions from machinery used for the transport or movement of substances, materials, equipment or products that are used in the production process at a facility where those emissions have resulted from the combustion of fuel delivered in a delivery to which an exemption certificate referred to in section 36 of the *Greenhouse Gas Pollution Pricing Act* (Canada) applies, containing a declaration described in subparagraph 36 (1) (b) (v) of that Act.

"Ontario Regulation 143/16" has the same meaning as in the Regulation.

"Ontario Regulation 452/09" has the same meaning as in the Regulation.

"Palladium and platinum" means palladium and platinum produced by milling and concentrating via flotation of ore extracted from surface and underground mining.

"Petroleum coke" means a solid residue consisting mainly of carbon which is derived either from the cracking of petroleum hydrocarbons in a refinery coker unit (petroleum coke) or from the destructive distillation of low-ash, low-sulphur bituminous coal (coal coke).

"Polyethylene" means polyethylene made from polymerization of ethylene at the facility, including all saleable prime and off-grade polyethylene but excluding scrap ethylene.

"Prime mover" means equipment such as an engine or water wheel that drives an electric generator and includes, but is not limited to, reciprocating

engines, combustion or gas turbines, steam turbines, microturbines, and fuel cells.

“Process gas” means blast furnace gas or coke oven gas from a blast furnace or coke oven located at a facility at which iron and steel production is engaged in.

“Process vent” means an opening where a gas stream is continuously or periodically discharged during normal operation.

“Products from steam cracker” means hydrogen gas, ethylene, propylene, butadiene and pyrolysis gas that are produced from steam cracking.

“Pulp” means market pulp produced from chemical recovery, semi-chemical recovery or thermal mechanical processes.

“Paper” means paper products including newsprint, paperboard products and converted paper products.

“Propane and butane” means combined volume of propane and butane at a temperature of 15 degrees Celsius and at an equilibrium pressure.

“Quicklime” means a substance that consists of oxides of calcium and magnesium resulting from the calcination of limestone or other highly calcareous materials such as aragonite, chalk, coral, marble and shell.

“Raw sugar processed” means sugar used as a raw material that is further refined or melted.

“Refinery feed” means feedstock used to produce lubricant base oil products.

“Rm³” or **“reference cubic metre”** means the amount of gas that would occupy a volume of one cubic metre under reference temperature and pressure conditions.

“Regulation” means O. Reg. 390/18 made under the Act.

“Rubber” means rubber produced from a butyl manufacturing process.

“Scotch-Brite” means products marketed as Scotch-Brite that are produced through the process of coating, curing, lamination and slitting of a non-woven web.

“Sinter machine” means equipment that is composed of a continuous traveling grate that conveys a bed of ore fines and other finely divided iron-bearing material and fuel (typically coke breeze), a burner at the feed end of the grate for ignition, and a series of downdraft windboxes along the length of the strand to support downdraft combustion and heat sufficient to produce a fused sinter product.

"Sinter production" means a process that uses a sinter machine to produce a fused aggregate of fine iron-bearing materials suited for use in a blast furnace.

"Stainless steel cast billets" means stainless steel billets casted from liquid steel produced at the facility.

"Stainless steel ingots" means stainless steel ingots produced from liquid steel produced at the facility.

"Standard conditions" means either a temperature of 15 degrees Celsius and a pressure of 101.325 kPa unless otherwise stated in the standard quantification methods or an applicable Technical Reference Document.

"Standard Temperature and Pressure" or **"STP"** has the same meaning as standard conditions.

"Standard cubic meter" or **"Sm³"** means the amount of gas that would occupy a volume of one cubic metre under standard conditions.

"Steel products at the facility with GHG ID 1412" means steel that is hot rolled and subsequently shipped from the facility.

"Stocked tires" means radial tires for cars and light trucks manufactured at a facility.

"Styrene" means styrene produced using a two-step catalytic process which involves the alkylation of benzene with ethylene to produce ethylbenzene followed by dehydrogenation of the ethylbenzene to produce styrene.

"Sulphur recovery unit" (**"SRU"**) means a process unit that recovers elemental sulphur from gases that contain reduced sulphur compounds and other pollutants, usually by a vapor-phase catalytic reaction of sulphur dioxide and hydrogen sulfide.

"Tape" means adhesive tape produced by extruding, coating and converting of raw material.

"Total synthetic oil, antioxidants, rubber additives and specialty chemicals" means total production from reactionary chemistry to make petroleum additives through various hydrocarbons and synthetic oil.

"Transmission and power train parts" means transmission and power train parts sold.

"Uranium hexafluoride (UF₆) and uranium dioxide (UO₂)" means total uranium hexafluoride (UF₆) and uranium dioxide (UO₂) converted from uranium trioxide (UO₃) produced.

"Uranium trioxide (UO₃)" means uranium trioxide (UO₃) refined from uranium ore.

"Urea" means urea liquor produced at a facility which produces ammonia.

“Used oil feed” means the used oil that is processed in the refinery process units at the facility to produce a base oil that is supplied for blending with other lubricants to create lubricant products that meet lubricant industry standards.

“Vehicles” means four-wheeled self-propelled vehicles that are designed for use on a highway and that have a gross vehicle weight rating of less than 4,536 kg (10,000 pounds).

“Waste derived fuel” has the same meaning as in Regulation 347 of the Revised Regulations of Ontario (General – Waste Management).

“Waste lime” means a byproduct produced by the kiln during the production of quicklime or lime that is not a lime type, Cal-85 or LKD.

“Wax” means wax produced by crystallization, filtration, and solvent recovery of slack wax.

“Wax paper” means wax paper produced by punching and wrapping of paper blanks for souffle cups.

“White cement” means a mix composed of clinker, gypsum and limestone, where the clinker contains 0.5 per cent or less by weight of ferric oxide.

“Zinc and copper concentrate” means copper and zinc concentrate produced from flotation.

“Zinc oxide” means zinc oxide produced in the in-direct French process.

3. Standard Quantification Methods

Where the Regulation requires the use of a standard quantification method, the methods listed in the following table shall be used.

Source of Greenhouse Gas	Standard Quantification Method	Appendix
Adipic acid production	ON.50 – ON.55	1
Aluminium production	ON.70 – ON.75	2
Ammonia production	ON.80 – ON.85	3
Base metal production	ON.260 – ON.265	4
Carbonate use	ON.180 – ON.185	5
Cement production	ON.90 – ON.95	6
CO ₂ Capture, CO ₂ Transport, CO ₂ Injection and CO ₂ Storage	ON.110 - ON.115	7

Source of Greenhouse Gas	Standard Quantification Method	Appendix
Coal storage	ON.100 – ON.105	8
Electricity and heat generation	ON.40 – ON.45	9
Electricity importation	ON.60 – ON.65	10
Fuel combustion and flaring	ON.20 – ON.26	11
Glass production	ON.140 – ON.145	12
HCFC-22 production and HFC-23 destruction	ON.120 – ON.125	13
Hydrogen production	ON.130 – ON.135	14
Iron, steel and ferroalloy production	ON.150 – ON.155	15
Lime production	ON.170 – ON.175	16
Magnesium production	ON.290 – ON.295	17
Nitric acid production	ON.310 – ON.315	18
Operation of equipment for a transmission system or a distribution system (electricity)	ON.230 – ON.235	19
Operation of natural gas pipeline system	ON.350 – ON.356	20
Other emissions	ON.190 – ON.195	21
Petrochemical production	ON.300 – ON.305	22
Petroleum refining	ON.200 – ON.205	23
Phosphoric acid production	ON.340 – ON.345	24
Pulp and paper production	ON.210 – ON.215	25
Soda ash production	ON.220 – ON.225	26
Waste water processing	ON.270 – ON.275	27

4. Technical Reference Documents

All of the methods listed in the “Reference Title” column of the following table are incorporated into the Guideline as amended from time to time and where the Guideline requires the use of one of these methods, the most current version shall be used.

Where the analysis or other measurements specified by the methods in the “Reference Title” column or in any of the methods in the Appendices are not offered by any supplier in Ontario, the person:

- (a) Shall use the most appropriate method published by a consensus-based standards organization; or
- (b) Where no appropriate method is published by a consensus-based standards organization, the person shall use an industry standard method, noting where such methods are used and what methods are used.

Reference Title
Analytical Methods section of the National Lime Association ‘CO ₂ Emissions Calculation Protocol for the Lime Industry English Units Version’
ASM CS-104 UNS No. G10460 “Carbon Steel of Medium Carbon Content”.
ASME Performance Test Codes
ASTM C25 - Standard Test Method for Chemical Analysis of Limestone, quicklime, and Hydrated Lime
ASTM D70 - Standard Test Method for Density of Semi-Solid Asphalt Binder (Pycnometer Method)
ASTM C114 - Standard Test Methods for Chemical Analysis of Hydraulic Cement
ASTM D240 - Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimetre
ASTM D1298 - Standard Test Method for Density, Relative Density, or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method
ASTM D1826 - Standard Test Method for Calorific (Heating) Value of Gases in Natural Gas Range by Continuous Recording Calorimetre
ASTM D1945 - Standard Test Method for Analysis of Natural Gas by Gas Chromatography
ASTM D1946 - Standard Practice for Analysis of Reformed Gas by Gas Chromatography
ASTM D2013 - Standard Practice of Preparing Coal Samples for Analysis.
ASTM D2163 - Standard Test Method for Determination of Hydrocarbons in Liquefied Petroleum (LP) Gases and Propane/Propene Mixtures by Gas Chromatography
ASTM D2234/D2234M - Standard Practice for Collection of a Gross Sample of Coal

Reference Title
ASTM D2502 - Standard Test Method for Estimation of Molecular Weight (Relative Molecular Mass) of Petroleum Oils from Viscosity Measurements
ASTM D2503 - Standard Test Method for Estimation of Mean Relative Molecular Mass of Petroleum Oils from Viscosity Measurements
ASTM D2597 - Standard Test Method for Analysis of Demethanized Hydrocarbon Liquid Mixtures Containing Nitrogen and Carbon Dioxide by Gas Chromatography.
ASTM D3176 - Standard Practice for Ultimate Analysis of Coal and Coke.
ASTM D3238 - Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method
ASTM D3588 - Standard Practice for Calculating Heat Value, Compressibility Factor, and Relative Density of Gaseous Fuels
ASTM D3682 - Standard Test Method for Major and Minor Elements in Combustion Residues from Coal Utilization Processes.
ASTM D4057 - Standard Practice for Manual Sampling of Petroleum and Petroleum Products
ASTM D4177 - Standard Practice for Automatic Sampling of Petroleum and Petroleum Products.
ASTM D4806 - Standard Specification for Denatured Fuel Ethanol for Blending with Gasolines for Use as Automotive Spark-Ignition Engine Fuel.
ASTM D4809 - Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)
ASTM D4891 - Standard Test Method for Heating Value of Gases in Natural Gas Range by Stoichiometric Combustion
ASTM D5142 - Standard Test Methods for Proximate Analysis of the Analysis Sample of Coal and Coke by Instrumental Procedures, for petroleum liquid based fuels and liquid waste-derived fuels
ASTM D5291 - Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants
ASTM D5373 - Standard Test Methods for Determination of Carbon, Hydrogen and Nitrogen in Analysis Samples of Coal and Carbon in Analysis Samples of Coal and Coke
ASTM D5468 - Standard Test Method for Gross Calorific and Ash Value of Waste Materials

Reference Title
ASTM D5580 - Standard Test Method for Determination of Benzene, Toluene, Ethylbenzene, p/m-Xylene, o-Xylene, C9 and Heavier Aromatics, and Total Aromatics in Finished Gasoline by Gas Chromatography
ASTM D5865 /D5865M- Standard Test Method for Gross Calorific Value of Coal and Coke
ASTM D6348 - Standard Test Method for Determination of Gaseous Compounds by Extractive Direct Interface Fourier Transform Infrared (FTIR) Spectroscopy
ASTM D6609 - Standard Guide for Part-Stream Sampling of Coal.
ASTM D6866 - Standard Test Methods for Determining the Biobased Content of Solid, Liquid, and Gaseous Samples Using Radiocarbon Analysis
ASTM D6883 - Standard Practice for Manual Sampling of Stationary Coal from Railroad Cars, Barges, Trucks, or Stockpiles
ASTM D7430 - Standard Practice for Mechanical Sampling of Coal
ASTM D7459 - Standard Practice for Collection of Integrated Samples for the Speciation of Biomass (Biogenic) and Fossil-Derived Carbon Dioxide Emitted from Stationary Emissions Sources
ASTM D7582: Standard Test Methods for Proximate Analysis of Coal and Coke by Macro Thermogravimetric Analysis
ASTM D7633 - Standard Test Method for Carbon Black Carbon Content
ASTM D7662 - Standard Test Method for Carbon Content in Carbon Black Feedstock Oils
ASTM E415 - Standard Test Method for Analysis of Carbon and Low-Alloy Steel by Spark Atomic Emission Spectrometry
ASTM E1019 - Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Various Combustion and Fusion Techniques
ASTM E1915 - Standard Test Methods for Analysis of Metal Bearing Ores and Related Materials for Carbon, Sulfur, and Acid-Base Characteristics
ASTM E1941 - Standard Test Method for Determination of Carbon in Refractory and Reactive Metals and Their Alloys by Combustion Analysis
ASTM UOP539 - Refinery Gas Analysis by Gas Chromatography
CCME EPC-73E: Environmental Code of Practice for the Measurement and Control of Fugitive VOC Emissions from Equipment Leaks (1993)

Reference Title
CSA Z741-12: Geological Storage of Carbon Dioxide
Environment and Climate Change Canada, “Reference method for source testing quantification of carbon dioxide releases by continuous emission monitoring systems from thermal power generation.” Report En14-46/1-2012E-PDF
Gas Processors Association (GPA) 2261–00, Revised 2000 - Analysis for Natural Gas and Similar Gaseous Mixtures by Gas Chromatography.
Gas Processors Association (GPA) 2172:1996, Calculation of Gross Heating Value, Relative Density and Compressibility For Natural Gas Mixtures From Compositional Analysis
Canadian Energy Partnership for Environmental Innovation (CEPEI), Methodology Manual: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System, prepared by Clearstone Engineering Ltd., 2018,
ISO 13909 - All Parts: Hard coal and coke -- Mechanical sampling
ISO/TR 15349-1: 1998 - Unalloyed steel – Determination of low carbon content, Part 1: Infrared absorption method after combustion in an electric resistance furnace (by peak separation)
ISO/TR 15349-3: 1998 - Unalloyed steel – Determination of low carbon content, Part 3: Infrared absorption method after combustion in an electric resistance furnace (with preheating)
ISO 3170: Petroleum Liquids— Manual sampling.
ISO 3171: Petroleum Liquids— Automatic pipeline sampling.
Technical Association of the Pulp and Paper Industry (TAPPI) T684 “Gross High Heating Value of Black Liquor”
Technical Association of the Pulp and Paper Industry (TAPPI) T650 “Solids Content of Black Liquor”
Solomon Associates, “The CAN-CWB Methodology for: Regulatory Support: Public Report”, January 2014.
U.S. EPA Method 320 (40 CFR part 63, Appendix A)
U.S. EPA TANKS Version 4.09D, U.S. Environmental Protection Agency, October 2005
U.S. EPA AP 42, Fifth Edition, Compilation of Air Pollutant Emission Factors, Volume 1: Stationary Point and Area Sources

5. Applicability

The person required by the Regulation to quantify the total amount of GHG emitted at a facility in 2023 or later shall use this version of the Guideline.

The person required by the Regulation to quantify the amount of an EPS parameter in respect of an activity component that is part of an industrial activity engaged in at a covered facility during 2023 or later shall use this version of the Guideline.

If the person is required to submit a revised report because of a requirement in the Regulation, Ontario Regulation 143/16, or Ontario Regulation 452/09, the person shall, for each activity required to be addressed in the revised report, use the standard quantification method contained in the version of this Guideline, the Guideline as incorporated into Ontario Regulation 143/16 or the Guideline for Greenhouse Gas Emissions Reporting as incorporated into Ontario Regulation 452/09 that was in effect for the year that was the subject of the original report.

6. Activity Components and EPS Parameters

This section applies to the owner or operator of a facility that is required by the Regulation to quantify the amount of the EPS parameter set out opposite the activity component in the Guideline. The table in section 6.1 sets out the EPS parameter for each activity component that is part of an industrial activity engaged in at the covered facility.

Where the *GHG Emissions Performance Standards and Methodology for the Determination of the Total Annual Emissions Limit* (the “EPS Methodology”) provides that an owner or operator is required to or is permitted to use a method to calculate the annual emissions activity limits (AAEL) for a covered facility, the person required to report shall report the following in an emissions report prepared for a calendar year in respect of the facility:

- 1) the amount of each EPS parameter set out opposite each activity component in the table in section 6.1 of this Guideline that was used in any calculation of an AAEL for each method used;
- 2) the amount of each EPS parameter set out opposite each activity component in the table in section 6.1 of this Guideline that was used in any calculation under an applicable method in respect of which an AAEL was calculated; and
- 3) the amount of each EPS parameter set out opposite each activity component in the table in section 6.1 of this Guideline that was used in any calculation for a stringency factor.

The person shall not report the amount of the EPS parameter for an activity component that is not carried out at the facility unless otherwise specified.

The person shall quantify the amount of the EPS parameter in accordance with sections 6.2 and 6.3 and report the amount of the EPS parameter in the units specified in section 6.1.

6.1 Activity Components and EPS Parameters Table

Item	Activity component	EPS parameter (units)
Method A: Sector Performance Standards		
1	Intermediate clinker produced	Mass (expressed in tonnes)
2	Grey cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
2(a)	Clinker in the grey cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
2(b)	Gypsum in the grey cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
2(c)	Limestone in the grey cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
3	CAN-CWB per calendar year	Amount (expressed in CAN-CWB)
4	Coke produced from a coke oven	Mass (expressed in tonnes)
5	Iron produced from a blast furnace	Mass (expressed in tonnes)
6	Steel produced from a basic oxygen furnace	Mass (expressed in tonnes)
7	Steel produced from an electric arc furnace	Mass (expressed in tonnes)
8(a)	Hydrogen produced	Mass (expressed in tonnes)
8(b)	Hydrogen produced at a petroleum refinery	Mass (expressed in tonnes)
9	Gold produced through the mining and milling of gold ore	Mass (expressed in kilograms)

Item	Activity component	EPS parameter (units)
10	Nitric acid produced	Mass (expressed in tonnes)
11	Anhydrous ammonia or aqueous ammonia produced	Mass (expressed in tonnes)
12	Urea produced	Mass (expressed in tonnes)
Method E: Facility Specific Performance Standards		
13	Mined material at the facility with GHG ID 1418	Mass (expressed in million tonnes)
14	Nepheline syenite produced at the facility with GHG ID 1417	Mass (expressed in tonnes)
15	Fuel ethanol produced	Volume (expressed in kilolitres of absolute ethanol)
16	Industrial ethanol produced	Volume (expressed in kilolitres of absolute ethanol)
17	Brick or other products made from clay or shale using a kiln	Mass (expressed in tonnes)
18	Mineral wool insulation produced	Mass (expressed in tonnes)
19	Glass produced	Mass (expressed in tonnes)
20	Gypsum panels produced	Area (expressed in thousand square feet)
21	White cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
21(a)	Clinker in the white cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
21(b)	Gypsum in the white cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
21(c)	Limestone in the white cement produced from clinker produced at the covered facility	Mass (expressed in tonnes)
22	Finished product(s) produced	Mass (expressed in tonnes)
23	Megawatt hours of work	Energy (expressed in MWh)

Item	Activity component	EPS parameter (units)
24	Refinery feed at the facility with GHG ID 1111	Volume (expressed in kilolitres)
25	Ethylene produced at the facility with GHG ID 1100	Mass (expressed in tonnes)
26	Polyethylene produced	Mass (expressed in tonnes)
27	Carbon black produced	Mass (expressed in tonnes)
28	Styrene produced	Mass (expressed in tonnes)
29	Nylon resins produced	Mass (expressed in tonnes)
30	Nylon fibres produced	Mass (expressed in tonnes)
31	Products from steam cracker at the site with GHG ID 1073	Mass (expressed in tonnes)
32	Products not from steam cracker at the site with GHG ID 1073	Mass (expressed in tonnes)
33	High calcium lime produced	Mass (expressed in tonnes)
34	Cal-85 produced	Mass (expressed in tonnes)
35	Dolomitic lime produced	Mass (expressed in tonnes)
36	Double burnt lime produced	Mass (expressed in tonnes)
37	Iron coated dolime produced	Mass (expressed in tonnes)
38	Propane and Butane produced	Volume (expressed in cubic metres), combined
39	Finished oilseed product(s) produced	Mass (expressed in tonnes)
40	Beans and seeds crushed	Mass (expressed in tonnes)
41	Beverage ethanol produced	Volume (expressed in kiloLABS)
42	Raw sugar processed	Mass (expressed in tonnes)
43	Malic acid produced	Mass (expressed in tonnes)
44	Fumaric acid produced	Mass (expressed in tonnes)
45	Used oil feed produced at the Facility with GHG ID 1122	Volume (expressed in kilolitres)
46	Hot rolled steel produced	Mass (expressed in tonnes)

Item	Activity component	EPS parameter (units)
47	n/a	n/a
48	Corn milled at the facility with GHG ID 1076	Mass (expressed in tonnes of air-dried corn milled)
49	Corn milled and corn germ processed at the facility with GHG ID 1075	Mass (expressed in tonnes of air-dried corn milled and corn germ processed)
50	MPMD produced	Mass (expressed in tonnes)
51	Corn milled at the facility with GHG ID 1085	Mass (expressed in tonnes)
52	Citric acid produced	Mass (expressed in tonnes)
53	Steel produced from an electric arc furnace	Mass (expressed in tonnes)
54	Lime kiln dust and waste lime produced	Mass (expressed in tonnes)
54.01	Aluminium poured	Mass (expressed in tonnes)
54.02	Aluminium alloys produced	Mass (expressed in tonnes)
54.03	Gold bearing ore produced at the facility with GHG ID 1457	Mass (expressed in thousand tonnes milled)
54.04	Gold mined and milled	Mass (expressed in kilograms)
54.05	Nickel matte produced	Mass (expressed in tonnes)
54.06	Palladium and platinum produced	Mass (expressed in kilograms)
54.07	Total billets and extruded product produced	Mass (expressed in tonnes)
54.08	Annealed steel	Mass (expressed in tonnes)
54.09	Direct strip steel produced	Mass (expressed in tonnes)
54.10	Finished steel - heat treated	Mass (expressed in tonnes)
54.11	Galvanized steel produced	Mass (expressed in tonnes)
54.12	Finished steel product produced	Mass (expressed in tonnes)
54.13	Forged steel produced	Mass (expressed in tonnes)
54.14	Heat-treated steel tubing produced	Mass (expressed in tonnes)

Item	Activity component	EPS parameter (units)
54.15	Steel products at the facility with GHG ID 1412	Mass (expressed in tonnes)
54.16	Carbon and alloy steel cast billets produced	Mass (expressed in tonnes)
54.17	Carbon and alloy steel ingots produced	Mass (expressed in tonnes)
54.18	Stainless steel cast billets produced	Mass (expressed in tonnes)
54.19	Stainless steel ingots produced	Mass (expressed in tonnes)
54.20	Biodiesel produced by acid esterification and base transesterification from renewable biomass lipids	Mass (expressed in tonnes)
54.21	Coal tar distillation products produced	Mass (expressed in tonnes)
54.22	Diaminocyclohexane (DCH) produced	Mass (expressed in tonnes)
54.23	Maleic anhydride produced	Mass (expressed in tonnes)
54.24	Polyvinyl chloride resin produced	Mass (expressed in tonnes)
54.25	Rubber produced	Mass (expressed in tonnes)
54.26	Total synthetic oil, antioxidants, rubber additives and specialty chemicals produced	Mass (expressed in tonnes)
54.27	Total uranium hexafluoride (UF ₆) and uranium dioxide (UO ₂) converted	Mass (expressed in tonnes of uranium)
54.28	Uranium trioxide (UO ₃) refined	Mass (expressed in tonnes of uranium)
54.29	Vaccine produced	Volume (expressed in litres)
54.30	Wax produced	Mass (expressed in tonnes)
54.31	Zinc oxide (ZnO) produced	Mass (expressed in tonnes)
54.32	Baked goods produced	Mass (expressed in tonnes)

Item	Activity component	EPS parameter (units)
54.33	Beer and other beverages produced from a brewing process using grains	Volume (expressed in hectolitres)
54.34	Canned food items produced	Mass (expressed in tonnes)
54.35	Confectionery products manufactured	Mass (expressed in tonnes)
54.36	Finished pork products produced	Mass (expressed in tonnes)
54.37	Potato chips and corn snacks produced	Mass (expressed in tonnes)
54.38	Poultry processed	Mass (expressed in tonnes)
54.39	Evaporated salt produced	Mass (expressed in tonnes)
54.40	Abrasives produced	Mass (expressed in kilograms)
54.41	Capsules produced	Mass (expressed in kilograms)
54.42	Masking tape produced	Mass (expressed in kilograms)
54.43	Medical tape produced	Mass (expressed in kilograms)
54.44	Medium density fibreboard produced	Volume (expressed in cubic meters)
54.45	Particleboard panels produced	Volume (expressed in cubic meters)
54.46	Tape produced at the facility with GHG ID 1507	Mass (expressed in kilograms)
54.47	Scotch-Brite produced	Mass (expressed in kilograms)
54.48	Expanded polystyrene produced	Mass (expressed in tonnes)
54.49	Moulded parts painted	Mass (expressed in tonnes)
54.50	Coils produced	Mass (expressed in tonnes)
54.51	Stocked tires produced	Mass (expressed in thousand pounds)
54.52	Transmission and power train parts	Amount (expressed in number of parts sold)
54.53	Vehicles produced with an internal combustion engine	Amount (expressed in number of vehicles)

Item	Activity component	EPS parameter (units)
54.54	Wax paper produced	Mass (expressed in tonnes)
54.55	Beverages produced other than beverages captured by item 54.33	Volume (expressed in kilolitres)
54.56	Finished metal product produced	Mass (expressed in tonnes)
54.57	Forged metal produced	Mass (expressed in tonnes)
54.58	Nylon 6 resins chips	Mass (expressed in tonnes)
54.59	Total zinc and copper concentrate	Mass (expressed in tonnes)
54.60	Finished metal – heat treated	Mass (expressed in tonnes)
Methods B & C: Electricity Generation Standard and Cogeneration Thermal Energy Standard		
55	Annual electricity generated (Production_{B,i,y}), required for Formula 3.1.2-1 of the EPS Methodology	Energy (expressed in gigawatt hours)
56	n/a	n/a
57	Annual useful thermal energy that is generated from a combustion device and transferred (Production_{C,i,y}), required for Formula 3.1.3-1 of the EPS Methodology	Energy (expressed in gigajoules)
58 - 63	n/a	n/a
Method D: Facility Specific Performance Standards (Facilities Not Subject to Method E)		
64	Annual amount produced of each activity component set out in the notice issued by the Director under subsection 12.1(1) of the EPS regulation	Amount (expressed in the units set out in the notice), set out separately for each activity component
65	Annual amount produced of the activity component (Production_{D2,i,y}) required for	Amount (expressed in the applicable units)

Item	Activity component	EPS parameter (units)
	Formula 3.1.4-2 of the EPS Methodology	
66	Annual amount produced of the activity component (Production_{i,y}) required for Formula 3.1.4-5 of the EPS Methodology	Amount (expressed in the applicable units), set out separately for each year set out in the Formula
67	Annual amount produced of the activity component (Production_{D3,i,y}) required for Formula 3.1.4-6 of the EPS Methodology	Amount (expressed in the applicable units), set out separately for each year set out in the Formula
67.01	Annual amount produced of the activity component (Production_y) required for Formula 3.1.4-8 of the EPS Methodology	Amount (expressed in the applicable units), set out separately for each year set out in the Formula
Method G: Steel Sector Facility Specific Performance Standard		
67.02	Coke produced from a coke oven	Mass (expressed in tonnes)
67.03	Iron produced from a blast furnace	Mass (expressed in tonnes)
67.04	Steel produced from a basic oxygen furnace (BOF)	Mass (expressed in tonnes)
67.05	Direct Reduced Iron (DRI)	Mass (expressed in tonnes)
67.06	Steel produced from an electric arc furnace (EAF) (installed in or after 2027)	Mass (expressed in tonnes)
67.07	Steel produced from an electric arc furnace (EAF) (installed before 2026)	Mass (expressed in tonnes)
67.08	Steel produced from an electric arc furnace (EAF) (hot metal)	Mass (expressed in tonnes)
67.09	Steel produced from an electric arc furnace (EAF) (cold charge)	Mass (expressed in tonnes)
67.10	Annual electricity generated at LSP	Energy (expressed in gigawatt hours)

Item	Activity component	EPS parameter (units)
Activity Components for Calculations		
68	Energy input from all biomass fuel used at the facility (El_{biomass,2022}) required for Formula 4.2-4 of the EPS Methodology	Energy (expressed in gigajoules)
69	Total energy input from all fuel used at the facility, including biomass fuels (El_{AllFuels,2022}) required for Formula 4.2-2 of the EPS Methodology	Energy (expressed in gigajoules)
70	Fraction of energy input that is not biomass (NBF_{i,y}) required for Formula 3.1.2-1 of the EPS Methodology	Fraction (unitless)
71	Fraction of energy input that is not biomass (NBF_{i,y}) required for Formula 3.1.3-1 of the EPS Methodology	Fraction (unitless)
72	Thermal energy transferred (TET_y) required for Formula 3.1.4-1 of the EPS Methodology	Energy (expressed in gigajoules)
73	The value of the non-fixed process baseline emissions intensity for the facility (BEI_{D2,i,nonFPE}) calculated in accordance with Formula 3.1.4-5 of the EPS Methodology	Emission intensity (expressed in CO _{2e} per unit of production)
74	Annual emissions (Emissions_{i,y}) required for Formula 3.1.4-5 of the EPS Methodology	Mass (expressed in tonnes of CO _{2e}), set out separately for each year set out in the Formula
75	The value of the non-fixed process baseline emissions intensity for the facility (BEI_{D3,i,nonFPE}) calculated in accordance with Formula 3.1.4-8 of the EPS Methodology	Emission intensity (expressed in CO _{2e} per unit of production)

Item	Activity component	EPS parameter (units)
76	Annual emissions (Emissions_y) required for Formula 3.1.4-8 of the EPS Methodology (expressed in CO _{2e})	Mass (expressed in tonnes of CO _{2e}), set out separately for each year set out in the Formula
77	Thermal energy transferred (TET_y) required for Formula 3.1.5-1 of the EPS Methodology	Energy (expressed in gigajoules)
78	Emissions from the use of by-product fuels (BPF_y) required for Formula 3.1.5-1 of the EPS Methodology	Mass (expressed in tonnes of CO _{2e})

6.2 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for EPS parameters and activity components are the same as those required for the measurement of production quantity and material usage in the applicable subsection entitled Sampling, Analysis and Measurement Requirements under each Standard Quantification Method. Where there are no requirements for production or material use under the applicable Standard Quantification Method, the person may use the following method:

- (1) Equipment used to measure the production quantity, material usage, thermal energy transferred, and energy input shall be:
 - (i) calibrated according to the manufacturer’s instructions where available; or, where not available, calibrated according to practices used for accounting purposes;
 - (ii) maintained to achieve an accuracy of plus or minus 5 per cent.
- (2) Measurement or engineering estimates for byproduct fuels.

6.3 Procedures for Estimating Missing Data

Determination of the amount of the EPS Parameter:

- (a) Whenever sampling, measurement, financial, purchase records, accounting records, or any other data required for the determination of an amount of an EPS parameter are missing, the person shall ensure that the data are replaced using the following missing data procedures:
 - (1) Determine the sampling or measurement rate using Equation 6-1:

$$R_p = \frac{Q_{PAct}}{Q_{PRequired}}$$

Equation 6-1

Where:

- R_p = valid production record that was used, expressed as a percentage
- Q_{PAct} = Quantity of valid production records obtained by the person
- $Q_{PRequired}$ = Quantity of production records required

- (i) Replace the missing data as follows,
 - (A) If $R \geq 0.9$: replace the missing data by the arithmetic mean of the production record from immediately before and after the missing data period. If no data are available from before the missing data period, the person shall use the first available data from after the missing data period;
 - (B) If $0.75 \leq R < 0.9$: replace the missing data by the lowest production record value during the reporting period for which the calculation is made; and
 - (C) If $R < 0.75$: replace the missing data by the lowest production record value sampled or analyzed during the 3 preceding years.

7. Partial Year Adjustment to Verification Amount

7.1 Partial Year Adjustment for Subsection 12 (7) of the Regulation

- (a) This section applies to the owner or operator of a covered facility that received notice of registration as a registered emitter issued under subsection 64 (2) of the *Greenhouse Gas Pollution Pricing Act* (Canada) from the Minister of National Revenue and the effective date of the notice is after January 1 in the first compliance period, in respect of a registration period, that applies to the facility.
- (b) An owner or operator that meets the criteria in (a) shall apply the following substitutions in calculating the verification amount in Section 12 of the Regulation for the covered facility's first compliance period, in respect of a registration period, under each applicable Standard Quantification Method or other applicable quantification method:
 - (1) All production values, material use, fuel use, energy use, and any other values used in each applicable Standard Quantification Method or other applicable quantification method for the calculation of emissions values used to calculate the verification amount in Section 12 of the Regulation shall be the values from the period starting from the effective date of the

notice referred to in (a) through to December 31 of the year of the effective date of the notice.

- (2) Calculate all emissions values used to calculate the verification amount in Section 12 of the Regulation substituting the values in the Standard Quantification Methods or other applicable quantification methods with the values referred to in paragraph (1) above.

For greater certainty, the owner or operator that applies the substitutions in (b) shall still calculate and report all values used in each applicable Standard Quantification Method or other applicable quantification method and the reporting amount for the full year and the partial year values shall be used only for the calculation and reporting of the verification amount.

7.2 Partial Year Adjustment for Subsection 12 (8) of the Regulation

- (a) This section applies to the owner or operator of a covered facility that received a notice under subsection 8 (3) of the EPS Regulation dated on or after January 1 in a compliance period setting out an effective date of a change in respect of the composition of sites that constitute the covered facility.
- (b) An owner or operator that meets the criteria in (a) shall apply the following substitutions in calculating the verification amount in Section 12 of the Regulation for the covered facility in respect of the year of the effective date of the notice referred to in (a) under each applicable Standard Quantification Method or other applicable quantification method:
 - (1) If paragraph 2 of subsection 12 (8) of the Regulation applies to the owner or operator of the covered facility, all production values, material use, fuel use, energy use, and any other values, in respect of the site that is added to the covered facility, that are used in each applicable Standard Quantification Method or other applicable quantification method for the calculation of emissions values used to calculate the verification amount in Section 12 of the Regulation shall be the values from the period starting from the effective date of the notice referred to in (a) through to December 31 of the year of the effective date of the notice.
 - (2) If paragraph 4 of subsection 12 (8) of the Regulation applies to the owner or operator of the covered facility, all production values, material use, fuel use, energy use, and any other values, in respect of the site that is removed from the covered facility, used in each applicable Standard Quantification Method or other applicable quantification method for the calculation of emissions values used to calculate the verification amount in Section 12 of the Regulation shall be the values from the period starting from January 1 of the year of the effective date of the notice referred to in (a) though to the effective date of the notice.

- (3) Calculate all emissions values used to calculate the verification amount in Section 12 of the Regulation substituting the values in the Standard Quantification Methods or other applicable quantification methods with the values referred to in paragraph (1) or (2) above as applicable.

For greater certainty, the owner or operator that applies the substitutions in (b) shall still calculate and report all values used in each applicable Standard Quantification Method or other applicable quantification method and the reporting amount for the full year and the partial year values shall be used only for the calculation and reporting of the verification amount.

7.3 Partial Year Adjustment for Subsection 12 (9) of the Regulation

- (a) This section applies to the owner or operator of a covered facility that received a notice under subsection 4.1 of the Regulation for the compliance period that is the subject of the determination under Section 12 of the Regulation setting out the first and last day of a temporary shutdown period in respect of the covered facility.
- (b) An owner or operator that meets the criteria in (a) shall apply the following substitutions in calculating the verification amount in Section 12 of the Regulation for the covered facility in respect of the compliance period that is the subject of the notice referred to in (a), under each applicable Standard Quantification Method or other applicable quantification method:
 - (1) All production values, material use, fuel use, energy use, and any other values used in each applicable Standard Quantification Method or other applicable quantification method for the calculation of emissions values used to calculate the verification amount in Section 12 of the Regulation shall be the values from:
 - (i) the period from January 1 through to the start date of the temporary shutdown period set out in the notice referred to in (a), plus
 - (ii) the period from the last date of the temporary shutdown period set out in the notice referred to in (a) through to December 31.
 - (2) Calculate all emissions values used to calculate the verification amount in Section 12 of the Regulation substituting the values in the Standard Quantification Methods or other applicable quantification methods with the values referred to in paragraph (1) above.

For greater certainty, the owner or operator that applies the substitutions in (b) shall still calculate and report all values used in each applicable Standard Quantification Method or other applicable quantification method and the reporting amount for the full year and the partial year values shall be used only for the calculation and reporting of the verification amount.

Appendices

ON.50 Adipic Acid Production

ON.51 Activity Definition

For the purposes of this standard quantification method (SQM):

“Adipic acid production” has the same meaning as in the Regulation.

“Person” means a person that engages in adipic acid production.

ON.52 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.50 – ON.55, in an emission report prepared for a calendar year in respect of adipic acid production at a facility:
- (b) Annual process N₂O emissions from adipic acid production (tonnes).
- (c) Annual adipic acid production (tonnes).

ON.53 Calculation of N₂O Emissions

- (a) The person shall determine annual N₂O emissions from adipic acid production according to paragraph (a)(1) or (a)(2) of this section:
 - (1) Using a site-specific emission factor and production data according to subsections (b) through (g) of this section.
 - (2) Using a CEMS.
- (b) The person shall conduct an annual performance test or use continuous monitors according to paragraphs (b)(1) through (b)(3) of this section.
 - (1) The person shall either conduct the test on the waste gas stream from the nitric acid oxidation step of the process using the methods specified in ON.54 (b) through (d) or use a continuous monitoring system.
 - (2) The person shall either conduct the performance test under normal process operating conditions and without using N₂O abatement technology or use a continuous monitoring system.
 - (3) The person shall measure the adipic acid production during the test and calculate the production rate for the test period; or measure the adipic acid production during the continuous monitoring period in tonnes per hour.
- (c) The person shall determine an N₂O emissions factor to use in Equation 50-2 of this section according to paragraph (c)(1) or (c)(2) of this section.
 - (1) The person may use a CEMS to determine N₂O concentration according to the procedures in paragraph (a)(2) of this section.
 - (2) Using the results of the test or continuous process monitors in subsection (b) of this section, the person shall calculate a facility-specific

emissions factor according to Equation 50-1 for performance test and 50-1a for continuous monitors of this section:

$$EF_{N_2O} = \frac{\sum_1^n \frac{C_{N_2O} \times 1.826 \times 10^{-6} \times Q}{P}}{n}$$

Equation 50-1

$$EF_{N_2O} = \frac{C_{N_2O} \times 1.826 \times 10^{-6} \times Q}{P}$$

Equation 50-1a

Where:

- EF_{N₂O} = Average facility-specific N₂O emissions factor without using N₂O abatement technology (kg N₂O generated/tonne adipic acid produced).
- C_{N₂O} = average N₂O concentration during the performance test or average hourly concentrations for continuous process monitors (ppm N₂O).
- 1.862x10⁻⁶ = Conversion factor (kg/dSm³-ppm N₂O).
- Q = average volumetric flow rate of effluent gas per test run during the performance test or average hourly readings for continuous monitor (dSm³/hr).
- P = average production rate during the performance test or the average hourly production rate for continuous monitors during the period (tonnes adipic acid produced/hr).
- n = Number of test runs.

- (d) If applicable, the person shall determine the destruction efficiency for each N₂O abatement technology used at the facility according to paragraphs (d)(1), (d)(2), (d)(3) or (d)(4) of this section.
 - (1) Use the manufacturer's specified destruction efficiency.
 - (2) Estimate the destruction efficiency through process knowledge. Examples of information that could constitute process knowledge include calculations based on material balances, process stoichiometry, or previous test results provided the results are still relevant to the current vent stream conditions. The person shall document how process knowledge was used to determine the destruction efficiency.
 - (3) Calculate the destruction efficiency by conducting an additional performance test on the emissions stream following the N₂O abatement technology.
 - (4) Calculate the destruction efficiency by the use of continuous monitors on the controlled and uncontrolled emissions.

- (e) If applicable, the person shall determine the abatement factor for each N₂O abatement technology used at the facility. The abatement factor is calculated for each adipic acid facility according to Equation 50-2 of this section.

$$AF = \frac{P_{a \text{ Abate}}}{P_a}$$

Equation 50-2

Where:

- AF = Abatement factor of N₂O abatement technology (fraction of production in the testing period that abatement technology is operating).
- P_{a Abate} = adipic acid production in the testing period during which N₂O abatement was used (tonnes acid produced).
- P_a = Total adipic acid production in the testing period (tonnes acid produced).

- (f) The person shall determine the annual amount of adipic acid produced and the annual adipic acid production during which N₂O abatement is operating.
- (g) The person shall calculate annual adipic acid production process emissions of N₂O by multiplying the emissions factor (determined using Equation 50-1 or 50-1a of this section) by the adipic acid production for each period and accounting for N₂O abatement, according to Equation 50-3 of this section:

$$N_2O = \sum_{i=1}^N \frac{EF_{N_2O_i} \times P_{ai} \times (1 - (DF_i \times AF_i))}{1000}$$

Equation 50-3

Where:

- N₂O = Annual N₂O mass emissions from adipic acid production (tonnes).
- EF_{N₂O_i} = Facility-specific N₂O emissions factor for the period without abatement technology (kg N₂O generated/tonne adipic acid produced).
- P_{ai} = Adipic acid produced in the period (tonnes).
- DF_i = Destruction efficiency of N₂O abatement technology in the period (abatement device destruction efficiency, per cent of N₂O removed from air stream).
- AF_i = Abatement factor of N₂O abatement technology in the period (fraction of period that is production abatement technology is operating).
- 1000 = Conversion factor (kg/tonne).

N = Number of different periods in the year. For performance test, the period would be the time between each test (e.g., N is 1 year if performance test conducted annually). For continuous monitors, N would be the number of months in the year (or more), with P_{ai} , $EF_{N_2O_i}$, DF_i and AF_i to be calculated for each month.

ON.54 Sampling, Analysis, and Measurement Requirements

- (a) The person shall conduct a new performance test and calculate a new facility-specific emissions factor according to the frequency specified in paragraph (a)(1) of this section, or use continuous monitors to calculate a facility-specific emissions factor and destruction efficiency according to paragraph (a)(2) of this section.
- (1) Performance Test
- (i) Conduct the performance test annually or
 - (ii) Conduct the performance test when the adipic acid production process is changed either by altering the ratio of cyclohexanone to cyclohexanol or by installing abatement equipment.
- (2) Continuous Process Monitors
- (i) Continuous process monitors shall be used to determine the uncontrolled emissions and the controlled N_2O emissions to derive an N_2O emission factor and abatement system destruction factor.
 - (ii) The continuous process monitors shall be operated in accordance with quality assurance and quality control programs.
- (b) The person shall measure the N_2O concentration during the performance test using one of the following methods:
- (1) Any of the applicable analytical methods listed in the Technical Reference Document section of this Guideline (section 4),
 - (2) The most appropriate method published by a consensus-based standards organization, if such a method exists. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used
- (c) The person shall determine the production rate(s) during the performance test and the annual adipic acid production according to either of the following methods:
- (1) Direct measurement (such as using flow meters or weigh scales).
 - (2) Existing plant procedures used for accounting purposes (such as sales records).

- (d) The person shall conduct all required performance tests according to the methods in subsection (b) of this section. For each test, the facility shall prepare an emissions factor determination report that shall include the following items.
 - (1) Analysis of samples, determination of emissions, and raw data.
 - (2) All information and data used to derive the emissions factor.
 - (3) The production rate(s) during the performance test and how each production rate was determined.
- (e) The person shall determine the monthly adipic acid production quantity and the monthly adipic acid production during which N₂O abatement technology is operating according to the methods in paragraph (c)(1) or (c)(2) of this section.
- (f) The person shall determine the annual adipic acid production quantity and the annual adipic production quantity during which N₂O abatement technology is operating by summing the respective monthly adipic acid production quantities. The equipment used to measure the production quantity shall:
 - (1) be calibrated according to the manufacturer's instructions; and
 - (2) be maintained to achieve an accuracy of plus or minus 5 per cent.

ON.55 Procedures for Estimating Missing Data

Unavailable analytical data:

- (a) Whenever analytical data relating to sampling are unavailable, the person shall, using the methods prescribed in ON.54, re-analyze the original sample, a backup sample or a replacement sample for the same measurement and sampling period.

Determination of quantity:

- (b) Whenever sampling and measurement data required by ON.54 for the calculation of emissions is missing the person shall ensure that the data are replaced using the following missing data procedures:
 - (1) When data determined on the basis of a performance test required by ON.54 are missing, conduct a new performance test;
 - (2) When the missing data are not data prescribed in a performance test and concern carbon content, temperature, pressure or gas concentration, the person shall:
 - (i) Determine the sampling or measurement rate that was used using the following Equation 50-4:

$$R = \frac{Q_{SAct}}{Q_{SRequired}}$$

Equation 50-4

- R = Sampling or measurement rate that was used, expressed as a percentage
- Q_{SAct} = Quantity of actual samples or measurements obtained by the person
- $Q_{SRequired}$ = Quantity of samples or measurements required under ON.54

- (ii) Replace the missing data as follows,
- (A) If $R \geq 0.9$: replace the missing data by the arithmetic mean of the sampling or measurement data from immediately before and after the missing data period. If no data are available from before the missing data period, the person shall use the first available data from after the missing data period;
 - (B) If $0.75 \leq R < 0.9$: replace the missing data by the highest data value sampled or analyzed during the reporting period for which the calculation is made;
 - (C) If $R < 0.75$: replace the missing data by the highest data value sampled or analyzed during the 3 preceding years;
- (3) When the missing data concern adipic acid production or gas flow rate, the replacement data shall be generated from best estimates based on all of the data relating to the processes.
- (4) For all units subject to the requirements of ON.20 that monitor and report emissions using a CEMS, the missing data backfilling procedures in “Reference method for source testing quantification of carbon dioxide releases by continuous emission monitoring systems from thermal power generation” shall be followed for CO₂ concentration, stack gas flow rate, fuel flow rate, high heating value, and fuel carbon content.

ON.70 Aluminium Production

ON.71 Activity Definition

For the purposes of this standard quantification method (SQM):

“Aluminium production” has the same meaning as in the Regulation.

“Person” means a person that engages in aluminium production.

ON.72 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.70 – ON.75, in an emission report prepared for a calendar year in respect of aluminium production at a facility.
- (b) Report the
 - (1) total annual quantity of CO₂ emissions from prebaked anode consumption, expressed in tonnes (t);
 - (2) annual anode consumption, expressed in tonnes of anodes/tonnes of liquid aluminium production;
 - (3) annual sulphur content of prebaked anodes, expressed in kilograms of S/kilograms of prebaked anodes; and
 - (4) annual ash content of prebaked anodes, expressed in kilograms of ash/kilograms of prebaked anodes.
- (c) Report the
 - (1) total annual quantity of CO₂ emissions from anode consumption from Søderberg electrolysis cells, expressed in tonnes (t);
 - (2) total annual quantity of cyclohexane-soluble matter emissions, expressed in tonnes (t), or the International Aluminium Institute factor used, expressed in kilograms of CSM/tonnes of liquid aluminium;
 - (3) total annual anode paste consumption, expressed in tonnes of paste/tonnes of liquid aluminium;
 - (4) annual average content of pitch or other binding agent in paste, expressed in kilograms of pitch or other binding agent/kilograms of paste;
 - (5) annual sulphur content in pitch or other binding agent, expressed in kilograms of S/kilograms of pitch or other binding agent;
 - (6) annual ash content in pitch or other binding agent, expressed in kilograms of ash/kilograms of pitch or other binding agent;

- (7) annual hydrogen content in pitch or other binding agent, expressed in kilograms of H₂/kilograms of pitch or other binding agent, or the International Aluminium Institute factor used;
 - (8) annual sulphur content in calcinated coke, expressed in kilograms of S/kilograms of calcinated coke;
 - (9) annual ash content in calcinated coke, expressed in kilograms of ash/kilograms of calcinated coke; and
 - (10) annual carbon content in dust from Söderberg electrolysis cells, expressed in kilograms of C/kilograms of liquid aluminium, or a value of 0.
- (d) Report the total annual quantity of CO₂ emissions from anode and cathode baking, expressed in tonnes (t).
- (e) Report the
- (1) total annual quantity of CO₂ emissions from packing material consumption, expressed in tonnes (t);
 - (2) annual packing material consumption, expressed in tonnes of packing material/tonnes of baked anodes or cathodes;
 - (3) total annual quantity of baked anodes and cathodes removed from furnace, expressed in tonnes (t);
 - (4) annual weighted average ash content of packing material, expressed in kilograms of ash/kilograms of packing material; and
 - (5) annual weighted average sulphur content of packing material, expressed in kilograms of S/kilograms of packing material.
- (f) Report the
- (1) total annual quantity of CO₂ emissions from coking of pitch or other binding agent, expressed in tonnes (t);
 - (2) total annual quantity of green anodes or cathodes put into furnace, expressed in tonnes (t);
 - (3) total annual quantity of baked anodes or cathodes removed from furnace, expressed in tonnes (t);
 - (4) annual weighted average hydrogen content of pitch or other binding agent, or the International Aluminium Institute factor used, expressed in kilograms of H₂/kilograms of pitch or other binding agent;
 - (5) annual weighted average pitch content of green anodes or cathodes, expressed in kilograms of pitch or other binding agent/kilograms of anodes or cathodes; and

(6) total annual quantity of recovered tar, expressed in tonnes (t).

(g) Report the

- (1) total annual quantity of CO₂ emissions from green coke calcination, expressed in tonnes (t);
- (2) total annual quantity of CO₂ emissions from coke dust, expressed in tonnes (t);
- (3) total annual quantity of green coke consumption, expressed in tonnes (t);
- (4) total annual quantity of calcinated coke production, expressed in tonnes (t);
- (5) total annual quantity of under-calcinated coke production, expressed in tonnes (t);
- (6) annual water content in green coke, expressed in kilograms of H₂O/kilograms of green coke;
- (7) annual volatile materials content in green coke, expressed in kilograms of volatile materials/kilograms of green coke;
- (8) annual sulphur content in green coke, expressed in kilograms of S/kilograms of green coke; and
- (9) annual sulphur content in calcinated coke, expressed in kilograms of S/kilograms of calcinated coke.

(h) Report the

- (1) total annual quantity of CF₄ emissions from anode effects, expressed in tonnes (t);
- (2) annual slope, if using the slope method, by a series of pots, expressed in tonnes of CF₄/tonnes of liquid aluminium/anode effect minute/pot-day/year;
- (3) annual anode effect duration, if using the slope method, expressed in anode effect minutes/pot-day calculated per year and obtained by multiplying the anode effects frequency, in number of anode effects per pot-day, by the average duration of anode effects in minutes;
- (4) overvoltage coefficient, if using the overvoltage coefficient method, expressed in tonnes of CF₄/tonnes of liquid aluminium/millivolt;
- (5) annual anode effect overvoltages, if using the overvoltage coefficient method, expressed in millivolts/pot;
- (6) current efficiency of the aluminium production process, if using the overvoltage coefficient method, expressed as a fraction; and
- (7) method used to determine the quantities reported under subsection (a).

- (i) Report the
 - (1) total annual quantity of C_2F_6 emissions, expressed in tonnes (t); and
 - (2) weight fraction of C_2F_6 to CF_4 or selected from Table 5-2, expressed in kilograms of C_2F_6 /kilograms of CF_4 .
- (j) Report the total annual quantity of emissions from SF_6 used as a cover gas, expressed in tonnes (t).
- (k) Report the total annual quantity of liquid aluminium production, expressed in tonnes (t).
- (l) Any person subject to this method who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions under subsections (a) through (f) of this section. This shall not include the emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

ON.73 Calculation of GHG Emissions

- (a) Quantify emissions using the GGQM in section 5A of the GGQR.

ON.74 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance with section 5B of the GGQR.

ON.75 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 5C of the GGQR.

ON.80 Ammonia Production

ON.81 Activity Definition

For the purposes of this standard quantification method (SQM):

“Ammonia production” has the same meaning as in the Regulation.

“Person” means a person that engages in ammonia production.

ON.82 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.80 – ON.85, in an emission report prepared for a calendar year in respect of ammonia production at a facility.
- (b) Report the total annual quantity of feedstock consumed, by feedstock type, expressed in
 - (1) cubic metres (m³), for gaseous quantities;
 - (2) kilolitres (kl), for liquid quantities; and
 - (3) tonnes (t), for solid quantities.
- (c) For each feedstock type used under subsection (a), report the annual weighted average carbon content expressed in
 - (1) kilograms (kg) of C/kilograms (kg) of feedstock, for gaseous quantities;
 - (2) kilograms (kg) of C/kilolitres (kl) of feedstock, for liquid quantities; and
 - (3) kilograms (kg) of C/kilograms (kg) of feedstock, for solid quantities.
- (d) Report the
 - (1) total annual quantity of urea, expressed in tonnes (t);
 - (2) total annual quantity of ammonia, expressed in tonnes (t);
 - (3) total annual quantity of CO₂ emissions from ammonia production, expressed in tonnes (t); and
 - (4) total annual quantity of CO₂ consumed in urea production, expressed in tonnes (t), which may be zero if the CO₂ consumed in urea production is accounted for in the amount reported under (d)(4).
- (e) Report the
 - (1) total annual quantity of CO₂ recovered or captured other than the amount reported under (d)(4), expressed in tonnes (t);
 - (2) Indicate if the CO₂ under (e)(1) that is recovered or captured is for downstream use, on-site production or permanent storage.
- (f) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the

emissions under paragraph (d)(3). This shall not include the emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

ON.83 Calculating GHG Emissions

The person shall calculate and report the annual process CO₂ emissions from each ammonia manufacturing process unit using the procedures in either subsection (a) or (b) of this section.

- (a) Calculate and report the process CO₂ emissions using the GGQM in section 8.A.(1) of the GGQR.
- (b) Calculate and report the process CO₂ emissions using the GGQM in section 8.A.(2)(A) through (D) of the GGQR.

ON.84 Sampling, Analysis, and Measurement Requirements

- (a) The person shall continuously measure the quantity of gaseous or liquid feedstock consumed using a flow meter. The quantity of solid feedstock consumed may be obtained from company records and aggregated on a monthly basis.
- (b) The person shall document the procedures used to ensure the accuracy of the estimates of feedstock consumption.
- (c) The person shall determine monthly carbon contents and the average molecular weight of each feedstock consumed from reports from the supplier(s). As an alternative to using supplier information on carbon contents, the person can also collect a sample of each feedstock on a monthly basis and analyze the carbon content and molecular weight of the fuel using any of the following methods listed in paragraphs (c) (1) through (c) (9) of this section, as applicable.
 - (1) ASTM D1945-03 Standard Test Method for Analysis of Natural Gas by Gas Chromatography.
 - (2) ASTM D1946-90 (Reapproved 2006) Standard Practice for Analysis of Reformed Gas by Gas Chromatography.
 - (3) ASTM D2502-04 (Reapproved 2002) Standard Test Method for Estimation of Mean Relative Molecular Mass of Petroleum Oils from Viscosity Measurements.
 - (4) ASTM D2503-92 (Reapproved 2007) Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurement of Vapor Pressure
 - (5) ASTM D3238-95 (Reapproved 2005) Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method.

- (6) ASTM D5291-02 (Reapproved 2007) Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants.
 - (7) ASTM D3176-89 (Reapproved 2002) Standard Practice for Ultimate Analysis of Coal and Coke.
 - (8) ASTM D5373-08 Standard Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal.
 - (9) The most appropriate method published by a consensus-based standards organization, if such a method exists. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (d) Calibrate all oil and gas flow meters (except for gas billing meters) and perform oil tank measurements according to the monitoring and QA/QC requirements specified in ON.25.
 - (e) If CO₂ from ammonia production is used to produce urea at the same facility, the person shall determine the quantity of urea produced using methods or plant instruments used for accounting purposes (e.g., sales records). The person shall document the procedures used.
 - (f) The person shall measure the ammonia produced using equipment that shall be:
 - (1) calibrated according to the manufacturer's instructions; and
 - (2) maintaining an accuracy of plus or minus 5 per cent.

ON.85 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 8C of the GGQR.

ON.260 Base Metal Production

ON.261 Activity Definition

For the purposes of this standard quantification method (SQM):

“Base Metal Production” has the same meaning as in the Regulation.

“Person” means a person that engages in base metal production.

ON.262 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.260 – ON.265, in an emission report prepared for a calendar year in respect of base metal production at a facility.
- (b) Total annual CO₂ emissions from base metal production, by type of base metal (tonnes).
- (c) Total annual quantities of carbon containing process input material (e.g., flux reagents, reducing agents or electrode consumption) by material type (tonnes).
- (d) Annual weighted average carbon content of carbon-containing process input (e.g., flux reagents, reducing agents or electrode consumption) by material type (tonnes of carbonate/tonnes of carbon containing process input material).
- (e) Total annual quantity of carbon-containing process output material, by material type, (tonnes).
- (f) Annual weighted average carbon content of carbon-containing process output, by material type (tonnes of C/tonnes of material).
- (g) Total annual quantity of individual base metal or nickel matte produced, by type (tonnes).

ON.263 Calculation of CO₂ Emissions

Calculate total CO₂ emissions as specified in subsection (a) or (b) of this section.

- (a) Determine facility process CO₂ emissions from base metal production using the GGQM in section 13.A.(1) of the GGQR.
- (b) Calculate CO₂ process emissions from base metal production using the GGQM in section 13.A.(2) of the GGQR.

ON.264 Sampling, Analysis, and Measurement Requirements

- (a) The annual mass of each solid carbon-containing input material consumed shall be determined using facility instruments, procedures, or records used for accounting purposes, including either direct measurement of the quantity of the material consumed or by calculations using process operating information.

- (b) The average carbon content of each material consumed shall be determined as specified under subsection (a) or (b) of this section.
- (c) Obtain carbon content by collecting and analyzing at least three representative samples of the material each year using one of the following:
 - (1) the methods in section 13.B.(1) of the GGQR.
 - (2) any of the applicable analytical methods listed in the Technical Reference Document section of this Guideline (section 4);
 - (3) the most appropriate method published by a consensus-based standards organization, if such a method exists or if no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (d) Obtain carbon content of the materials, including carbon electrodes, from the vendor or supplier.

ON.265 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 13.C of the GGQR.

ON.180 Carbonate Use

ON.181 Activity Definition

For the purposes of this standard quantification method (SQM):

“Carbonate use” has the same meaning as in the Regulation.

“Person” means a person that engages in carbonate use.

ON.182 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.180 – ON.185, in an emission report prepared for a calendar year in respect of carbonate use at a facility.
- (b) Annual CO₂ emissions from miscellaneous carbonate use (tonnes).
- (c) If the person followed the calculation methodology contained in ON.183(a), the person shall report the following information:
 - (1) Annual carbonate consumption by carbonate type (tonnes).
 - (2) Annual calcination fractions used in calculations.
- (d) If the person followed the calculation methodology contained in ON.183(b), the person shall report the following information:
 - (1) Annual carbonate input by carbonate type (tonnes).
 - (2) Annual carbonate output by carbonate type (tonnes).

ON.183 Calculating GHG Emissions

The person shall determine CO₂ process emissions from carbonate use in accordance with the procedures specified in either subsection (a) or (b) of this section.

- (a) Calculate the process emissions of CO₂ using calcination fractions with Equation 180-1 of this section.

$$E_{CO_2} = \sum_{i=1}^n (M_i \times EF_i \times F_i)$$

Equation 180-1

Where:

- E_{CO₂} = Annual CO₂ mass emissions from consumption of carbonates (tonnes).
- M_i = Annual mass of carbonate type i consumed (tonnes).
- EF_i = Emission factor for the carbonate type i, as specified in Table 180-1 to this section, tonnes of CO₂/tonne carbonate consumed.

- F_i = Calcination fraction achieved for each particular carbonate type i (weight fraction). As an alternative to measuring the calcination fraction, a value of 1.0 can be Used.
- n = Number of carbonate types.

- (b) Calculate the process emissions of CO₂ using actual mass of output carbonates with Equation 180-2 of this section.

$$E_{CO_2} = \left[\sum_{k=1}^m (M_k \times EF_k) - \sum_{j=1}^n (M_j \times EF_j) \right]$$

Equation 180-2

Where:

- E_{CO_2} = Annual CO₂ mass emissions from consumption of carbonates (tonnes).
- M_k = Annual mass of input carbonate type k (tonnes).
- EF_k = Emission factor for the input carbonate type k , as specified in Table 180-1 of this section (tonnes of CO₂/tonne carbonate).
- M_j = Annual mass of output carbonate type j (tonnes).
- EF_j = Emission factor for the output carbonate type j , as specified in Table 180-1 of this section (tonnes of CO₂/tonne carbonate).
- m = Number of input carbonate types.
- n = Number of output carbonate types.

ON.184 Sampling, Analysis, and Measurement Requirements

- (a) The annual mass of carbonate consumed (for Equation 180-1 of this section) or carbonate inputs (for Equation 180-2 of this section) shall be determined annually from monthly measurements using the same plant instruments used for accounting purposes including purchase records or direct measurement, such as weigh hoppers or weigh belt feeders.
- (b) The annual mass of carbonate outputs (for Equation 180-2 of this section) shall be determined annually from monthly measurements using the same plant instruments used for accounting purposes including purchase records or direct measurement, such as weigh hoppers or belt weigh feeders.
- (c) If the person followed the procedures of ON.183(a), rather than assuming a calcination fraction of 1.0, the person may determine, on an annual basis, the calcination fraction for each carbonate consumed using one of the following:
- (1) Any of the applicable analytical methods listed in the Technical Reference Document section of this Guideline (section 4);
 - (2) The most appropriate method published by a consensus-based standards organization, if such a method exists. If no appropriate method is published by a consensus-based standards organization, use

industry standard methods, noting where such methods are used and what methods are used.

ON.185 Procedures for Estimating Missing Data

Unavailable analytical data:

- (a) Whenever analytical data relating to sampling are unavailable, the person shall, using the methods prescribed in ON.184, re-analyze the original sample, a backup sample or a replacement sample for the same measurement and sampling period.

Determination of quantity:

- (b) Whenever sampling and measurement data required by ON.184 for the calculation of emissions is missing, the person shall ensure that the data are replaced using the following missing data procedures:
- (1) When the missing data concern carbon content, temperature, pressure or gas concentration, the person shall:
- (i) Determine the sampling or measurement rate using the following Equation 180-3:

$$R = \frac{Q_{SAct}}{Q_{SRequired}}$$

Equation 180-3

Where:

- R = Sampling or measurement rate that was used, expressed as a percentage
- Q_{SAct} = Quantity of actual samples or measurements obtained by the person
- $Q_{SRequired}$ = Quantity of samples or measurements required under ON.184

- (ii) Replace the missing data as follows,
- (A) If $R \geq 0.9$: replace the missing data by the arithmetic mean of the sampling or measurement data from immediately before and after the missing data period. If no data are available from before the missing data period, the person shall use the first available data from after the missing data period;
- (B) If $0.75 \leq R < 0.9$: replace the missing data by the highest data value sampled or analyzed during the reporting period for which the calculation is made;
- (C) If $R < 0.75$: replace the missing data by the highest data value sampled or analyzed during the 3 preceding years;

- (2) When the missing data concern raw material consumption or carbonate consumption, the replacement data shall be generated from best estimates based on all of the data relating to the processes.
- (3) For all units subject to the requirements of ON.20 that monitor and report emissions using a CEMS, the missing data backfilling procedures in “Reference method for source testing quantification of carbon dioxide releases by continuous emission monitoring systems from thermal power generation” shall be followed for CO₂ concentration, stack gas flow rate, fuel flow rate, high heating value, and fuel carbon content.

Table 180-1 – CO₂ Emission Factors for Common Carbonates

Mineral Name – Carbonate	CO ₂ Emission Factor (tonnes of CO ₂ /tonne carbonate)
Limestone - CaCO ₃	0.43971
Magnesite - MgCO ₃	0.52197
Dolomite - CaMg(CO ₃) ₂	0.47732
Siderite - FeCO ₃	0.37987
Ankerite - Ca(Fe,Mg,Mn)(CO ₃) ₂	0.47572
Rhodochrosite - MnCO ₃	0.38286
Sodium Carbonate/Soda Ash – Na ₂ CO ₃	0.41492
Others	Facility specific factor to be determined through analysis or supplier information or using stoichiometric ratio

ON.90 Cement Production

ON.91 Activity Definition

For the purposes of this standard quantification method (SQM):

“Cement production” has the same meaning as in the Regulation.

“Person” means a person that engages in cement production.

ON.92 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.90 – ON.95, in an emission report prepared for a calendar year in respect of cement production at a facility.
- (b) Total annual quantity of CO₂ emissions from clinker production, expressed in tonnes.
- (c) Total monthly quantity of clinker, expressed in tonnes (t);
- (d) Monthly plant-specific emission factor of clinker, expressed in tonnes of CO₂/tonnes of clinker;
- (e) Monthly calcium oxide (CaO) content of clinker, expressed in tonnes of CaO/tonnes of clinker;
- (f) Monthly magnesium oxide (MgO) content of clinker, expressed in tonnes of MgO/tonnes of clinker;
- (g) Monthly non-calcined calcium oxide (CaO) content of clinker, expressed in tonnes of CaO/tonnes of clinker;
- (h) Monthly non-calcined magnesium oxide (MgO) content of clinker, expressed in tonnes of MgO/tonnes of clinker;
- (i) Monthly quantity of non-carbonate raw materials entering the kiln, expressed in tonnes (t);
- (j) Total annual quantity of CO₂ emissions from organic carbon oxidation, expressed in tonnes (t);
- (k) Total annual quantity of raw material consumption, expressed in tonnes (t);
- (l) Annual weighted average carbon content in raw material consumption, expressed in tonnes of C/tonnes of raw material consumption;
- (m) Total annual quantity of CO₂ emissions from cement kiln dust (CKD) not recycled back to the kiln, expressed in tonnes (t);
- (n) Total quarterly quantity of CKD not recycled back to the kiln, expressed in tonnes (t);
- (o) Quarterly plant-specific emission factor of CKD not recycled back to the kiln, expressed in tonnes of CO₂/tonnes of CKD.

- (p) Quarterly calcium oxide (CaO) content of CKD not recycled back to the kiln, expressed in tonnes of CaO/tonnes of CKD;
- (q) Quarterly magnesium oxide (MgO) content of CKD not recycled back to the kiln, expressed in tonnes of MgO/tonnes of CKD;
- (r) Quarterly non-calcined calcium oxide (CaO) content of CKD not recycled back to the kiln, expressed in tonnes of CaO/tonnes of CKD; and
- (s) Quarterly non-calcined magnesium oxide (MgO) content of CKD not recycled back to the kiln, expressed in tonnes of MgO/tonnes of CKD.
- (t) The person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions and production information under subsections (a), (i), and (l). This shall not include the emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

ON.93 Calculation of GHG Emissions from Kilns

- (a) Calculate CO₂ emissions using the GGQM in section 4.A of the GGQR.

ON.94 Sampling, Analysis, and Measurement Requirements

- (a) Sampling, analysis and measurement requirements for this activity shall be done in accordance with section 4B of the GGQR. The monthly plant-specific weight fractions of total calcium (as CaO) and total magnesium (as MgO) in clinker may also be determined using one of the following:
 - (1) Any of the applicable analytical methods listed in the Technical Reference Document section of this Guideline (section 4);
 - (2) The most appropriate method published by a consensus-based standards organization, if such a method exists. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (b) The quantity of limestone and gypsum blended with the clinker shall be determined monthly by direct weight measurement using the same plant instruments used for accounting purposes
- (c) Equipment used to measure the clinker, limestone and gypsum shall be:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.

ON.95 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 4C of the GGQR.

ON.110 CO₂ Capture, CO₂ Transport, CO₂ Injection and CO₂ Storage

ON.111 Activity Definition

If a person required to determine the verification amount in respect of a covered facility elects to identify an amount of carbon dioxide for the purposes of Section 12 of the Regulation in accordance with the eligibility rules in subsection 12(4) of the Regulation, the person shall calculate the carbon capture, transportation and storage in accordance with this standard quantification method.

For the purposes of this standard quantification method (SQM):

“CO₂ Capture” means the capture of CO₂ at a covered facility that was generated in respect of one or more specified GHG activities engaged in at the covered facility during the year.

“CO₂ Transportation” means transporting captured CO₂ for the purposes of its permanent storage.

“CO₂ Storage” means placement and permanent storage of CO₂ in a long term geological formation.

“GHGRP” means the federal Greenhouse Gas Reporting Program under the *Canadian Environmental Protection Act, 1999* (Canada).

ON.112 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, determined for the calendar year using SQM ON.110 – ON.115, in an emission report prepared for the calendar year in respect of a facility:
- (1) Total CO₂ captured at the facility, expressed in tonnes of CO₂e.
 - (2) Total CO₂ captured at the facility that is transported to a geological storage site, expressed in tonnes of CO₂e.
 - (3) Total CO₂ captured at the facility that is permanently stored in a long-term geological storage site, expressed in tonnes of CO₂e.
 - (4) Name of each person or entity that is engaged in the capture of the CO₂ from the facility and the amount of CO₂ it captured, expressed in tonnes of CO₂e.
 - (5) Name of each person or entity that is engaged in the transportation of the CO₂ captured at the facility to the long-term geological storage site, the GHGRP ID number of the person or entity engaged in the transportation or a copy of the report submitted under GHGRP where the transfer of the CO₂ is reported, and the amount of CO₂ it transferred, expressed in tonnes of CO₂e.

- (6) Name of each person or entity that is engaged in the injection of the CO₂ captured at the facility into the long-term geological storage site, the GHGRP ID number of the person or entity engaged in the injection or a copy of the report submitted under GHGRP where the injection of the CO₂ is reported, and the amount of CO₂ it injected, expressed in tonnes of CO₂e.
- (7) Name of each person or entity that operates the long-term geological storage site where the CO₂ captured at the facility is permanently stored, the GHGRP ID number of the person or entity that operates the long-term geological storage site, where applicable, or a copy of the report submitted under GHGRP associated with the storage of the CO₂ where applicable, and the location of the geological storage site.

ON.113 Calculation of Greenhouse Gas Emissions

- (a) The person shall determine the quantity of CO₂ for each step of ON.112 (a)(1) through (a)(3).

ON.114 Sampling, Analysis, and Measurement Requirements

- (a) The person shall ensure the quantity of CO₂ captured and transported reported is based on the use of flow meters and measurement of CO₂ concentrations, in accordance with the following:
 - (1) The most appropriate method published by a consensus-based standards organization; or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used.
 - (2) Using flow meters that are:
 - (i) calibrated according to the manufacturer's instructions where available; or, where not available, calibrated according to practices used for accounting purposes; and
 - (ii) maintained to achieve an accuracy of plus or minus 5 per cent.
- (b) The person shall ensure the quantity of CO₂ injected into the geological storage site reported is based on one of the following:
 - (1) The requirement in section 7.5.5 of CSA Z741-12 on measurement of injected CO₂ (Geological storage of carbon dioxide), or
 - (2) The most appropriate method published by a consensus-based standards organization; or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used.

- (c) The person shall maintain the records of each step of the custody transfers from the capture of the CO₂ to the permanent long-term geological storage of the CO₂, including the transportation and injection of the CO₂.

ON.115 Procedures for Estimating Missing Data

- (a) Whenever sampling, measurement, financial, purchase records, accounting records, or any other data required for the determination of an amount of CO₂ required in this SQM are missing, the person shall ensure that the data is replaced using zero for the quantity of CO₂ captured, CO₂ transported, CO₂ injected and CO₂ stored for the period.

ON.100 Coal Storage

ON.101 Activity Definition

For the purposes of this standard quantification method (SQM):

“Coal storage” has the same meaning as in the Regulation.

“Person” means a person that engages in coal storage.

ON.102 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.100 – ON.105, in an emission report prepared for a calendar year in respect of coal storage at a facility.
- (b) Annual greenhouse gas emissions in tonnes, reported as follows:
 - (1) Total CH₄ emissions.
- (c) Annual coal purchases (tons for U.S.; tonnes for Canada).
- (d) Source of coal purchases:
 - (1) Coal basin.
 - (2) State/province.
 - (3) Coal mine type (surface or underground).

ON.103 Calculation of CH₄ Emissions

Calculate fugitive CH₄ emissions from coal storage piles as specified under subsection (a), (b), or (c) of this section.

- (a) For coal purchased from U.S. sources, calculate fugitive CH₄ emissions using Equation 100-1 and Table 100-1.
- (b) For coal purchased from Canadian sources, calculate fugitive CH₄ emissions using Equation 100-1 and Table 100-2.
- (c) For coal purchased from non-U.S. and non-Canadian sources, the person shall use either ON.103 (a) or ON.103 (b), whichever is the most applicable.

$$CH_4 = \sum_i (PC_i \times EF_i) \times 0.6772 / 1,000$$

Equation 100-1

Where:

- | | | |
|-----------------|---|---|
| CH ₄ | = | Fugitive emissions from coal storage piles for each coal origin category "i", (tonnes of CH ₄ per year); |
| PC _i | = | Purchased coal for each coal origin category "i" (tonnes per year); |
| EF _i | = | Default CH ₄ emission factor for each coal origin category "i" specified by location and mine type from which coal |

originated, provided in Table 100-2 (m³ CH₄ per tonne of coal);
 0.6772 = Methane conversion factor to convert m³ to kg;
 1,000 = Factor to convert kg to tonnes.

ON.104 Sampling, Analysis, and Measurement Requirements

Coal Purchase Monitoring Requirements:

- (a) Facilities may determine the quantity of coal purchased either using records provided by the coal supplier(s) or monitoring coal purchase quantities using the same plant instruments used for accounting purposes, such as weigh hoppers or belt weigh feeders.

ON.105 Procedures for Estimating Missing Data

When the missing data relate to the total quantity of coal purchased, the replacement data shall be generated from best estimates based on all of the data relating to the processes.

Table 100-1 - U.S. Default Fugitive Methane Emission Factors from Post-Mining Coal Storage and Handling (CH₄ m³ per Tonne)

Coal Origin Coal Basin	Coal Origin States	Coal Mine Type Surface Post-Mining Factors	Coal Mine Type Underground Post-Mining Factors
Northern Appalachia	Maryland, Ohio, Pennsylvania, West Virginia North	0.6025	1.4048
Central Appalachia (WV)	Tennessee, West Virginia South	0.2529	1.3892
Central Appalachia (VA)	Virginia	0.2529	4.0490
Central Appalachia (E KY)	East Kentucky	0.2529	0.6244
Warrior	Alabama, Mississippi	0.3122	2.7066
Illinois	Illinois, Indiana, Kentucky West	0.3465	0.6525
Rockies (Piceance Basin)	Arizona, California, Colorado, New Mexico, Utah	0.3372	1.9917
Rockies (Uinta Basin)		0.1623	1.0083
Rockies (San Juan Basin)		0.0749	1.0645
Rockies (Green River Basin)		0.3372	2.5068
Rockies (Raton Basin)		0.3372	1.2987
N. Great Plains	Montana, North Dakota, Wyoming	0.0562	0.1592
/ West Interior (Forest City, Cherokee Basins)	Arkansas, Iowa, Kansas, Louisiana, Missouri, Oklahoma, Texas	0.3465	0.6525
West Interior (Arkoma Basin)		0.7555	3.3591

West Interior (Gulf Coast Basin)		0.3372	1.2987
Northwest (AK)	Alaska	0.0562	1.6233
Northwest (WA)	Washington	0.0562	0.5900

Table 100-2. Canada Default Fugitive Methane Emission Factors from Post-Mining Coal Storage and Handling (CH₄ m³ per tonne)

Coal Origin Province	Coal Origin Coalfield	Coal Mine Type Surface Post-Mining Factors	Coal Mine Type Underground Post-Mining Factors
British Columbia	Comox	0.500	n/a
	Crowness	0.169	n/a
	Elk Valley	0.900	n/a
	Peace River	0.361	n/a
	Province Average	0.521	n/a
Alberta	Battle River	0.067	n/a
	Cadomin-Luscar	0.709	n/a
	Coalspur	0.314	n/a
	Obed Mountain	0.238	n/a
	Sheerness	0.048	n/a
	Smokey River	0.125	0.067
	Wabamun	0.176	n/a
	Province Average	0.263	0.067
Saskatchewan	Estavan	0.055	n/a
	Willow Bunch	0.053	n/a
	Province Average	0.054	n/a
New Brunswick	Province Average	0.060	n/a
Nova Scotia	Province Average	n/a	2.923

ON.40 Electricity and Heat Generation

ON.41 Activity Definition

For the purposes of this standard quantification method (SQM):

“Electricity and heat generation” has the same meaning as in the Regulation.

“Person” means a person that engages in electricity and heat generation.

ON.42 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.40 – ON.45, in an emission report prepared for a calendar year in respect of electricity generation at a facility. For fuel combustion and flaring emissions from electricity generation, the person shall report using ON.20.
- (b) Total annual quantity of CO₂ emissions from acid gas scrubbing, expressed in tonnes (t).
- (c) Total annual consumption of limestone or other sorbent, by sorbent type, expressed in tonnes (t).

ON.43 Calculation of Greenhouse Gas Emissions

- (a) Calculation of CO₂ Emissions. The person shall calculate CO₂ emissions from electricity and heat generation using ON.23.
- (b) Calculation of CH₄ and N₂O Emissions. The person shall calculate CH₄ and N₂O emissions from electricity and heat generation using ON.24.
- (c) Calculation of CO₂ Emissions from Acid Gas Scrubbing. The person that uses acid gas scrubbers or adds an acid gas reagent to the combustion unit shall calculate CO₂ emissions using the GGQM in section 7.C of the GGQR.

ON.44 Sampling, Analysis, and Measurement Requirements

- (a) The person that is required to monitor fuel consumption pursuant to this SQM or is using a CEMS shall do so in accordance with ON.25.
- (b) The person that is required to report CO₂ emission from acid gas scrubbers or acid gas reagent is required to measure the parameters required in section 7.D(2) of the GGQR.

ON.45 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 7.E of the GGQR.

ON.60 Electricity Importation

ON.61 Activity Definition

“Balancing authority area” means the metered boundaries of the collection of generation, transmission, and loads of a balancing authority.

“Balancing authority” means an entity that maintains load-interchange-generation balance within a balancing authority area, and supports frequency in real time.

“Electricity generating facility” means a facility that generates electricity and includes one or more electricity generating units at the same location.

“Electricity generation unit” is the physically connected equipment that operate together to produce electricity at the same location.

“Electricity importer” means a person who engages in electricity importation.

“Electricity transaction” means the purchase, sale, import, export or exchange of electric power.

“Environmental attributes” means environmental premiums or tradeable instruments that are recognized as being derived from the generation of electricity.

“e-tag” means North American Energy Standards Board (NAESB) energy tag.

“Frequency in real time” means maintaining interconnection frequency at 60 hertz (Hz).

“Market participant” has the same meaning as in subsection 2(1) of the *Electricity Act, 1998*.

“Megawatt hour” or “MWh” means the electrical energy unit of measure equal to one million watts of power supplied to, or taken from, an electric circuit steadily for one hour.

“Metered boundaries” means boundaries between adjacent balancing authority areas as defined by tie line meters that record the flow of energy between the balancing authority areas.

“Power contract” means an arrangement for the purchase of electricity including but not limited to power purchase agreements and tariff provisions.

“Scheduled quantity” means the final amount listed in the e-tag that is approved by all balancing authority areas on the transmission path specified on the e-tag.

“Sink balancing authority area” means the balancing authority area that is the final destination of electricity on an e-tag.

“Sink” when used in a reference to electricity importation means imported electricity that is consumed in a given jurisdiction.

“Source balancing authority area” means the balancing authority area that is the origin of the electricity on an e-tag.

“Specified electricity generator” means an electricity generation unit, facility or new additional capacity outside of Ontario that started generation on or after January 1, 2017.

“Specified imported electricity” means electricity imported from a specified electricity generator which:

- (a) Is generated, at an output level at least equal to the scheduled quantity, by that generator at the time of the import transaction;
- (b) Is transmitted to Ontario;
- (c) Can be matched to a specific reported electricity transaction by evidence of the electricity importer’s rights to the scheduled quantity of electricity from that generator at the time of the import transaction through:
 - (1) Full or partial ownership of that generator by the electricity importer;
 - (2) Its identification in a power contract between the electricity generator and the electricity importer, and
 - (3) Documented in an e-tag indicating the balancing authority area in which that generator is located as the source balancing authority area and Ontario as the sinking balancing authority area in accordance with ON.65.

“Station service” does not include electrical power produced by a cogeneration system for the purposes of a production process that is not an electricity power production process.

“Unspecified imported electricity” means imported electricity that is not specified imported electricity.

“Wheeled electricity” is imported electricity that is identified in the e-tag of a transaction that shows Ontario as an intermediate balancing authority on the transmission path and does not show Ontario as the sink balancing authority area.

ON.62 Greenhouse Gas Reporting Requirements

- (a) The electricity importer shall set out the following information, calculated for the calendar year using SQM ON.60– ON.65, in the report prepared for a calendar year in respect of electricity importation.
- (b) Annual quantity of specified and unspecified imported electricity used in the calculations contained in ON.63 and ON.64, expressed in MWh.
- (c) The following information for each specified electricity generating facility from which the electricity importer imports electricity:

- (1) The facility name;
 - (2) The facility ID;
 - (3) If applicable, the electricity generating unit ID;
 - (4) Annual scheduled quantity of specified imported electricity used in ON.63, expressed in MWh; and
 - (5) Annual scheduled quantity of specified imported electricity wheeled through Ontario, expressed in MWh.
- (d) Report the following information for each balancing authority area from which unspecified electricity originated:
- (1) The name of the balancing authority area;
 - (2) Annual scheduled quantity of unspecified imported electricity used in ON.64, expressed in MWh; and
 - (3) Annual scheduled quantity of unspecified imported electricity wheeled through Ontario, expressed in MWh.

ON.63 Calculation of Specified Imported Electricity

The electricity importer shall use Equation 60-1 to calculate the amount of specified imported electricity imported in the year. All imported electricity that meets the definition of specified imported electricity must be reported using this calculation.

$$MWh_s = \sum_{i=1}^n [MWh_{total_i} - MWh_{wheel_i}]$$

Equation 60-1

Where:

- MWh_s = Annual Scheduled quantity of specified imported electricity imported into Ontario by the electricity importer, expressed in MWh.
- MWh_{total_j} = Scheduled quantity of specified imported electricity recorded in each e-tag “i” that is imported into Ontario by the electricity importer, expressed in MWh.
- MWh_{wheel_j} = Scheduled quantity of specified imported electricity recorded in each e-tag “i” that is imported into Ontario by the electricity importer that is wheeled through Ontario, expressed in MWh.

ON.64 Calculation of Unspecified Imported Electricity

The electricity importer shall use Equation 60-2 to calculate the unspecified imported electricity from each source balancing authority area that sinks in Ontario.

$$MWh_u = \sum_{i=1}^n \sum_{j=1}^n [MWh_{total_ij} - MWh_{wheel_ij}]$$

Equation 60-2

Where:

- MWh_u = Annual Scheduled quantity of unspecified imported electricity imported into Ontario by the electricity importer, expressed in MWh.
- MWh_{total_ij} = Scheduled quantity of unspecified imported electricity recorded in each e-tag for source balancing authority “i” and peak/off period “j” that is imported into Ontario by the electricity importer, expressed in MWh.
- MWh_{wheel_ij} = Scheduled quantity of unspecified imported electricity recorded in each e-tag for source balancing authority “i” and peak/off period “j” that is imported into Ontario by the electricity importer that is wheeled through Ontario, expressed in MWh.

ON.65 Measurements and Documentation Requirements

(a) Meter Data Requirement:

Importers of specified electricity shall retain metered generation data required to demonstrate that the electricity claimed by the electricity importer was generated by the facility or unit at the time the power was directly delivered.

The meter generation data shall be based on records from a revenue meter of the actual generation injected into the grid.

(b) E-tag documentation:

Electricity importers are identified as the Purchasing Selling Entity on the Physical Path of the e-tag before it enters Ontario.

All electricity importers shall retain records of the e-tag transactions which they scheduled with the pools and balancing authorities in the transmission path.

Electricity Importers shall retain e-tags indicating the source balancing authority area in which a specified electricity generator is located, the source balancing authority area that the unspecified electricity originated from, and Ontario as the sinking balancing authority area.

Electricity importers shall keep records of e-tags showing the full transmission path in the physical path table of a single or multiple NERC e-tag from the first point of receipt at the source balancing authority area to the final point of delivery at the sink balancing authority area.

ON.20 Fuel Combustion and Flaring

ON.21 Activity Definition

For the purposes of this standard quantification method (SQM):

“Agent” means an individual, group of individuals or corporation authorized to act for and on behalf of an RNG supplier or the person in respect to the transfer, transport, purchase or sale of the RNG.

“Contiguous record” means a record that documents that the transport of RNG associated with the value of the scheduled RNG quantity is uninterrupted and connected by receipt and delivery locations in the RNG transfer record.

“Custody transfer” means the change of title, ownership or control of RNG from one party to another party.

“Delivery point” means the physical location in the natural gas pipeline system where the custody of RNG changes from the RNG supplier or an agent of the RNG supplier to the person or the agent of the person.

“Final destination” means the location where purchased RNG, transported with a contiguous record of transfers through the natural gas pipeline system, is used.

“Fuel combustion and flaring” has the same meaning as in the Regulation.

“Natural gas pipeline system” means the natural gas transmission and natural gas distribution system in Ontario.

“Scheduled RNG quantity” means the amount of gas listed in the RNG transfer record of the natural gas pipeline system as being scheduled for transfer, based on the records of the natural gas pipeline system operators.

“Person” means a person that engages in fuel combustion and flaring.

“Renewable natural gas” or “RNG” has the same meaning as in the Regulation.

“RNG contract” means an agreement between the person and the RNG supplier or agent for the purchase of RNG.

“RNG facility” means a facility that produces gas from biomass that is to be added to the natural gas pipeline system.

“RNG source” means the location in Ontario where the RNG is physically added to the Ontario natural gas pipeline system and may be listed instead as the origin of the RNG in the transfer record.

“RNG supplier” means an individual, group of individuals or corporation who engages in the collection of RNG from one or more RNG facilities for sale or transfer from a RNG source to a delivery point, or to the person.

“RNG transfer record” means a record generated by the natural gas pipeline system operator showing the following information:

- (1) Scheduled RNG quantities,
- (2) RNG source,
- (3) Custody transfers and locations of custody transfers, and
- (4) Final destination of the RNG.

ON.22 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.20 – ON.26, in an emission report prepared for a calendar year in respect of fuel combustion or flaring at a facility.
- (b) Any person subject to this SQM and whose facility is classified under NAICS 221112 shall use ON.20 to report the total annual quantity, expressed in tonnes (t), of CO₂, CH₄ and N₂O emissions, by fuel type and source, from
 - (1) each electricity generating unit;
 - (2) heat and steam generation;
 - (3) all other stationary fuel combustion;
 - (4) on-site transportation; and
 - (5) flaring.
- (c) Any person that is subject to this SQM but not subject to subsection (b) above shall report the total annual quantity, expressed in tonnes (t), of CO₂, CH₄ and N₂O emissions, by fuel type and source, from
 - (1) electricity generation;
 - (2) heat and steam generation;
 - (3) all other stationary fuel combustion;
 - (4) on-site transportation; and
 - (5) flaring.
- (d) Any person subject to this SQM shall report the methods used to quantify each greenhouse gas under subsections (b) and (c) of this section, by fuel type and source.
- (e) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS at the facility to report the total emissions of CO₂, CH₄ and N₂O. The person shall report their fuel information by fuel type, in accordance with subsections (f) and (g) below.
- (f) Any person subject to this SQM shall, for each fuel reported under subsections (b) and (c) report the

- (1) gaseous quantities, expressed in cubic metres (m³) or in megajoules (MJ);
 - (2) solid quantities, expressed in tonnes (t), for coal by rank and by country, province and state; and
 - (3) liquid quantities, expressed in kilolitres (kl) or in megajoules (MJ).
- (g) Any person subject to this SQM may, for each fuel reported under subsections (b) and (c), report the annual:
- (1) higher heating value calculated using Equation 2-26 in section 2 of the GGQR, expressed in megajoules (MJ) higher heating value per unit of fuel consumed for all methods, except when applying Equation 2-2, Equation 2-4, Equation 2-11, Equation 2-19 or Equation 2-21 of the GGQR;
 - (2) carbon content calculated using Equation 2-27 in section 2 of the GGQR, expressed in kilograms of carbon per unit of fuel consumed. A facility shall report the carbon content, when using a CEMS or the variable fuels or flaring methods (except when applying Equation 2-9, Equation 2-11, Equation 2-20 and for fuels identified in Table 2-3 of the GGQR);
 - (3) temperature, expressed in degrees Celsius (°C) and pressure, expressed in kilopascals (kPa), for gaseous quantities (if higher heating value or carbon content are reported under standard temperature and pressure, report the standard temperature and pressure in this section);
 - (4) moisture content, expressed as a percentage (per cent), for solid quantities; and
 - (5) CH₄ and N₂O emission factors, when using the facility-specific emission factors measured directly or provided by the fuel supplier or equipment manufacturers, expressed in grams per unit of fuel.
- (h) Any person subject to this SQM shall, for each fuel reported under subsections (b) and (c), report the default CO₂, CH₄ and N₂O emission factors, when using values presented in Table 2-1 to Table 2-12 and in Equation 2-20, Equation 2-22 and Equation 2-23 of the GGQR.
- (i) Any person subject to this SQM shall report, for each fuel, the combustion oxidation factor when applied and provide supporting documentation used in its derivation.
- (j) Any person subject to this SQM shall, for steam used to quantify emissions under subsections (b) and (c) above, report the
- (1) steam quantities expressed in tonnes (t);

- (2) quantity and type of each biomass fuel combusted expressed in tonnes (t);
 - (3) CO₂, CH₄ and N₂O emission factors expressed in kilograms of CO₂, CH₄ and N₂O/megajoules (MJ) of steam or kilograms of CO₂, CH₄ and N₂O /tonnes (t) of steam; and
 - (4) measured temperature, expressed in degrees Celsius (°C), the measured pressure expressed in kilopascals (kPa) and the ratio of the boiler's design rated heat input capacity to its design rated steam output capacity, expressed in megajoules (MJ)/tonnes of steam, if using the steam default emission factor method.
- (k) Any person subject to this SQM and whose facility is classified under NAICS 221112 shall report the annual quantities of
- (1) gross electricity generated on-site by each electricity generating unit, expressed in megawatt hours (MWh);
 - (2) electricity sold off-site, expressed in megawatt hours (MWh);
 - (3) electricity lost on-site, expressed in megawatt hours (MWh); and
 - (4) electricity purchased, expressed in megawatt hours (MWh).
- (l) Any person subject to this SQM who is not subject to section (b) above or is not engaged in operation of a natural gas pipeline system may report the annual quantities of
- (1) gross electricity generated on-site, expressed in megawatt hours (MWh);
 - (2) electricity sold off-site, expressed in megawatt hours (MWh);
 - (3) electricity lost on-site, expressed in megawatt hours (MWh); and
 - (4) electricity purchased, expressed in megawatt hours (MWh).
- (m) Any person subject to this SQM who operates one or more cogeneration system or purchases or sells steam or heat shall report the annual quantities of
- (1) gross steam and heat generated on-site, expressed in megajoules (MJ);
 - (2) gross steam and heat used to generate electricity on-site, expressed in megajoules (MJ);
 - (3) steam and heat sold off-site, expressed in megajoules (MJ);
 - (4) steam and heat purchased, expressed in megajoules (MJ).
- (n) Any person subject to this SQM shall submit documentation describing the methodology used, when
- (1) developing equipment-specific on-site transportation emission factors, as required by section 2.A.1a(3) or 2.B(3)(B) of the GGQR;

- (2) determining the mass of biomass combusted for premixed fuels containing biomass and fossil fuels, as required by section 2.A.4 of the GGQR; or
 - (3) developing facility-specific CH₄ and N₂O emission factors, as required by section 2.B(1) of the GGQR.
- (o) Any person subject to this SQM, who obtains from a supplier or performs fuel sampling, analysis and consumption measurement, as required in section 2.D of the GGQR, shall submit a fuel quantity, carbon content and higher heating value for all sampling and measurement periods.
 - (p) Annual CO₂ emissions from the use of sorbent calculated in accordance with ON.23(d).
 - (q) Emissions from flaring that are reported under ON.350 are not to be reported under ON.20.

ON.22.1 RNG Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.23.1 and ON.25.1 in the report prepared for a calendar year in respect of RNG CO₂ quantities reported for the purposes of “F” in the formula in subsection 12(2) of the Regulation:
 - (1) Annual RNG CO₂ quantity, calculated using the methods in ON.23.1, expressed in tonnes of CO₂.
 - (2) The following information on an annual basis for each RNG supplier:
 - (i) The name of the RNG supplier;
 - (ii) The RNG source(s) associated with the RNG supplier;
 - (iii) The RNG quantity added at the RNG source in item (ii) (expressed in GJ) with a final destination at the person’s covered facility;
 - (iv) The total annual scheduled RNG quantity for each RNG quantity listed in item (iii) (expressed in GJ);
 - (v) The final destination of the RNG in each record of the scheduled quantity of RNG listed in item (iv); and
 - (vi) The annual RNG CO₂ quantity associated with the RNG quantities referred to in item (iv) (expressed in tonnes of CO₂).

ON.23 Calculation of CO₂ Emissions

The person shall calculate the annual CO₂ emissions from fuel combustion and flaring as follows:

- (a) Any person subject to this SQM is not required to report fuels and their associated emissions when the sum of CO₂, CH₄ and N₂O emissions

(excluding CO₂ from biomass combustion), in CO₂e., from the combustion of one or more of the fuels does not exceed 0.5 per cent of the total facility GHG emissions from all fuels combusted (excluding CO₂ from biomass combustion).

- (b) Calculate CO₂ emissions from fuel combustion using the GGQM in section 2.A of the GGQR.
- (c) Calculate CO₂ emissions from flares using the GGQM in section 2.C of the GGQR.
- (d) Calculate CO₂ emissions where low Btu gases (e.g., coker flue gas, gases from vapour recovery systems, vents from storage tanks) are destroyed using methods other than flares using the GGQM in section 2.C.3 of the GGQR.
- (e) Calculation of CO₂ from the use of sorbent.
 - (1) Where the person operates a fluidized bed boiler that is equipped with a wet flue gas desulphurization system, or uses other acid gas emission controls with sorbent injection, the person shall calculate CO₂ emissions using:
 - (i) Data from a CEMS; or
 - (ii) Where a CEMS is not available, using Equation 20-1:

$$CO_2 = S \times R \times \left(\frac{MW_{CO_2}}{MW_S} \right)$$

Equation 20-1

Where:

- CO₂ = Annual CO₂ emissions from the use of sorbent, expressed in tonnes.
- S = Quantity of limestone or other sorbent used in the calendar year, from company records, expressed in tonnes.
- R = The calcium-to-sulphur stoichiometric ratio which has a value of 1.00, or is determined based on actual sorbent used.
- MW_{CO₂} = Molecular weight of carbon dioxide.
- MW_S = Molecular weight of sorbent.

- (f) Notwithstanding ON.23(a) through (c) the person is not required to calculate emissions from the combustion of process gas that is transferred from a facility where the amount of process gas that is transferred is included in paragraphs (d)(14), (e)(8) or (j)14 of ON.152 in a report required to be submitted by the other facility under the Regulation.

(g) Where a quantity of natural gas is delivered by a natural gas distributor to a person's facility and the following criteria apply:

- (1) The natural gas is recorded by the natural gas meter for the facility; and
- (2) Some or all of the natural gas that is recorded by the natural gas meter for the facility is used by another facility.

The person is required to include the quantity of natural gas used by the other facility in the value of: "fuel" in ON.23(a) through (c).

(h) The person that is required to quantify and, where applicable, report the GHG emissions from the other facility mentioned in subsection (g) shall not include the quantity of natural gas received from the facility mentioned in subsection (g) in the value of: "fuel" in calculations under subsections ON.23(a) through (c).

(i) If a person referenced in subsection (h) is quantifying emissions using a CEMS, the person shall subtract emissions from the use of the fuel provided to them from the emissions calculated using the CEMS. The emissions from the subtracted fuel shall be calculated using ON.23(a) through (c).

(j) The CO₂ from the combustion of landfill gas or biogas may be calculated using ON.190 for the calculation of CO₂ emissions instead of the methods in subsections (b) through (d).

(k) Emissions from the combustion of RNG that is not delivered directly to the facility and combusted at the facility shall not be reported as biomass CO₂ emissions at the facility under ON.20.

ON.23.1 Calculation of RNG CO₂ Quantity

(a) The person shall only determine the annual RNG CO₂ Quantity from RNG for the purposes of "F" in the formula in subsection 12(2) of the Regulation if all of the following criteria are met:

- (1) There is an RNG contract or contracts which stipulate that the final destination is the person's covered facility;
- (2) There is an RNG transfer record or records showing:
 - (i) The RNG source is in Ontario; and
 - (ii) The RNG transport and a contiguous record of custody transfers.
- (3) The final destination of the RNG is the person's covered facility.

(b) The person has not reported the RNG associated with RNG in any of the RNG transfer records as CO₂ from the combustion of biomass in ON.23(b).

(c) The person described in subsection (a) shall use Equation 20-2 to calculate the annual RNG CO₂ quantity for RNG used as a value for "F" in the formula in s. 12(2) of the Regulation:

$$E_{RNG} = \sum_{i=1}^n V_i \times CC_i \times Bio_i \times 3.664 - \sum_{j=1}^m V_j \times CC_j \times Bio_j \times 3.664$$

Equation 20-2

Where:

- E_{RNG} = RNG CO₂ quantity, expressed in tonnes of CO₂
- i = the number of RNG transfer records
- V_i = the scheduled RNG quantity shown in the RNG transfer record “i” that is delivered to the final destination, expressed in gigajoules (GJ)
- CC_i = total carbon content of the RNG, expressed in tonnes of carbon per GJ of RNG, calculated using either the:
- (i) monthly average gas composition (in units of tonnes of carbon per m³), divided by high heat value (in units of GJ/m³), as published or provided by a natural gas pipeline system operator; or
 - (ii) lowest value of the measured gas composition (in units of tonnes of carbon per m³) divided by the high heat value (in units of GJ/m³), at a location in the natural gas pipeline system transfer record.
- Bio_i = the fraction of the gas added that is biomass for each RNG transfer record, expressed as a fraction (volume over volume, or mole over mole). This is the fraction of the carbon content that is biomass in the RNG at the point the RNG is added to the natural gas pipeline system.
- j = the number of RNG transfer out records
- V_j = quantity of any RNG that is transferred out of the person’s covered facility, or to another owner/operator within the person’s covered facility if the emissions related to the transferred RNG are not reported by the person’s covered facility, expressed in gigajoules (GJ)
- CC_j = total carbon content of RNG, expressed as tonnes of carbon per gigajoule (GJ) of RNG
- Bio_j = the fraction of the gas transferred out of the person’s covered facility that is biomass for each RNG transfer record, expressed as a fraction (volume over volume, or mole over mole)

(d) If the value of E_{RNG} from Equation 20-2 is a negative number, it is deemed to be zero.

- (e) Where natural gas is added to the scheduled RNG quantity in the transfer record, the person must deduct the amount of natural gas added from the determination of the RNG quantity.

ON.24 Calculation of CH₄ and N₂O Emissions

- (a) The person shall calculate the annual CH₄ and N₂O emissions from fuel combustion as follows:
 - (1) Calculate CH₄ and N₂O emissions from fuel combustion using the GGQM in section 2.B of the GGQR.
 - (2) Calculate CH₄ and N₂O emissions from flaring using the GGQM in section 2.C of the GGQR.
- (b) The person may elect to use engineering estimates to calculate the annual CH₄ and N₂O emissions for fuels that are not listed in the tables in section 2.B of the GGQR.
- (c) Where a quantity of natural gas is delivered by a natural gas distributor to a person's facility and the following criteria apply:
 - (1) The natural gas is recorded by the natural gas meter for the facility; and
 - (2) Some or all of the natural gas that is recorded by the natural gas meter for the facility is used by another facility.

The person is required to include the quantity of natural gas used by the other facility in the calculating of emission in subsections (a) through (c) of this section.

- (d) The person that is required to quantify and, where applicable, report GHG emissions from the other facility mentioned in subsection (c) shall not include the quantity of natural gas received from the facility mentioned in calculating the emission in subsections (a) through (c) of this section.
- (e) If a person referenced in subsection (e) is quantifying emissions using a CEMS, the person shall subtract emissions from the use of the fuel provided to them from the emissions calculated using the CEMS. The emissions from the subtracted fuel shall be calculated using subsections (a) through (c) of this section.

ON.25 Sampling, Analysis, and Measurement Requirements

Fuel Sampling Frequency Requirements:

- (a) Where a calculation in this SQM requires obtaining fuel samples, the person shall obtain those samples in accordance with section 2.D.1 of the GGQR.

Fuel Consumption Monitoring Requirements:

- (b) Where a calculation in this SQM requires monitoring of fuel consumption the person shall monitor in accordance with section 2.D.2 of the GGQR.

- (c) The person required to report emissions by fuel type and source under ON.22(b) and (c) may use engineering estimates to calculate the breakdown of fuel usage for determining the emissions by fuel type and source.
- (d) The person required to determine quantities of fuel in accordance with this method shall calibrate orifice, nozzle, and venturi flow meters using in-situ calibration of the differential pressure (ΔP), total pressure, and temperature transmitters.

Fuel Heat Content Monitoring Requirements:

- (e) The person required to monitor heat content of gaseous fuels in accordance with this method shall do so in accordance with the following rules:
 - (1) Using any applicable analytical methods listed in the Technical Reference Document section of this Guideline;
 - (2) Using the most appropriate method published by a consensus-based standards organization; or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used.
 - (3) For natural gas, using methods and requirements in accordance with the requirements under the Weights and Measures Act, R.S.C., 1985, c. W-6 or the Electricity and Gas Inspection Act, R.S.C., 1985, c. E-4.
 - (4) Using on-line instrumentation that determines heating value accurate to within ± 5.0 per cent and, where such instrumentation provides only low heat value, the person shall convert the value to high heat value using Equation 20-2 in accordance with the following:
 - (i) When the heating value of natural gas is being measured the value of CF shall be 1.11.
 - (ii) Where the heating value of refinery fuel gas or mixtures of refinery fuel gas is being measured, the CF shall be determined as a fuel-specific weekly average CF using the following:
 - (A) Concurrent LHV and HHV measurements determined by on-line instrumentation or laboratory analysis as part of the daily carbon content determination; or
 - (B) The HHV/LHV ratio obtained from the laboratory analysis of the daily samples.

$$HHV = LHV \times CF$$

Equation 20-3

Where:

- HHV = Fuel or fuel mixture high heat value, expressed in MJ per Sm³.
- LHV = Fuel or fuel mixture low heat value, expressed in MJ per Sm³.
- CF = Conversion factor.

- (f) The person shall conduct fuel heat content monitoring of all solid and liquid fuel, including biomass and waste derived fuels, in accordance with the following:
- (1) Using any applicable analytical methods listed in the Technical Reference Document section of this Guideline;
 - (2) Using the most appropriate method published by a consensus-based standards organization; or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used.
- (g) The person that is required to use the weighted annual heat content of a fuel shall do so in accordance with section 2.D.3(6) of the GGQR.
- (h) The person that is required to monitor black liquor heat content shall do so in accordance with section 2.D.3(5) of the GGQR.

Fuel Carbon Content Monitoring Requirements:

- (i) The person required to determine fuel carbon content and either molecular weight or molar fraction for gaseous fuels shall use the results of fuel sampling and analysis received from the fuel supplier or results determined by the person using the following:
- (1) Any applicable analytical methods listed in the Technical Reference Document section of this Guideline;
 - (2) The most appropriate method published by a consensus-based standards organization or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used; or
 - (3) For natural gas, using methods and requirements in accordance with the requirements under the *Weights and Measures Act, R.S.C., 1985, c. W-6* or the *Electricity and Gas Inspection Act, R.S.C., 1985, c. E-4*.

- (j) The person that is required to determine the carbon content of solid or liquid fuel including biomass and waste-derived fuels shall use the results of fuel sampling and analysis received from the fuel supplier or results determined by the person using the following.
 - (1) Any applicable analytical methods listed in the Technical Reference Document section of this Guideline;
 - (2) The most appropriate method published by a consensus-based standards organization; or where no appropriate method is published by a consensus-based standards organization, using industry standard methods, noting where such methods are used and what methods are used.
- (k) The person that is required to calculate the carbon content of refinery fuel gas and flexigas pursuant to this method shall do so in accordance with section 2.D.4(3) of the GGQR.
- (l) The person that is required to calculate the weighted annual average carbon content pursuant to this method shall do so in accordance with section 2.D.4(5) of the GGQR.

Fuel Analytical Data Capture:

- (m) If the fuel analytical capture rate is between 80 per cent and 100 per cent for any emission source, use the methods in ON.26 to substitute for the missing value for the period of missing data.

On-site Transportation Consumption of Biofuel:

- (n) The person that is required to determine the fuel and emission factors pursuant to this method shall do so in accordance with section 2.D.6 of the GGQR.

Flares and Other Control Devices:

- (o) The person that is required to monitor flow rates, carbon content or HHV for flares and other control devices pursuant to this method shall do so in accordance with section 2.D.7 of the GGQR.

ON.25.1 Sampling, Analysis, and Measurement Requirements for RNG

- (a) The person that calculates CO₂ emissions from RNG in accordance with ON 23.1 shall create and retain the following records for RNG used as a value for “F” in the formula in s.12(2) of the Regulation:
 - (1) RNG contracts which shall contain:
 - (i) The name and location of the RNG supplier, and agent as applicable;
 - (ii) The names, locations and types of RNG facilities;
 - (iii) The location of the RNG source;

- (iv) The name and location of the final destination which shall be the person's covered facility;
 - (v) The supply quantities of RNG purchased including, where applicable, information about contract quantities, deliveries, minimum quantities and maximum quantities);
 - (vi) The timing for the deliveries of the RNG and length of contracts including, where applicable delivery periods, months, year; and
 - (vii) The shipping and custody transfers information.
- (2) RNG transfer record(s) for each scheduled RNG quantity transferred from the RNG supplier to the person's covered facility, including the following:
- (i) Records showing the dates and a contiguous record of custody transfers from the RNG supplier to the person's covered facility;
 - (ii) For an RNG supplier that adds RNG for multiple customers into the natural gas pipeline system at the RNG source, transfer records showing a contiguous record of scheduled gas quantities:
 - (A) from the RNG source to where the RNG supply is split for delivery to different customers
 - (B) from the location where the RNG supply is split and transferred to the person's covered facility
 - (iii) For an RNG supplier that adds RNG only for the person, transfer records showing a contiguous record of the scheduled gas quantity from the RNG source to the person's covered facility.
 - (iv) Monthly and annual gas delivered and received associated with the RNG quantities.
- (3) Biomass fraction of each RNG transfer
- (4) Record of any RNG quantity that is transferred to another facility or to a different owner or operator within the person's covered facility.
- (b) Where RNG is provided to the natural gas pipeline system operators for the purpose of transporting the customer's nomination quantity, the natural gas pipeline system operator may use the record for that fuel quantity as the RNG quantity in Equation 20-2 if that quantity is not included in any other covered facility's RNG transfer record.
- (c) The person shall determine the biomass fraction (Bio_i) of each RNG quantity that is added into the natural gas pipeline system. The determination of biomass fraction shall be at a frequency of at least quarterly for each RNG contract if a delivery period covers a period of more than three months.

- (d) If the gas added at the RNG source is a mixture of biomass and fossil fuels, the person shall determine the fraction of biomass in accordance with section 2.A of the GGQR.
- (e) The person shall determine RNG quantities using direct measurement (based on measured volumes and high heat value), or measurements or records provided by the natural gas pipeline system operator.

ON.26 Procedures for Estimating Missing Data

- (a) Missing data requirements for this activity shall be estimated in accordance with section 2.E of the GGQR.

ON.140 Glass Production

ON.141 Activity Definition

For the purposes of this standard quantification method (SQM):

“Glass production” has the same meaning as in the Regulation.

“Person” means a person that engages in glass production.

ON.142 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.140 – ON.145, in an emission report prepared for a calendar year in respect of glass production at a facility.
- (b) Total CO₂ process emissions from all glass melting furnaces (tonnes).
- (c) If a CEMS is not used to determine CO₂ emissions from glass melting furnaces, and process CO₂ emissions are calculated according to the procedures specified in ON.143(b), report the following information:
 - (1) Annual quantity of each carbonate-based raw material charged for all furnaces combined (tonnes).
 - (2) Total number of glass melting furnaces.

ON.143 Calculation of CO₂ Emissions

The person shall calculate the annual CO₂ process emissions from each glass melting furnace using the procedure in subsections (a) and (b) of this section.

- (a) Calculate and report the process and combustion CO₂ emissions by operating and maintaining a CEMS according to ON.23 or using the GGQM in section 2.A.3 of the GGQR if a CEM is required under ON.23. The CO₂ process emission is the reported process and combustion emission from the CEMS minus the amount of CO₂ emissions calculated using ON.143(b)(2).
- (b) For each glass melting furnace that is not reported under subsection (a) of this section, use either the procedure in paragraph (b)(1) of this section or the procedure in paragraph (b)(2) of this section.
 - (1) Calculate the process and combustion CO₂ emissions separately using the procedures specified in paragraph (b)(1) for process emissions and paragraph (b)(2) for combustion emissions.
 - (i) For each carbonate-based raw material charged to the furnace, obtain the carbonate-based mineral mass fraction from the supplier of the raw material.
 - (ii) Determine the quantity of each carbonate-based raw material charged to the furnace.

- (iii) Apply the appropriate emission factor from Table 140-1 to the method for each carbonate-based raw material charged to the furnace.
- (iv) Use Equation 140-1 of this section to calculate process mass emissions of CO₂ for each furnace:

$$E_{CO_2} = \sum_{i=1}^n (M_i \times MF_i \times EF_i \times F_i)$$

Equation 140-1

Where:

- E_{CO₂} = Process emissions of CO₂ from the furnace (tonnes).
- n = Number of carbonate-based raw materials charged to furnace.
- MF_i = Annual average mass fraction of carbonate-based mineral i in carbonate-based raw material i (weight fraction).
- M_i = Annual amount of carbonate-based raw material i charged to furnace (tonnes).
- EF_i = Emission factor for carbonate-based mineral i (tonnes of CO₂ per tonne of carbonate-based mineral from Table 140-1).
- F_i = Fraction of calcination achieved for carbonate-based mineral i, 1.0 for completed calcination(weight fraction).

- (v) Calculate and report the total process CO₂ emissions from glass melting furnaces at the facility using Equation 140-2 of this section:

$$CO_2 = \sum_{i=1}^k E_{CO_2i}$$

Equation 140-2

Where:

- CO₂ = Annual process CO₂ emissions from glass manufacturing facility (tonnes).
- E_{CO₂i} = Annual CO₂ emissions from glass melting furnace i (tonnes).
- k = Number of glass melting furnaces.

- (2) Calculate and report under ON.20 the combustion CO₂ emissions in the glass furnace according to the applicable requirements in ON.20.

ON.144 Sampling, Analysis, and Measurement Requirements

- (a) The person shall measure annual amounts of carbonate-based raw materials charged to each glass melting furnace from monthly measurements using plant instruments used for accounting purposes, such as calibrated scales or weigh hoppers. Total annual mass of carbonate-based raw material charged to glass melting furnaces at the facility shall be compared to records of raw material purchases for the year.

- (b) The person shall measure carbonate-based mineral mass fractions at least annually to verify the mass fraction data provided by the supplier of the raw material; such measurements shall be based on sampling and chemical analysis conducted by a laboratory using ASTM D3682 or any of the other analytical methods listed in the Technical Reference Document section of this Guideline (section 4), or the most appropriate method published by a consensus-based standards organization. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (c) The person shall determine the annual average mass fraction for the carbonate-based mineral in each carbonate-based raw material by calculating an arithmetic average of the monthly data obtained from raw material suppliers or sampling and chemical analysis. As an alternative to data provided by the raw material supplier, a value of 1.0 can be used for the monthly mass fraction (MF_i) of carbonate-based mineral i in Equation 140-1 of this section.
- (d) The person shall determine on an annual basis the calcination fraction for each carbonate consumed based on sampling and chemical analysis using an industry consensus standard, or use a value of 1.0 for the calcination fraction. This chemical analysis shall be conducted using an x-ray fluorescence test or other enhanced testing method published by an industry consensus-based standards organization. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (e) The person shall measure the quantity of glass production using equipment that is:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.

ON.145 Procedures for Estimating Missing Data

Unavailable analytical data:

- (a) Whenever analytical data relating to sampling are unavailable, the person shall, using the methods prescribed in ON.144, re-analyze the original sample, a backup sample or a replacement sample for the same measurement and sampling period.

Determination of quantity:

(b) Whenever sampling and measurement data required by ON.144 for the calculation of emissions is missing the person shall ensure that the data are replaced using the following missing data procedures:

- (1) When the missing data concern carbon content, temperature, pressure or gas concentration, the person shall,
 - (i) Determine the sampling or measurement rate using the following Equation 140-3:

$$R = \frac{Q_{SAct}}{Q_{SRequired}}$$

Equation 140-3

Where:

- | | | |
|-----------------|---|---|
| R | = | Sampling or measurement rate that was used, expressed as a percentage |
| Q_{SAct} | = | Quantity of actual samples or measurements obtained by the person |
| $Q_{SRequired}$ | = | Quantity of samples or measurements required under ON.144 |

- (ii) Replace the missing data as follows,
 - (A) If $R \geq 0.9$: replace the missing data by the arithmetic mean of the sampling or measurement data from immediately before and after the missing data period. If no data are available from before the missing data period, the person shall use the first available data from after the missing data period;
 - (B) If $0.75 \leq R < 0.9$: replace the missing data by the highest data value sampled or analyzed during the reporting period for which the calculation is made;
 - (C) If $R < 0.75$: replace the missing data by the highest data value sampled or analyzed during the 3 preceding years;
- (2) When the missing data concern raw material consumption, glass production or carbonate consumption, the replacement data shall be generated from best estimates based on all the data relating to the processes.
- (3) For all units subject to the requirements of ON.20 that monitor and report emissions using a CEMS, the missing data backfilling procedures in “Reference method for source testing quantification of carbon dioxide releases by continuous emission monitoring systems from thermal power

generation” shall be followed for CO₂ concentration, stack gas flow rate, fuel flow rate, high heating value, and fuel carbon content.

Table 140-1 - CO₂ Emission Factors for Carbonate-Based Minerals

Carbonate-Based Raw Material – Mineral	CO₂ Emission Factor^a
Limestone – CaCO ₃	0.43971
Dolomite – CaMg(CO ₃) ₂	0.47732
Sodium carbonate/soda ash – Na ₂ CO ₃	0.41492

^a Emission factors in units of tonnes of CO₂ emitted per tonne of carbonate-based mineral charged to the furnace.

ON.120 HCFC-22 Production and HFC-23 Destruction

ON.121 Activity Definition

For the purposes of this standard quantification method (SQM):

“HCFC-22 production and HFC-23 destruction” has the same meaning as in the Regulation.

“Person” means a person that engages in HCFC-22 Production or HFC-23 destruction.

ON.122 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.120 – ON.125, in an emission report prepared for a calendar year in respect of HCFC-22 production and HFC-23 destruction at a facility:
- (b) HFC-23 emissions from HCFC-22 production processes and HFC-23 destruction processes.

ON.123 Calculation of GHG Emissions

- (a) Quantify emissions in accordance with U.S. EPA 40 CFR 98 Subpart O Section 98.153.

ON.124 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance with U.S. EPA 40 CFR 98 Subpart O Section 98.154.

ON.125 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with U.S. EPA 40 CFR 98 Subpart O Section 98.155.

ON.130 Hydrogen Production

ON.131 Activity Definition

For the purposes of this standard quantification method (SQM):

“Hydrogen production” has the same meaning as in the Regulation.

“Person” means a person that engages in hydrogen production.

ON.132 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.130 – ON.135, in an emission report prepared for a calendar year in respect of hydrogen production at a facility.
- (b) Report the
 - (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of CO₂ recovered or captured, expressed in tonnes (t) and whether the CO₂ is for downstream use, on-site production or for permanent storage
 - (3) total annual quantity of hydrogen production, expressed in tonnes (t);
and
 - (4) total annual quantity of hydrogen purchased, expressed in tonnes (t).
- (c) Indicate if the CO₂ under (a)(2) that is recovered or captured is for downstream use, on-site production or for permanent storage.
- (d) Report the total annual quantity of feedstock charged, reported by feedstock type, expressed in:
 - (1) cubic metres (m³), for gaseous quantities;
 - (2) litres (L), for liquid quantities;
 - (3) tonnes (t), for non-biomass solid quantities; and
 - (4) bone-dry tonnes (t), for biomass-derived solid fuel quantities.
- (e) For each feedstock type reported under subsection (d) in this section, report the annual weighted average carbon content expressed in
 - (1) kilograms (kg) of C/kilograms (kg) of feedstock, for gaseous quantities;
 - (2) kilograms (kg) of C/kilograms (kg) of feedstock or kilograms (kg) of C/cubic metres (m³) of feedstock, for liquid quantities; and
 - (3) kilograms (kg) of C/kilograms (kg) of feedstock, for solid quantities.
- (f) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions under paragraphs (b)(1) and (b)(2). This shall not include the

emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

ON.133 Calculation of Greenhouse Gas Emissions

- (a) The person shall calculate CO₂ process emissions using the GGQM in section 10.A of the GGQR.

ON.134 Sampling, Analysis, and Measurement Requirements

- (a) Persons using the feedstock methodology under section 10.A of the GGQR shall follow the procedure under section 10.B of the GGQR.
- (b) Persons shall quantify the hydrogen produced daily using equipment for measuring the production quality that is:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.
- (c) The calibration requirements under subsection (b) do not apply to meters that are used for financial transactions if the supplier and purchaser do not have common owners and are not owned by subsidiaries or affiliates of the same company.
- (d) The person shall use the following methods, as applicable, to determine the carbon content of the feedstocks:
 - (1) Any of the applicable analytical methods listed in the Technical Reference Document section of this Guideline (section 4).
 - (2) The most appropriate method published by a consensus-based standards organization to determine the carbon content of the feedstocks. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.

ON.135 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 10.C of the GGQR.

ON.150 Iron, Steel and Ferroalloy Production

ON.151 Activity Definition

For the purposes of this standard quantification method (SQM):

“Iron, steel and ferroalloy production” has the same meaning as in the Regulation.

“Person” means a person that engages in iron, steel and ferroalloy production.

“Semi-finished steel shapes” means blooms, billets, slabs or ingots from the electric arc furnace or basic oxygen furnace that are later rolled into finished products such as beams, bars, or sheets.

ON.152 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.150 – ON.155, in an emission report prepared for a calendar year in respect of iron, steel and ferroalloy production at a facility
- (b) Report the
 - (1) total annual quantity of biomass consumed, by biomass type, expressed in tonnes (t); and
 - (2) type of use for biomass (such as flux material, reducing agent).
- (c) For an induration furnace, report the
 - (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of green pellets consumption, expressed in tonnes, if using equation 6-1;
 - (3) annual weighted average carbon content of green pellets consumption, expressed in tonnes of C/tonnes of green pellets, if using equation 6-1;
 - (4) total annual quantity of additive material consumption, by material type, expressed in tonnes, if using equation 6-2;
 - (5) annual weighted average carbon content of additive material consumption, expressed in tonnes of C/tonnes of additive material, if using equation 6-2;
 - (6) total annual quantity of iron ore concentrate fed to the furnace, expressed in tonnes, if using equation 6-2;
 - (7) annual weighted average carbon content of iron ore concentrate fed to the furnace, expressed in tonnes of C/tonnes of iron ore concentrate;
 - (8) total annual quantity of fired pellet production, expressed in tonnes (t);
 - (9) annual weighted average carbon content of fired pellet production, expressed in tonnes of C/tonnes of fired pellets;

- (10) annual quantity of air pollution control residue collected, expressed in tonnes (t);
 - (11) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue; and
 - (12) method used to determine the quantities under paragraph (1) above.
- (d) For a basic oxygen furnace, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of molten iron charged to the furnace, expressed in tonnes (t);
 - (3) annual weighted average carbon content of molten iron charged to the furnace, expressed in tonnes of C/tonnes of molten iron;
 - (4) total annual quantity of ferrous scrap charged to the furnace, expressed in tonnes (t);
 - (5) annual weighted average carbon content of ferrous scrap charged to the furnace, expressed in tonnes of C/tonnes of ferrous scrap;
 - (6) total annual quantity of carbonaceous material consumption, by material type, expressed in tonnes (t);
 - (7) annual weighted average carbon content of non-biomass carbonaceous material consumption, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (8) total annual quantity of non-biomass flux material charged to the furnace, by material type, expressed in tonnes (t);
 - (9) annual weighted average carbon content of non-biomass flux material charged to the furnace, expressed in tonnes of C/tonnes of flux;
 - (10) total annual quantity of molten raw steel production, expressed in tonnes (t);
 - (11) annual weighted average carbon content of molten raw steel production, expressed in tonnes of C/tonnes of molten raw steel;
 - (12) total annual quantity of slag production, expressed in tonnes (t);
 - (13) annual weighted average carbon content of slag production, expressed in tonnes of C/tonnes of slag;
 - (14) total annual quantity of furnace gas transferred off-site, expressed in tonnes of furnace gas (t) and tonnes of CO₂ (t);
 - (15) annual weighted average carbon content of furnace gas transferred off-site, expressed in tonnes of C/tonnes of furnace gas transferred;

- (16) total annual quantity of air pollution control residue collected, expressed in tonnes (t); and
 - (17) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (e) For coke oven battery, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of coking coal charged to battery, expressed in tonnes (t);
 - (3) annual weighted average carbon content of non-biomass coking coal charged to battery, expressed in tonnes of C/tonnes of coking coal;
 - (4) total annual quantity of non-biomass carbonaceous material consumption, other than coking coal charged to battery, by material type, expressed in tonnes (t);
 - (5) annual weighted average carbon content of non-biomass carbonaceous material consumption, other than coking coal charged to battery, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (6) total annual quantity of coke produced, expressed in tonnes (t);
 - (7) annual weighted average carbon content of coke produced, expressed in tonnes of C/tonnes of coke;
 - (8) total annual quantity of coke oven gas transferred off-site, expressed in tonnes of coke oven gas (t) and tonnes of CO₂;
 - (9) annual weighted average carbon content of coke oven gas transferred off-site, expressed in tonnes of C/tonnes of coke oven gas;
 - (10) total annual quantity of by-product from coke oven battery, expressed in tonnes (t);
 - (11) annual weighted average carbon content of non-biomass by-product from coke oven battery, expressed in tonnes of C/tonnes of by-product;
 - (12) total annual quantity of air pollution control residue collected, expressed in tonnes (t); and
 - (13) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (f) For sinter production, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of non-biomass carbonaceous material consumption, by material type, expressed in tonnes (t);

- (3) annual weighted average carbon content of non-biomass carbonaceous material consumption, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (4) total annual quantity of sinter feed material, expressed in tonnes (t);
 - (5) annual weighted average carbon content of sinter feed material, expressed in tonnes of C/tonnes of sinter feed;
 - (6) total annual quantity of sinter production, expressed in tonnes (t);
 - (7) annual weighted average carbon content of sinter production, expressed in tonnes of C/tonnes of sinter production;
 - (8) total annual quantity air pollution control residue collected, expressed in tonnes (t); and
 - (9) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (g) For an electric arc furnace, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of direct reduced iron charged to furnace, expressed in tonnes (t);
 - (3) annual weighted average carbon content of direct reduced iron charged to furnace, expressed in tonnes of C/tonnes of direct reduced iron;
 - (4) total annual quantity of ferrous scrap charged to furnace, expressed in tonnes (t);
 - (5) annual weighted average carbon content of ferrous scrap charged to furnace, expressed in tonnes of C/tonnes of ferrous scrap;
 - (6) total annual quantity of carbonaceous material consumption, by material type, expressed in tonnes (t);
 - (7) annual weighted average carbon content of non-biomass carbonaceous material consumption, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (8) total annual quantity of carbon electrode consumption, expressed in tonnes (t);
 - (9) annual weighted average carbon content of non-biomass carbon electrode consumption, expressed in tonnes of C/tonnes of carbon electrode;
 - (10) total annual quantity of flux material charged to the furnace, by material type, expressed in tonnes (t);

- (11) annual weighted average carbon content of non-biomass flux material charged to the furnace, expressed in tonnes of C/tonnes of flux;
 - (12) total annual quantity of molten raw steel production or ferroalloys, expressed in tonnes (t);
 - (13) annual weighted average carbon content of molten raw steel production, expressed in tonnes of C/tonnes of molten raw steel;
 - (14) total annual quantity of slag production, expressed in tonnes (t);
 - (15) annual weighted average carbon content of slag production, expressed in tonnes of C/tonnes of slag;
 - (16) total annual quantity air pollution control residue collected, expressed in tonnes (t);
 - (17) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue; and
 - (18) Annual emissions of CH₄ emissions from the production of ferroalloys in tonnes (t).
- (h) For an argon-oxygen decarburization vessel, report the following information in this section or as part of the information in subsection (d) or (g) above.
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of molten steel charged to the vessel, expressed in tonnes (t);
 - (3) annual weighted average carbon content of molten steel charged to the vessel, expressed in tonnes of C/tonnes of molten raw steel;
 - (4) annual weighted average carbon content of molten steel before decarburization, expressed in tonnes of C/tonnes of molten steel;
 - (5) annual weighted average carbon content of molten steel after decarburization, expressed in tonnes of C/tonnes of molten steel;
 - (6) total annual quantity of air pollution control residue collected, expressed in tonnes (t); and
 - (7) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (i) For a direct reduction furnace, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of iron ore or iron ore pellets consumption, expressed in tonnes (t);

- (3) annual weighted average carbon content of iron ore or iron ore pellets consumption, expressed in tonnes of C/tonnes of iron ore or iron ore pellets;
 - (4) total annual quantity of consumed raw material, other than carbonaceous material and ore, by material type, expressed in tonnes (t);
 - (5) annual weighted average carbon content of raw material, other than carbonaceous material and ore, by material type, expressed in tonnes of C/tonnes of raw material;
 - (6) total annual quantity of carbonaceous material consumption, by material type, expressed in tonnes (t);
 - (7) annual weighted average carbon content of non-biomass carbonaceous material consumption, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (8) total annual quantity of iron production, expressed in tonnes (t);
 - (9) annual weighted average carbon content of iron production, expressed in tonnes of C/tonnes of iron;
 - (10) total annual quantity of non-metallic material production, expressed in tonnes (t);
 - (11) annual weighted average carbon content of non-metallic material production, expressed in tonnes of C/tonnes of non-metallic material;
 - (12) total annual quantity of air pollution control residue collected, expressed in tonnes (t); and
 - (13) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (j) For a blast furnace, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of iron ore or iron ore pellets consumption, expressed in tonnes (t);
 - (3) annual weighted average carbon content of iron ore or iron ore pellets consumption, expressed in tonnes of C/tonnes of iron ore or iron ore pellets;
 - (4) total annual quantity of consumed raw material, other than carbonaceous material and ore, by material type, expressed in tonnes (t);

- (5) annual average carbon content of consumed raw material, other than carbonaceous material and ore, by material type, expressed in tonnes of C/tonnes of raw material;
 - (6) total annual quantity of carbonaceous material consumption, by material type, expressed in tonnes (t);
 - (7) annual weighted average carbon content of non-biomass carbonaceous material consumption, by material type, expressed in tonnes of C/tonnes of carbonaceous material;
 - (8) total annual quantity of flux material charged to the furnace, by material type, expressed in tonnes (t);
 - (9) annual weighted average carbon content of non-biomass flux material charged to the furnace, expressed in tonnes of C/tonnes of flux;
 - (10) total annual quantity of iron production, expressed in tonnes (t);
 - (11) annual weighted average carbon content of iron production, expressed in tonnes of C/tonnes of iron;
 - (12) total annual quantity of non-metallic material production, expressed in tonnes (t);
 - (13) annual weighted average carbon content of non-metallic material production, expressed in tonnes of C/tonnes of non-metallic material;
 - (14) total annual quantity of blast furnace gas transferred off-site, expressed in tonnes of blast furnace gas (t) and tonnes of CO₂;
 - (15) annual weighted average carbon content of blast furnace gas transferred off-site, expressed in tonnes of C/tonnes of blast furnace gas;
 - (16) total annual quantity of air pollution control residue collected, expressed in tonnes (t); and
 - (17) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue.
- (k) For the ladle furnace, report the following information in this section or as part of the information in subsection (d) or (g) above.
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of molten steel fed to the furnace, expressed in tonnes (t);
 - (3) annual weighted average carbon content of molten steel fed to the furnace, expressed in tonnes of C/tonnes of molten steel;
 - (4) total annual quantity of additive material consumed by the furnace, by material type, expressed in tonnes (t);

- (5) annual weighted average carbon content of additive material consumed by the furnace, by material type, expressed in tonnes of C/tonnes of additive material;
 - (6) total annual carbon electrodes consumed by the furnace, expressed in tonnes (t);
 - (7) annual weighted average carbon content of carbon electrodes consumed by the furnace, expressed in tonnes of C/tonnes of carbon electrodes;
 - (8) total annual quantity of molten steel production, expressed in tonnes (t);
 - (9) annual weighted average carbon content of molten steel production, expressed in tonnes of C/tonnes of molten steel;
 - (10) total annual quantity of slag production, expressed in tonnes (t);
 - (11) annual weighted average carbon content of slag production, or a default value of 0, expressed in tonnes of C/tonnes of slag;
 - (12) total annual quantity of air pollution control residue collected, expressed in tonnes (t);
 - (13) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue;
 - (14) total annual quantity of other residue produced, expressed in tonnes (t); and
 - (15) annual weighted average carbon content of other residue produced or a default value of 0, expressed in tonnes of C/tonnes of residue.
- (l) For the atomization of molten cast iron, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of molten cast iron fed into the process, expressed in tonnes (t);
 - (3) annual weighted average carbon content of molten cast iron fed into the process, expressed in tonnes of C/tonnes of molten cast iron;
 - (4) total annual quantity of other material used in the process, by material type, expressed in tonnes (t);
 - (5) annual weighted average carbon content of other material used in the process, by material type, expressed in tonnes of C/tonnes of other material;
 - (6) total annual quantity of atomized cast iron production, expressed in tonnes (t);

- (7) annual weighted average carbon content of atomized cast iron production, expressed in tonnes of C/tonnes of atomized cast iron;
 - (8) total annual quantity of by-products, by by-product type, expressed in tonnes (t); and
 - (9) annual weighted average carbon content of by-products, reported by by-product type, expressed in tonnes of C/tonnes of by-product.
- (m) For the decarburization of iron powder, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of iron powder fed into the process, expressed in tonnes (t);
 - (3) annual weighted average carbon content of iron powder fed into the process, expressed in tonnes of C/tonnes of iron powder;
 - (4) total annual quantity of decarburized iron powder production, expressed in tonnes (t);
 - (5) annual weighted average carbon content of decarburized iron powder production, expressed in tonnes of C/tonnes of decarburized iron powder production;
 - (6) total annual quantity of by-product, by by-product type, expressed in tonnes (t); and
 - (7) (g) annual weighted average carbon content of by-product, by by-product type, expressed in tonnes of C/tonnes of by-product.
- (n) For steel grading, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) (b) total annual quantity of molten steel fed into the process, expressed in tonnes (t);
 - (3) annual weighted average carbon content of molten steel fed into the process, expressed in tonnes of C/tonnes of molten steel;
 - (4) total annual quantity of additive used in the process, expressed in tonnes (t);
 - (5) annual weighted average carbon content of additive used in the process, by additive type, expressed in tonnes of C/tonnes of additive;
 - (6) total annual quantity of carbon electrode consumption, expressed in tonnes (t);
 - (7) annual weighted average carbon content of carbon electrode consumption, expressed in tonnes of C/tonnes of carbon electrode consumption;

- (8) total annual quantity of molten steel production, expressed in tonnes (t);
 - (9) annual weighted average carbon content of molten steel production, expressed in tonnes of C/tonnes of molten steel production;
 - (10) total annual quantity of slag production, expressed in tonnes (t);
 - (11) annual weighted average carbon content of slag production, expressed in tonnes of C/tonnes of slag production;
 - (12) total annual quantity of air pollution control residue collected, expressed in tonnes (t);
 - (13) annual weighted average carbon content of air pollution control residue collected, expressed in tonnes of C/tonnes of residue;
 - (14) total annual quantity of other residue production, expressed in tonnes (t); and
 - (15) annual weighted average carbon content of other residue production, expressed in tonnes of C/tonnes of other residue.
- (o) For steel powder annealing, report the
- (1) total annual quantity of CO₂ emissions, expressed in tonnes (t);
 - (2) total annual quantity of steel powder fed into the process, expressed in tonnes (t);
 - (3) annual weighted average carbon content of steel powder fed into the process, expressed in tonnes of C/tonnes of steel powder;
 - (4) total annual quantity of steel powder production, expressed in tonnes (t);
 - (5) annual weighted average carbon content of steel powder production, expressed in tonnes of C/tonnes of steel powder;
 - (6) total annual quantity of by-product, by by-product type, expressed in tonnes (t); and
 - (7) annual weighted average carbon content of by-product, by by-product type, expressed in tonnes of C/tonnes of by-product.
- (p) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS shall use the GGQM in section 6.A of the GGQR for iron and steel production to report:
- (1) CO₂ emissions information under subsections (c) through (n) of this section separately from CO₂ emissions information specified for the CEMS in ON.23; and
 - (2) production information specified under paragraphs (c)(8), (d)(10), (d)(12), e(6), (f)(6), (g)(12), (g)(14), (h)(2), (i)(8), (i)(10), (j)(10), (j)(12), (k)(8), (k)(10), (l)(6), (m)(4), (n)(8), (n)(10) and (o)(4).

- (3) N₂O, and CH₄ process emissions from waste water emissions in tonnes using method ON.203(g).

ON.153 Calculation of CO₂ Emissions

- (a) Determine process CO₂ emissions as specified in one of the following:
- (1) CEMS using the GGQM in section 6.A.10 of the GGQR.
 - (2) Calculation methodologies specified in subsection (b) of this section.
- (b) Calculate CO₂ process emissions for each process specified in paragraphs (b)(1) through (b)(14). Specific process inputs or outputs that contribute less than 1 per cent of the total mass of carbon into or out of the process do not have to be included in the mass balances in paragraphs (b)(1) through (b)(14).
- (1) Taconite indurating furnace CO₂ emissions using the GGQM in section 6.A.1 of the GGQR.
 - (2) Basic oxygen process furnace CO₂ emissions using the GGQM in section 6.A.2 of the GGQR.
 - (3) Coke oven battery CO₂ emissions using the GGQM in section 6.A.3 of the GGQR.
 - (4) Sinter process CO₂ emissions using the GGQM in section 6.A.4 of the GGQR.
 - (5) Electric arc furnace (EAF) CO₂ emissions using the GGQM in section 6.A.5 of the GGQR.
 - (6) Electric arc furnace CH₄ emissions from the production of any ferroalloy using equation 150-1:

$$E_{CH_4-FeAlloy} = \sum_{j=1}^m \sum_{i=1}^n M_{i,j} \times EF_{i,j}$$

Equation 150-1

Where:

- $E_{CH_4-FeAlloy}$ = Annual process CH₄ emissions from EAF (tonnes).
 M_i = Annual mass of alloy product “i” produced in the EAF (tonnes).
 EF_i = CH₄ emission factor for alloy product “i” from Table 150-1 (tonne CH₄/ tonne of alloy product “i”).
i = ferroalloy product
n = number of ferroalloy products produced at the facility
j = EAF number
m = number of EAFs at the facility

Table 150-1- Electric Arc Furnace (EAF) CH₄ Emission Factors

Alloy product produced in EAF	CH ₄ emission factor (tonne CH ₄ per metric ton product) EAF Operation		
	Batch-charging	Sprinkle-charging ^a	Sprinkle-charging and >750 °C ^b
Silicon metal	0.0015	0.0012	0.0007
Ferrosilicon 90 per cent	0.0014	0.0011	0.0006
Ferrosilicon 75 per cent	0.0013	0.0010	0.0005
Ferrosilicon 65 per cent	0.0010		

^a Sprinkle-charging is charging intermittently every minute.

^b Temperature measured in off-gas channel downstream of the furnace hood

- (7) Argon-oxygen decarburization vessel CO₂ emissions using the GGQM in section 6.A.6 of the GGQR.
- (8) Direct reduction furnace CO₂ emissions using the GGQM in section 6.A.7 of the GGQR.
- (9) Blast furnace CO₂ emissions using the GGQM in section 6.A.8 of the GGQR.
- (10) Ladle furnace CO₂ emissions using the GGQM in section 6.A.9 of the GGQR.
- (11) Molten cast iron CO₂ emissions using the GGQM in section 6.B.1 of the GGQR.
- (12) Decarburization of iron powder CO₂ emissions using the GGQM in section 6.B.2 of the GGQR.
- (13) Steel grading CO₂ emissions using the GGQM in section 6.B.3 of the GGQR.
- (14) Steel powder annealing CO₂ emissions using the GGQM in section 6.B.4 of the GGQR.

ON.154 Sampling, Analysis, and Measurement Requirements

The annual mass of each material used in ON.153 shall be determined using plant instruments used for accounting purposes, including either direct measurement of the quantity of material used in the process or by calculations using process operating information.

- (a) The average carbon content of each material used shall be determined in accordance with:

- (1) section 6.C.1 and 6.C.2 of the GGQR.
 - (2) Any of the other analytical methods listed in the Technical Reference Document section of this Guideline (section 4).or
 - (3) The most appropriate method published by a consensus-based standards organization. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (b) The annual mass of each material used in the ON.153 mass balance methodologies shall be determined using plant instruments used for accounting purposes, including either direct measurement of the quantity of material used in the process or by calculations using process operating information.
- (c) The person shall measure the quantity of production and material usage used in the calculation as follows.
- (1) Equipment used to measure the production quantity and material usage under ON.152(b) shall be:
 - (i) calibrated according to the manufacturer's instructions where available; or, where not available calibrated according to practices used for accounting purposes;
 - (ii) maintained to achieve an accuracy of plus or minus 5 per cent.
 - (2) The person may use engineering estimates or mass balance along with measurements to determine:
 - (i) coking coal, and nonfuel carbonaceous material charged to battery; and
 - (ii) coke production in coke oven batteries.
 - (3) The person may use measurements of semi-finished steel shape dimensions, counts and densities to determine the quantity and mass of the semi-finished steel shapes.

ON.155 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 6.D of the GGQR.

ON.170 Lime Production

ON.171 Activity Definition

For the purposes of this standard quantification method (SQM):

“Lime production” has the same meaning as in the Regulation.

“Person” means a person that engages in lime production.

ON.172 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.170 – ON.175, in an emission report prepared for a calendar year in respect of lime production at a facility.
- (b) Total annual quantity of CO₂ emissions from lime production, expressed in tonnes;
- (c) Total monthly quantity of lime, by lime type, expressed in tonnes (t);
- (d) Monthly plant-specific emission factor, by lime type, expressed in tonnes of CO₂/tonnes of lime;
- (e) Monthly calcium oxide (CaO) content of lime, by lime type, expressed in tonnes of CaO/tonnes of lime;
- (f) Monthly magnesium oxide (MgO) content of lime, by lime type, expressed in tonnes of MgO/tonnes of lime;
- (g) Total quarterly quantity of calcined by-products/wastes, by by-product/waste type, expressed in tonnes (t);
- (h) Quarterly plant-specific emission factor of calcined by-products/wastes, by calcined by-product/waste type, expressed in tonnes of CO₂/tonnes of by-product/waste;
- (i) Quarterly weighted average calcium oxide (CaO) content of calcined by-products/wastes, by calcined by-product/waste type, expressed in tonnes of CaO/tonnes of by-product/waste; and
- (j) Quarterly weighted average magnesium oxide (MgO) content of calcined by-products/wastes, by calcined by-product/waste type, expressed in tonnes of MgO/ tonnes of by-product/waste.
- (k) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions and production quantities under subsections (a), (c), and (g).

ON.173 Calculation of Greenhouse Gas Emissions from Kilns

- (a) Calculate CO₂ emissions using the GGQM in section 3.A of the GGQR.

ON.174 Sampling, Analysis, and Measurement Requirements

- (a) Sampling, analysis and measurement requirements for this activity shall be done in accordance with section 3B of the Greenhouse Gas Quantification. The chemical composition (CaO and MgO contents) of each type of lime and each type of calcined byproduct/waste may also be determine using:
- (1) Any of the other analytical methods listed in the Technical Reference Document section of this Guideline (section 4).
 - (2) The most appropriate method published by a consensus-based standards organization. If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (b) Equipment used to measure the production quantity shall be:
- (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.

ON.175 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 3C of the GGQR.

ON.290 Magnesium Production

ON.291 Activity Definition

For the purpose of this standard quantification method (SQM):

“Cover gas” means a greenhouse gas used to protect the surface of molten magnesium from rapid oxidation and burning in the presence of air and includes but is not limited to SF₆ and HFC–134a.

“Carrier gas” means a gas mixed with a cover gas to transport and dilute the cover gas.

“Heels” means any material remaining in a tank following unloading, delivery, or discharge of the transported cargo.

“Magnesium production” has the same meaning as in the Regulation.

“Person” means a person who engages in magnesium production.

ON.292 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.290- ON.295, in an emission report prepared for a calendar year in respect of magnesium production.
- (b) The total annual emissions of each greenhouse gas listed in Schedule 1 of the Regulation resulting from the use of the greenhouse gas as a cover or carrier gas in magnesium production expressed in tonnes of CO_{2e} per year calculated using the methods in ON.293.
- (c) Where applicable, an explanation of any change greater than 30 per cent in the facility’s cover gas usage rate from the previous calendar year.
- (d) Where applicable, a description of any new melt protection technologies adopted to account for reduced or increased greenhouse gas emissions in the previous reporting period.
- (e) The total annual quantity of magnesium produced or processed, by process type, in tonnes.

ON.293 Calculation of GHG Emissions

- (a) A magnesium producer shall use Equation 290-1 or 290-2 to calculate the mass of GHG emissions from the consumption of cover or carrier gases expressed in tonnes,

- (1) Monitoring changes in container masses and inventories:

$$E_x = (I_{B,x} - I_{E,x} + A_x - D_x) \times 0.001$$

Equation 290-1

Where:

E_x	=	Total GHG emissions from the consumption of cover or carrier gases expressed in tonnes
$IB_{,x}$	=	Inventory of cover gas or carrier gas “x” stored in cylinders or other containers at the beginning of the reporting period, including heels expressed in kg;
$I_{E,x}$	=	Inventory of each cover gas or carrier gas “x” stored in cylinders or other containers at the end of the reporting period, including heels expressed in kg;
A_x	=	Acquisitions of cover gas or carrier gas “x” during the reporting period, including heels in cylinders or other containers returned to the magnesium production or processing facility expressed in kg;
D_x	=	Transfers of cover gas or carrier gas “x” off-site during the reporting period, including heels in cylinders or other containers returned by the magnesium production or processing facility to the gas supplier expressed in kg;
0.001	=	Conversion factor from kg to tonnes; and
X	=	Each cover gas or carrier gas that is a GHG contained in Schedule 1 of the Regulation.

(2) Monitoring changes in masses of individual containers as contents are used:

$$E_x = \sum_{p=1}^n Q_p \times 0.001$$

Equation 290-2

Where:

E_x	=	Total GHG emissions from the consumption of cover or carrier gases expressed in tonnes;
Q_p	=	Mass of the cover or carrier gas consumed calculated in accordance with Equation 290-3 expressed in kg;
n	=	Number of cylinders or other containers in period p ; and
0.001	=	Conversion factor from kg to tonnes.

(b) For the purposes of Equation 290-2, the mass of the cover or carrier gas consumed over the period p for an individual container shall be estimated by using Equation 290-3:

$$Q_p = M_B - M_E$$

Equation 290-3

Where:

Q_p	=	Mass of cover or carrier gas consumed over the period p
-------	---	---

- M_B = Mass of the cylinder or container's contents expressed in kg at the beginning of period p ; and
- M_E = Mass of the cylinder or container's contents expressed in kg at the end of period p .

- (c) Notwithstanding (b) above, if a facility has mass flow controllers (MFC) and the capacity to track and record MFC measurements to estimate total gas usage, the mass of each cover or carrier gas monitored may be used as the value for Q_p in Equation 290-2 expressed in kg.

ON.294 Sampling, Analysis, and Measurement Requirements

Determination of quantities of cover and carrier gases and mass flows:

- (a) The person required to determine quantities of cover and carrier gases for the purposes of using this method shall determine changes in cylinder or container weights and inventories as follows:
- (1) Using scales or load cells with an accuracy of 1 per cent of full scale or better, accounting for the tare weights of the cylinders or other containers or
 - (2) Using gas masses or weights provided by the gas supplier (e.g., for the contents of containers containing new gas or for the heels remaining in cylinders or other containers returned to the gas supplier) if the supplier provides documentation verifying that accuracy standards in (c) are met.
- (b) The person required to determine quantities of cover and carrier gases for the purposes of using Equations 290-2 and 290-3 shall monitor and record cylinder and other container identities and masses as follows:
- (1) Track the identities and masses of cylinders and other containers leaving and entering storage with check-out and check-in sheets and procedures.
 - (2) Measure masses of cylinders and other containers returning to storage immediately before the cylinders or other containers are put back into storage.
- (c) The person required to monitor the mass flows of the cover or carrier gas into the gas distribution system for the purposes of ON.293(c) shall use gas flow meters or mass flow controllers, with an accuracy of 1 per cent of full scale or better.

Equipment Calibration:

- (d) The person required to determine quantities of cover and carrier gases pursuant to this method shall calibrate all flow meters, scales, and load cells prior to its first use for the purposes of this method using calibration procedures specified by the equipment manufacturer.

- (e) The person required to determine quantities of cover and carrier gases pursuant to this method shall recalibrate equipment mentioned in (d) at the minimum frequency specified by the manufacturer.
- (f) The person shall measure the magnesium production quantity using equipment that is:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained an accuracy of plus or minus 5 per cent.

ON.295 Procedures for Estimating Missing Data

Determination of quantity:

- (a) Whenever sampling and measurement data required by ON.293 for the calculation of emissions are unavailable, the person shall ensure that the data are substituted using the following missing data procedures:
 - (1) Replace missing data on the emissions of cover or carrier gases by multiplying magnesium production during the missing data period by the average cover or carrier gas usage rate calculated using Equation 290-4.

$$R_x = \left(\frac{C_x}{Mg} \right) \times 0.001$$

Equation 290-4

Where:

- R_x = Usage rate of a particular cover gas or carrier gas "x" over the period of comparable operation expressed in tonnes gas/tonne Mg;
 - C_x = Consumption of a particular cover gas or carrier gas "x" over the period of comparable operation expressed in kg;
 - Mg = Magnesium produced or fed into the process over the period of comparable operation expressed in tonnes;
 - 0.001 = Conversion factor from kg to tonnes; and
 - X = Each cover gas or carrier gas that is a GHG listed in Schedule 1 of the Regulation.
- (2) Unavailable weights: Where the calculation of the before and after weight of a cylinder or other container is required, and a precise weight is not available, the magnesium producer shall assume that the cylinder or other container, except for the heel, was emptied.
 - (3) Records for missing data: The magnesium producer shall ensure that where data are missing, the following information is recorded;
 - (i) the length of time the data were missing for each cover gas or carrier gas,

- (ii) the method used to estimate emissions in the absence of the data,
and
- (iii) the quantity of emissions estimated using that method.

ON.310 Nitric Acid Production

ON.311 Activity Definition

For the purposes of this standard quantification method (SQM):

“Nitric acid production” has the same meaning as in the Regulation.

“Person” means a person that engages in nitric acid production.

ON.312 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.310 – ON.315, in an emission report prepared for a calendar year in respect of nitric acid production at a facility:
- (b) Report the
 - (1) total annual quantity of N₂O emissions, expressed in tonnes (t); and
 - (2) total annual quantity of nitric acid produced, expressed in tonnes (t).
- (c) Any person who operates a facility where there is abatement downtime shall report the
 - (1) annual weighted average N₂O generation factor, measured upstream of N₂O abatement, expressed in kilograms (kg) of N₂O/tonnes (t) of nitric acid (nitric acid as 100 per cent acid basis);
 - (2) annual weighted average abatement factor of N₂O abatement technology per acid train, expressed as a fraction of annual nitric acid production per train in which abatement technology is operating; and
 - (3) destruction efficiency of N₂O abatement technology used on nitric acid train, expressed as per cent of N₂O removed from air stream, by type of abatement technology and shall include documentation demonstrating how process knowledge was used to estimate destruction efficiency, if not specified by the manufacturer or estimated using Equation 9-3 of the GGQR.
- (d) Any person who operates a facility where the N₂O abatement is integrated within the operating process and cannot be bypassed shall report the annual weighted average N₂O emission factor, measured from the final stack gas stream downstream of N₂O abatement, expressed in kilograms (kg) of N₂O/tonnes (t) of nitric acid, 100 per cent acid base.
- (e) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions under paragraph (b)(1). This shall not include the emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

- (f) Total CO₂ emissions from the reducing agents used in the non-selective catalytic reduction units (expressed in tonnes of CO₂), calculated using ON.313(b).
- (g) Total CH₄ emissions from unreacted methane in reducing agents used in the non-selective catalytic reduction unit (expressed in tonnes of CH₄), calculate using ON.313(b).

ON.313 Calculation of GHG emissions

- (a) Calculate nitric acid production emissions using the GGQM in section 9.A of the GGQR.
- (b) The person shall determine the annual emissions of CO₂ and CH₄ from reducing agents used in the non-selective catalytic reduction (NSCR) unit using Equations 310-1 and 310-2 of this section.

$$E_{ra_CO2} = Q_a \times (1 - M_s) \times C_a \times 3.664$$

Equation 310-1

$$E_{ra_CH4} = Q_a \times (M_s) \times C_{CH4}$$

Equation 310-2

Where:

- E_{ra_CO2} = Annual CO₂ emissions from other reducing agents or material used (tonnes);
- E_{ra_CH4} = Annual CH₄ emissions from unreacted methane in the reducing agent (tonnes)
- Q_a = Annual quantity of reducing agents or material used in the NSCR unit expressed in tonnes if it is a solid, Rm³ at reference temperature and pressure conditions as used by the facility if it is a gas, or kilolitres if it is a liquid;
- M_s = Fraction of reducing agents or materials that did not react in the NSCR unit based on engineering estimates or design;
- C_a = Carbon content of reducing agents or material used expressed in tonnes of carbon per tonne of solid, tonnes of carbon per Rm³ of gas, or tonnes of carbon per kilolitre of liquid;
- C_{CH4} = methane content of the reducing agent or material used expressed in tonnes methane per tonne of solid, tonnes of methane per Rm³ of gas, or tonnes methane per kilolitre of liquid;
- 3.664 = ratio of molecular weights, carbon dioxide to carbon.

ON.314 Sampling, Analysis, and Measurement Requirements

- (a) The person shall conduct a new performance test and calculate a new site-specific emissions factor as specified in the following paragraphs.
 - (1) Conduct the performance test at least once per year.
 - (2) Conduct the performance test when the nitric acid production process is changed, specifically when abatement equipment is installed.
- (b) The NO_x CEMS shall use the procedures in section 9.B(2) of the GGQR.
- (c) The person shall measure the N₂O concentration during the performance test using one of the following methods.
 - (1) EPA Method 320 at 40 CFR part 63, appendix A, Measurement of Vapor Phase Organic and Inorganic Emissions by Extractive Fourier Transform Infrared (FTIR) Spectroscopy.
 - (2) ASTM D6348.
 - (3) A method based on the use of a non-dispersive infrared (NDIR) analyzer within a stack monitoring system where the method is equivalent to EPA method 320, or any equivalent method published by Environment Canada or other Provinces.
 - (4) The most appropriate method published by a consensus-based standards organization, if such a method exists.
 - (5) If no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (d) The person shall determine the production rate(s) (100 per cent basis) from each nitric acid train during the performance test according to one of the following methods.
 - (1) Direct measurement of production and concentration (such as using flow meters, weigh scales, for production and concentration measurements).
 - (2) Existing plant procedures used for accounting purposes (i.e. dedicated tank-level and acid concentration measurements).
- (e) The person shall conduct all performance tests in conjunction with the applicable methods. For each test, the facility shall prepare an emission factor determination report that shall include the following items.
 - (1) Analysis of samples, determination of emissions, and raw data.
 - (2) All information and data used to derive the emissions factor(s).
 - (3) The production rate during each test and how it was determined.

- (f) The person shall determine the monthly nitric acid production quantity and the monthly nitric acid production quantity during which N₂O abatement technology is operating from each nitric acid train according to the methods in paragraph (c)(1) or (c)(2) of this section. Equipment used to measure the production quantity shall be:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.
- (g) The person shall determine the annual nitric acid production quantity and the annual nitric acid production quantity during which N₂O abatement technology is operating for each train by summing the respective monthly nitric acid production quantities. Equipment used to measure the production quantity shall be:
 - (1) calibrated according to the manufacturer's instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.

ON.315 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 9.C of the GGQR.

ON.230 Operation of Equipment for a Transmission System or a Distribution System (Electricity)

ON.231 Activity Definition

For the purposes of this standard quantification method (SQM):

“Automated mass-flow measurement” means the use of mass-flow meters attached to electrical power distribution equipment to directly measure the amount of SF₆ added to equipment.

“Electricity transmission and distribution” has the same meaning as “operation of equipment for a transmission system or a distribution system (electricity)” in Schedule 2 of the Regulation.

“Person” means a person that engages in electricity transmission or distribution.

“PFC” means perfluoroethane, perfluoropropane, perfluorobutane, perfluorocyclobutane, perfluoropentane, perfluorohexane.

“Storage containers” includes cylinders, gas carts, and other storage containers, but does not include electrical power distribution equipment.

“Total nameplate capacity” means the full and proper charge of electrical power distribution equipment.

“Weigh-scale measurement” means measuring the SF₆ or PFC in a storage container before and after its contents are added to electrical power distribution equipment with the difference being equal to the SF₆ or PFC added to the equipment.

ON.232 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.230 – ON.235, in an emission report prepared for a calendar year in respect of electricity transmission and distribution at a facility:
- (b) The SF₆ and PFC emissions from electricity transmission and distribution and distribution calculated in accordance with ON.233(a) and (b).

ON.233 Calculation of SF₆ and PFC Emissions

- (a) The person shall use one of the following calculation methodologies to calculate SF₆ emissions
 - (1) Mass Balance Methodology.
 - (i) Calculate the change in inventory of SF₆ in storage using Equation 230-1.

$$\Delta S_{Inv} = S_{Inv-Begin} - S_{Inv-End}$$

Equation 230-1

Where:

- ΔS_{Inv} = Change in inventory of SF₆ in storage expressed in kilograms
- $S_{Inv-Begin}$ = Quantity of SF₆ in storage at the beginning of the reporting period expressed in kilograms;
- $S_{Inv-End}$ = Quantity of SF₆ in storage at the end of the reporting period expressed in kilograms

- (ii) Calculate the amount of all SF₆ acquired during the year that is contained either in storage containers or in electrical power distribution equipment using Equation 230-2.

$$S_{PA} = S_{Cyl} + S_{Equip} + S_{Recyc-ret}$$

Equation 230-2

Where:

- S_{PA} = Sum of all SF₆ acquired during the year that is contained either in storage containers or in electrical power distribution equipment expressed in kilograms;
- S_{Cyl} = Quantity of SF₆ in storage containers obtained from producers or distributors expressed in kilograms;
- S_{Equip} = Quantity of SF₆ stored or contained inside equipment provided by electrical power distribution equipment manufacturers expressed in kilograms;
- $S_{Recyc-ret}$ = Quantity of SF₆ returned to site after off-site recycling expressed in kilograms.

- (iii) Calculate the sum of all SF₆ transferred out of the facility during the year either in storage containers or in electrical power distribution equipment using Equation 230-3.

$$S_{SD} = S_{Sales} + S_{Returns} + S_{Destruct} + S_{Recyc-off}$$

Equation 230-3

Where:

- S_{SD} = Sum of all SF₆ transferred out of the facility during the year either in storage containers or in electrical power distribution equipment expressed in kilograms;
- S_{Sales} = Quantity of SF₆ sold or transferred to other facilities including SF₆ that is left in electrical power distribution equipment that is sold expressed in kilograms;
- $S_{Returns}$ = Quantity of SF₆ returned to suppliers expressed in kilograms;

- $S_{Destruct}$ = Quantity of SF₆ sent to destruction facilities expressed in kilograms;
- $S_{Recyc-off}$ = Quantity of SF₆ sent off-site for recycling expressed in kilograms.

- (iv) Calculate the net increase in total nameplate capacity of electrical power distribution equipment that uses SF₆ using Equation 230-4.

$$\Delta S_{Cap} = S_{Cap-new} - S_{Cap-retire}$$

Equation 230-4

Where:

- ΔS_{Cap} = Net increase in total nameplate capacity of electrical power distribution equipment that uses SF₆ expressed in kilograms
- $S_{Cap-new}$ = Total nameplate capacity of new electrical power distribution equipment at proper full charge expressed in kilograms;
- $S_{Cap-retire}$ = Total nameplate capacity of electrical power distribution equipment that has been retired, sold or transferred at proper full charge expressed in kilograms.

- (v) Calculate total emissions for the reporting period using Equation 230-5.

$$S = (\Delta S_{Inv} + S_{PA} - S_{SD} - \Delta S_{Cap}) / 1,000$$

Equation 230-5

Where:

- S = Total annual SF₆ emissions expressed in tonnes;
- ΔS_{Inv} = Change in inventory of SF₆ in storage expressed in kilograms calculated in accordance with Equation 230-1;
- S_{PA} = Sum of all SF₆ acquired that is contained either in storage containers or in electrical power distribution equipment expressed in kilograms, calculated in accordance with Equation 230-2;
- S_{SD} = Sum of all SF₆ transferred out of the facility during the year that is contained either in storage containers or in electrical power distribution equipment expressed in kilograms calculated in accordance with Equation 230-3;
- ΔS_{Cap} = Net increase in total nameplate capacity of electrical power distribution equipment using SF₆ expressed in kilograms calculated in accordance with Equation 230-4
- 1,000 = Factor to convert kilograms to tonnes.

(2) Direct Measurement Methodology.

- (i) SF₆ emissions from the operations phase shall be calculated by directly measuring the mass of SF₆ added to electrical power distribution equipment during the operation phase using automated mass-flow measurement or weigh-scale measurement in accordance with Equation 230-6.

$$S_O = \sum_i^N s_i$$

Equation 230-6

Where:

- S_O = Annual SF₆ emissions during the operation phase expressed in kilograms;
 N = Number of SF₆ additions in a given year;
 S_i = SF₆ added to electrical power distribution equipment during addition *i*, expressed in kilograms

- (ii) SF₆ emissions from the decommissioning phase shall be calculated by directly measuring the amount of SF₆ collected from any decommissioned electrical power distribution equipment calculated in accordance with Equation 230-7.

$$S_D = \sum_i^N (NC_i - S_i)$$

Equation 230-7

Where:

- S_D = Annual SF₆ emissions during decommissioning phase expressed in kilograms;
 N = Number of units of electrical power distribution equipment decommissioned in a given year;
 NC_i = Nameplate capacity of decommissioned electrical power distribution equipment *i*, expressed in kilograms;
 S_i = SF₆ collected from decommissioned electrical power distribution equipment *i*, expressed in kilograms.

- (iii) Total annual SF₆ emissions are calculated according to Equation 230-8.

$$S = \frac{S_O + S_D}{1,000}$$

Equation 230-8

Where:

- S = Annual SF₆ emissions expressed in tonnes;
- S_O = Annual SF₆ emissions during operation phase expressed in kilograms;
- S_D = Annual SF₆ emissions during decommissioning phase expressed in kilograms.

- (b) The person shall use the methods in (a) to calculate the emissions from PFCs, substituting PFCs for SF₆ and making all other necessary substitutions in Equations 230-1 through 230-8.

ON.234 Sampling, Analysis, and Measurement Requirements

- (a) When using the calculation methodology in ON.233(a)(1), the person shall determine changes in cylinder or container weights and inventories as follows:
 - (1) Using scales or load cells with an accuracy of 1 per cent of full scale or better, accounting for the tare weights of the cylinders or other containers; or
 - (2) Using gas masses or weights provided by the gas supplier (e.g., for the contents of containers containing new gas or for the heels remaining in cylinders or other containers returned to the gas supplier) if the supplier provides documentation verifying that accuracy standards in (c) are met.
- (b) When using the calculation methodology in ON.233(a)(1), the person shall monitor and record cylinder and other container identities and masses as follows:
 - (1) Track the identities and masses of cylinders and other containers leaving and entering storage with check-out and check-in sheets and procedures.
 - (2) Measure masses of cylinders and other containers returning to storage immediately before the cylinders or other containers are put back into storage.
- (c) When using the calculation methodologies in ON.233(a)(2) or the corresponding method required by ON.233 (b), the person shall measure additions of SF₆ or PFCs during the operation phase using a measuring instrument such as a flowmeter or weigh scale.

- (d) When using the calculation methodologies in ON.233(a)(2) or the corresponding method required by ON.233 (b), the person shall calibrate equipment used to measure the mass of SF₆ or PFCs as follows.
- (1) For automated mass-flow measurement, equipment shall be calibrated according to the calibration procedure specified by manufacturer.
 - (2) For weigh-scale measurement, equipment shall be calibrated annually by weighing objects of pre-determined mass and zeroing the weigh scale accordingly.

ON.235 Procedures for Estimating Missing Data

Unavailable analytical data:

- (a) Whenever analytical data relating to sampling are unavailable, the person shall, using the methods prescribed in ON.234, re-analyze the original sample, a backup sample or a replacement sample for the same measurement and sampling period.

Determination of quantity:

- (b) Whenever sampling and measurement data required by ON.234 for the calculation of emissions are unavailable the person shall ensure that the data are substituted using the following missing data procedures:
- (1) Determine the sampling or measurement rate that was used using Equation 230-9:

$$R = \frac{Q_{SAct}}{Q_{SRequired}}$$

Equation 230-9

Where:

- | | | |
|------------------------|---|---|
| R | = | Sampling or measurement rate that was used, expressed as a percentage |
| Q _{SAct} | = | Quantity of actual samples or measurements obtained by the person |
| Q _{SRequired} | = | Quantity of samples or measurements required under ON.230 |

- (2) Substitute the missing data as follows,
 - (i) If $R \geq 0.9$: substitute the missing data by the arithmetic mean of the sampling or measurement data from immediately before and after the missing data period. If no data are available from before the missing data period, the person shall use the first available data from after the missing data period;

- (ii) If $0.75 \leq R < 0.9$: substitute the missing data with the highest data value sampled or analyzed during the reporting period for which the calculation is required;
 - (iii) If $R < 0.75$: substitute the missing data with the highest data value sampled or analyzed during the 3 preceding years;
- (3) When the missing data concern gas quantity, the person shall generate the replacement data from best estimates based on all of the data relating to the processes.
- (4) When the missing data relate to electrical power distribution equipment capacity, the person shall estimate the replacement data on the basis of an equivalent nominal SF₆ and PFC gas capacity, and on repair, replacement and maintenance data for similar pieces of equipment.

ON.350 Operation of a Natural Gas Pipeline System

ON.351 Activity Definition

For the purposes of this standard quantification method (SQM):

“Blowdown vent stack emissions” mean natural gas and/or CO₂ released due to maintenance and/or blowdown operations including compressor blowdown and emergency shut-down (ESD) system testing.

“Calibrated bag” means a flexible, non-elastic, anti-static bag of a calibrated volume that can be affixed to an emitting source such that the emissions inflate the bag to its calibrated volume.

“Centrifugal compressor” means any equipment that increases the pressure of a process natural gas or CO₂ by centrifugal action, employing rotating movement of the driven shaft.

“Centrifugal compressor dry seals” mean a series of rings around the compressor shaft where it exits the compressor case that operates mechanically under the opposing forces to prevent natural gas or CO₂ from escaping to the atmosphere.

“Centrifugal compressor dry seals emissions” mean natural gas or CO₂ released from a dry seal vent pipe and/or the seal face around the rotating shaft where it exits one or both ends of the compressor case.

“Centrifugal compressor wet seal degassing venting emissions” mean emissions that occur when the high-pressure oil barriers for centrifugal compressors are depressurized to release absorbed natural gas or CO₂. High-pressure oil is used as a barrier against escaping gas in centrifugal compressor shafts. Very little gas escapes through the oil barrier, but under high pressure, considerably more gas is absorbed by the oil. The seal oil is purged of the absorbed gas (using heaters, flash tanks, and degassing techniques) and recirculated. The separated gas is commonly vented to the atmosphere.

“Component” means each metal to metal joint or seal of non-welded connection separated by a compression gasket, screwed thread (with or without thread sealing compound), metal to metal compression, or fluid barrier through which natural gas or liquid can escape to the atmosphere.

“Compressor” means any machine for raising the pressure of natural gas by drawing in low pressure natural gas and discharging significantly higher pressure natural gas.

“Continuous bleed” means a continuous flow of pneumatic supply gas to the process measurement device (e.g. level control, temperature control, pressure control) where the supply gas pressure is modulated by the process condition, and then flows to the valve controller where the signal is compared with the process set-point to adjust gas pressure in the valve actuator.

“Damage events” means damages to gas pipelines and surface facilities resulting from natural causes or incidents. Natural causes include corrosion, abrasion, rock damage, frost heaving or settling. Incidents causing pipeline damages may include hits on surface facilities and dig-ins. Specific incident examples of dig-ins include grader/dozer/scrapper excavation, demolition/breakout, general agriculture, driving bars/stakes/posts/anchors, backhoe/trackerhoe excavation, ditch shaping, snow removal, landscaping/tree planting, hand excavation, bobcat/loader excavation, saw cutting, cable/pipe plowing, vertical augering/drilling, trencher excavation, blasting/vibroslit, deep tillage, horizontal augering/boring, and other such anthropogenic ground disturbances.

“De-methanizer” means the natural gas processing unit that separates methane-rich residue gas from the heavier hydrocarbons (e.g., ethane, propane, butane, pentane-plus) in feed natural gas stream.

“Equipment leak detection” means the process of identifying emissions from equipment, components, and other point sources.

“Farm taps” mean pressure regulation stations that deliver gas directly from transmission pipelines to generally rural customers.

“Field gas” means natural gas extracted from a production well prior to its entering the first stage of processing, such as dehydration.

“Flare”, for the purposes of ON.350, means a combustion device, whether at ground level or elevated, that uses an open or closed flame to combust waste gases without energy recovery.

“Flare combustion efficiency” means the fraction of natural gas, on a volume or mole basis, that is combusted at the flare burner tip.

“Fugitive emissions” means the unintended or incidental emissions of greenhouse gases from the transmission, processing, storage, use or transportation of fossil fuels, greenhouse gases, or other liquids or gases.

“Fugitive equipment leaks” means those fugitive emissions which could not reasonably pass through a stack, chimney, vent, or other functionally-equivalent opening.

“Gas conditions” mean the actual temperature, volume, and pressure of a gas sample.

“High-bleed pneumatic devices” means automated control devices powered by pressurized natural gas and used for maintaining a process condition such as liquid level, pressure, delta-pressure and temperature. Part of the gas power stream which is regulated by the process condition flows to a valve actuator controller where it vents (bleeds) to the atmosphere at a rate in excess of 0.17 standard cubic meters per hour.

“Intermittent-bleed pneumatic devices” mean automated flow control devices powered by pressurized natural gas and used for maintaining a process condition such as liquid level, pressure, delta-pressure and temperature. These are snap-acting or throttling devices that discharge the full volume of the actuator intermittently when control action is necessary, but do not bleed continuously.

“Liquefied natural gas (LNG)” means natural gas that has been liquefied by reducing its temperature to -162 degrees Celsius at atmospheric pressure.

“Liquefied natural gas (LNG) storage” means onshore LNG storage vessels located above ground, equipment for liquefying natural gas, compressors to capture and re-liquefy boil-off-gas, re-condensers, and vapourization units for re-gasification of the liquefied natural gas.

“LNG boiloff gas” means natural gas in the gaseous phase that vents from LNG storage tanks due to ambient heat leakage through the tank insulation and heat energy dissipated in the LNG by internal pumps.

“LNG import equipment” means all onshore or offshore equipment that receives imported LNG via ocean transport, stores LNG, re-gasifies LNG, and delivers re-gasified natural gas to a natural gas transmission or distribution system.

“LNG export equipment” means all onshore or offshore equipment that receives natural gas, liquefies natural gas, stores LNG, and transfers the LNG via ocean transportation to any location, including locations in Canada.

“Low-bleed pneumatic devices” mean automated control devices powered by pressurized natural gas and used for maintaining a process condition such as liquid level, pressure, delta-pressure and temperature. Part of the gas power stream which is regulated by the process condition flows to a valve actuator controller where it vents (bleeds) to the atmosphere at a rate equal to or less than 0.17 standard cubic meters per hour.

“Meter-regulating station” means a station that meters the flow rate, regulates the pressure, or both, of natural gas in a natural gas distribution system (including gate stations). This does not include customer meters, customer regulators, or farm taps.

“Natural gas distribution” has the same meaning as the regulation.

“Natural gas pneumatic pump” means a pump that uses pressurized natural gas to move a piston or diaphragm, which pumps liquids on the opposite side of the piston or diaphragm.

“Natural gas transmission pipelines” means a high pressure pipeline (and associated equipment) transporting sellable quality natural gas from production or natural gas processing to natural gas distribution systems before delivery to customers. In some cases natural gas is delivered directly from natural gas transmission pipelines to farms and industrial end users along the pipeline route.

“Onshore natural gas transmission compression” means any stationary combination of compressors that move natural gas at elevated pressure from production fields or natural gas processing facilities in transmission pipelines to natural gas distribution pipelines, into storage or at times directly to industrial customers or farms located along the pipeline route. In addition, transmission compressor stations may include equipment for liquids separation, natural gas dehydration, and tanks for the storage of water and hydrocarbon liquids. Residue (sales) gas compression operated by natural gas processing facilities are included in the onshore natural gas processing segment and are excluded from this segment.

“Operation of a natural gas pipeline system” has the same meaning as in the Regulation.

“Operating pressure” means the containment pressure that characterizes the normal state of gas or liquid inside a particular process, pipeline, vessel or tank.

“Person” means a person that engages in the operation of a natural gas pipeline system.

“Pump means” a device used to raise pressure, drive, or increase flow of liquid streams in closed or open conduits.

“Pump seals” means any seal on a pump drive shaft used to keep methane and/or carbon dioxide containing light liquids from escaping the inside of a pump case to the atmosphere.

“Pump seal emissions” means hydrocarbon gas released from the seal face between the pump internal chamber and the atmosphere.

“Reciprocating compressor” means a piece of equipment that increases the pressure of a gas stream by positive displacement, employing linear movement of a shaft driving a piston in a cylinder.

“Reciprocating compressor rod packing” means a series of flexible rings in machined metal cups that fit around the reciprocating compressor piston rod to create a seal limiting the amount of the compressed gas stream that escapes to the atmosphere.

“Re-condenser” means heat exchangers that cool compressed boil-off gas to a temperature that will condense natural gas to a liquid.

“Reservoir” means a porous and permeable underground natural formation containing significant quantities of hydrocarbon liquids and/or gases.

“Underground natural gas storage” means subsurface storage, including depleted gas or oil reservoirs and salt dome caverns that store natural gas that has been transferred from its original location for the primary purpose of load balancing (the process of equalizing the receipt and delivery of natural gas); natural gas underground storage processes and operations (including

compression, dehydration and flow measurement, and excluding transmission pipelines); and all the wellheads connected to the compression units located at the underground natural gas storage site that inject and recover natural gas into and from the underground reservoirs.

“Vapour recovery system” means any equipment located at the source of potential gas emissions to the atmosphere or to a flare, that is composed of piping, connections, and, if necessary, flow-inducing devices, and that is used for routing the gas back into the process as a product and/or fuel.

“Vapourization unit” means a process unit that performs controlled heat input to vapourize LNG to supply transmission and distribution pipelines or consumers with natural gas.

ON.352 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.350 – ON.356, in an emission report prepared for a calendar year in respect of Operation of equipment related to natural gas:
 - (1) CO₂ and CH₄ (and N₂O, if applicable) emissions (in tonnes) from each industry segment specified in subsections (b) through (f) of this section.
- (b) For onshore natural gas transmission compression and natural gas transmission pipelines, report CO₂, CH₄ and N₂O emissions from the following sources:
 - (1) Compressor venting (from the following sources):
 - (i) Reciprocating compressors in accordance with ON.353(a)(9).
 - (ii) Centrifugal compressors in accordance with ON.353(a)(8).
 - (iii) Blowdown vent stacks in accordance with ON.353(a)(5).
 - (iv) Natural gas continuous high-bleed pneumatic devices in accordance with ON.353(a)(1).
 - (v) Natural gas pneumatic pumps in accordance with ON.353(a)(2).
 - (vi) Natural gas continuous low-bleed pneumatic device venting in accordance with ON.353(a)(3).
 - (vii) Natural gas intermittent (low and high) bleed pneumatic device (including compressor starters) venting in accordance with ON.353(a)(4).
 - (viii) Other venting emission sources in accordance with ON.353(a)(15).
 - (2) Compressor fugitive equipment leaks from valves, connectors, open ended lines, pressure relief valves and meters in accordance with ON.353(a)(10), ON.353(a)(11).

- (3) Compressor station flaring in accordance with ON.353(a)(7).
 - (4) Compressor other fugitive emission sources in accordance with ON.353(a)(15).
 - (5) Pipeline flaring in accordance with ON.353(a)(7).
 - (6) Pipeline below grade meters and regulators and valve fugitives in accordance with ON.353(a)(11).
 - (7) Pipeline other fugitive emission sources not covered in (b)(6), or (b)(10) (including, but not limited to, farm taps, pipe leaks, and customer meter sets) in accordance with ON.353(a)(15).
 - (8) Pipeline other venting emission sources in accordance with ON.353(a)(15).
 - (9) Transmission storage tanks in accordance with ON.353(a)(16).
 - (10) Damage events in accordance with ON.353(a)(6).
- (c) For underground natural gas storage, report CO₂, CH₄ and N₂O emissions from the following sources:
- (1) Venting (from the following sources):
 - (i) Reciprocating compressors in accordance with ON.353(a)(9).
 - (ii) Centrifugal compressors in accordance with ON.353(a)(8).
 - (iii) Natural gas continuous high-bleed pneumatic devices in accordance with ON.353(a)(1).
 - (iv) Natural gas pneumatic pumps in accordance with ON.353(a)(2).
 - (v) Natural gas continuous low-bleed pneumatic device venting in accordance with ON.353(a)(3).
 - (vi) Natural gas intermittent (low and high) bleed pneumatic device (including compressor starters) venting in accordance with ON.353(a)(4).
 - (vii) Other venting emission sources in accordance with ON.353(a)(15).
 - (2) Fugitive equipment leaks from valves, connectors, open ended lines, pressure relief valves and meters in accordance with ON.353(a)(10), ON.353(a)(11).
 - (3) Flares in accordance with ON.353(a)(7).
 - (4) Other fugitive emission sources. ON.353(a)(15).
- (d) For LNG storage, report CO₂, CH₄ and N₂O emissions from the following sources:
- (1) Venting (from the following sources):

- (i) Reciprocating compressors in accordance with ON.353(a)(9).
 - (ii) Centrifugal compressors in accordance with ON.353(a)(8).
 - (iii) Other venting emission sources in accordance with ON.353(a)(15).
 - (2) Fugitive equipment leaks from valves, pump seals, connectors, vapour recovery compressors, and other equipment leak sources in accordance with ON.353(a)(10), ON.353(a)(11).
 - (3) Flares in accordance with ON.353(a)(7).
 - (4) Other fugitive emission sources in accordance with ON.353(a)(15).
- (e) LNG import and export equipment, report CO₂, CH₄ and N₂O emissions from the following sources:
- (1) Venting (from the following sources):
 - (i) Reciprocating compressors in accordance with ON.353(a)(9).
 - (ii) Centrifugal compressors in accordance with ON.353(a)(8).
 - (iii) Blowdown vent stacks (including damage events) in accordance with ON.353(a)(5).
 - (iv) Other venting emission sources in accordance with ON.353(a)(15).
 - (2) Fugitive equipment leaks from valves, pump seals, connectors, vapour recovery compressors, and other equipment leak sources in accordance with ON.353(a)(10), ON.353(a)(11).
 - (3) Flares in accordance with ON.353(a)(7).
 - (4) Other fugitive emission sources in accordance with ON.353(a)(15).
- (f) For natural gas distribution, report CO₂, CH₄ and N₂O emissions from the following sources:
- (1) Equipment leaks from equipment at above grade metering- regulating stations, including fugitive equipment leaks from connectors, block valves, control valves, pressure relief valves, meters, regulators, and open- ended lines in accordance with ON.353(a)(11).
 - (2) Equipment leaks from vaults at below grade metering-regulating stations in accordance with ON.353(a)(11).
 - (3) Pipeline main fugitive equipment leaks in accordance with ON.353(a)(11).
 - (4) Service line fugitive equipment leaks in accordance with ON.353(a)(11).
 - (5) Pipeline flaring in accordance with ON.353(a)(7).
 - (6) Flares in accordance with ON.353(a)(7).

- (7) Damage events in accordance with ON.353(a)(6).
- (8) Other fugitive emission sources (including, but not limited to, farm taps, and customer meter sets) in accordance with ON.353(a)(15).
- (9) Venting (from the following sources):
 - (i) Natural gas continuous high-bleed pneumatic devices in accordance with ON.353(a)(1).
 - (ii) Natural gas pneumatic pumps in accordance with ON.353(a)(2).
 - (iii) Natural gas continuous low-bleed pneumatic device venting in accordance with ON.353(a)(3).
 - (iv) Natural gas intermittent (low and high) bleed pneumatic device (including compressor starters) venting in accordance with ON.353(a)(4).
 - (v) Other venting emission sources in accordance with ON.353(a)(15).

ON.353 Calculation of Greenhouse Gas Emissions

- (a) The person shall use the following calculation methodologies to calculate CO₂, CH₄ and N₂O emissions:
 - (1) Natural gas continuous high-bleed pneumatic device venting. The person required to report pursuant to this quantification method shall calculate emissions from a natural gas pneumatic continuous high-bleed flow control device venting using the methods specified in subparagraph (a)(1)(i) or (a)(1)(ii).
 - (i) Calculate vented emissions for metered high-bleed pneumatic devices using the following equation:

$$E_s = Q_j$$

Equation 350-1

Where:

E_s = Annual natural gas volumetric emissions for pneumatic continuous high-bleed devices where gas is metered (Sm³/y).

Q_j = Natural gas consumption for meter j (Sm³/y).

- (ii) Calculate vented emissions for any high-bleed pneumatic devices using the following equation:

$$E_s = EF_j \times t_j$$

Equation 350-2

Where:

- E_s = Annual natural gas volumetric emissions for pneumatic continuous high-bleed devices (Sm^3/y).
- EF_j = Natural gas-drive pneumatic device (or equivalent device), j , bleed rate volume in Table 350-6 or in the CEPEI Methodology Manual ($\text{Sm}^3/\text{h}/\text{device}$).
- t_j = Total time that the pneumatic device, j , has vented to the atmosphere during the reporting period (h).

(iii) The EF_j parameter may be calculated using Equation 350-2a:

$$EF_j = m \times SP_j$$

Equation 350-2a

Where:

- m = the supply pressure coefficient in Table 350-6
- SP_j = the supply pressure (kPa) of controller j
- (iv) If the device or equivalent device, is not listed in Table 350-6 or the CEPEI Methodology Manual, use the generic continuous high bleed emission factor.
- (v) Both CH_4 and CO_2 volumetric and mass emissions shall be calculated from volumetric natural gas emissions using calculations in paragraphs (a)(13) and (a)(14) of this section

(2) Natural gas pneumatic pump venting. The person required to report pursuant to this quantification method shall calculate emissions from natural gas-driven pneumatic pump venting using the method specified in subparagraph (a)(1)(i) above or use the methods specified in this section.

Natural gas-driven pneumatic pumps used in dehydrator systems do not have to report emissions under paragraph (2) of this section.

- (i) Calculate vented emissions for pneumatic pumps using Equation 350-3 or in the case of odourant injection pumps, the method specified in subparagraph (iii) below.

$$E_s = EF_j \times t_j$$

Equation 350-3

Where:

- E_s = Annual natural gas volumetric emissions for high-bleed pneumatic devices (Sm^3/y).
- EF_j = Natural gas-drive pneumatic device (or equivalent device), j bleed rate volume in Table 350-6 ($\text{Sm}^3/\text{h}/\text{device}$).
- t_j = Total time that the pump, j , has vented to atmosphere during the reporting period (h)

(ii) For pumps, except as noted in clauses A and B below use the pump (or equivalent pump) specific emission factor provided in Table 350-6.

(A) The EF_j parameter for pumps may be calculated using Equation 350-3a¹

$$EF_j = (g \times SP_j) + (n \times DP_j) = (p \times SPM_j)$$

Equation 350-3a

Where:

- EF_j = bleed rate, the volume of natural gas bled per hour for pneumatic pump (or equivalent pump), j ($\text{Sm}^3\text{NG}/\text{h}$).
- g = The supply pressure coefficient provided in Table 350-6
- SP_j = The fuel supply pressure for the pump (or equivalent pump) j (kPa)
 n = The discharge pressure coefficient provided in Table 350-6
- DP_j = The discharge pressure of pump (or equivalent pump) j (kPa)
- SPM_j = the pump strokes per minute of pump “ j ” or equivalent pump.
- P = The strokes per minute coefficient provided in Table 350-6

(B) The EF_j parameter maybe be calculated using Equation 350-3b

$$EF_j = Q_j \times R_j$$

Equation 350-3b

Where:

- Q_j = The volume rate of chemical injection for pump j (l/h)
- R_j = The pump specific factor expressed as the volume of gas vented per litre of chemical injected. The factor takes into account fuel supply pressure, piston size, and discharge

¹ If the pump is operating at less than five strokes per minute, this equation is not applicable and the mean bleed rate or volume of chemical equation should be used instead.

pressure based on chart published by the pump j
manufacturer ($\text{Sm}^3\text{NG/L}$)

- (iii) If the pump, or equivalent pump is not listed in Table 350-6 use the generic piston or diaphragm pump type emission factor, as appropriate
 - (A) Calculate vented emissions from pneumatic pumps used for odourant injection using engineering estimates or emission factors as provided in the CEPEI Methodology Manual.
- (iv) Both CH_4 and CO_2 volumetric and mass emissions shall be calculated from volumetric natural gas emissions using calculations in paragraphs (a)(13) and (a)(14) of this section.
- (3) Natural gas continuous low-bleed pneumatic device venting. The person required to report pursuant to this quantification method shall calculate emissions from natural gas continuous low-bleed pneumatic device venting as follows:
 - (i) Calculate emissions from natural gas continuous low-bleed pneumatic device venting using Equation 350-4.

$$E_s = EF_j \times t_j$$

Equation 350-4

Where:

- E_s = Annual natural gas volumetric emissions for continuous low-bleed bleed pneumatic devices (Sm^3/y).
- EF_j = Population emission factor for natural gas-driven continuous low-bleed pneumatic device, j , as provided in Tables 350-6 or in the CEPEI Methodology Manual ($\text{Sm}^3/\text{h}/\text{device}$).
- t_j = Total time that the pneumatic device, j , has vented to atmosphere during the reporting period (h).

- (ii) Both CH_4 and CO_2 volumetric and mass emissions shall be calculated from volumetric natural gas emissions using calculations in paragraphs (a)(13) and (a)(14) of this section.
- (4) Natural gas intermittent (low and high) bleed pneumatic device venting. The person required to report pursuant to this quantification method shall calculate emissions from natural gas intermittent (low and high) bleed pneumatic device venting as follows:
 - (i) Calculate vented emissions for intermittent (low and high) bleed pneumatic devices used to maintain a process condition such as liquid level, pressure, delta pressure or temperature using Equation 350-5:

$$E_s = EF_j \times t_j$$

Equation 350-5

Where:

- E_s = Annual natural gas volumetric emissions for intermittent (low and high) bleed pneumatic devices (Sm^3/y).
- EF_j = Natural gas-drive pneumatic device (or equivalent device), j bleed rate volume in Table 350-6 or in the CEPEI Methodology Manual) ($\text{Sm}^3/\text{h}/\text{device}$).
- t_j = Total time that the pneumatic device, j , vented to atmosphere during the reporting period (h).

- (A) For individual intermittent pneumatic devices, except as noted below, use the device (or equivalent device) – specific emission factor provided in Table 350-6, or the EF_j parameter may be calculated using Equation 350-5a.

$$EF_j = m \times SP_j$$

Equation 350-5a

Where:

- m = The supply pressure coefficient in Table 350-6
- SP_j = The supply pressure (kPa) of the pneumatic device.

- (B) If the device (or equivalent device) is not present in Table 350-6 use the generic intermittent (high or low as appropriate) bleed factor in Table 350-6 or in the CEPEI Methodology Manual.
- (ii) The person required to report pursuant to this quantification method shall calculate vented emissions for intermittent (high) bleed pneumatic devices, used to drive compressor engine starters, using Equation 350-6:

$$E_s = EF_j \times t_j$$

Equation 350-6

Where:

- E_s = Annual natural gas volumetric emissions for intermittent (high) bleed pneumatic devices (Sm^3/y).
- EF_j = Emission factor for natural gas-driven pneumatic compressor engine starter, j , as provided by the manufacturer for the operating condition ($\text{Sm}^3/\text{min}/\text{device}$). If an emission factor is not available from the manufacturer, an emission factor for a similar compressor engine starter may be used in its place.
- t_j = Total time that the pneumatic device, j , vented to atmosphere during the reporting period (min).

Note: The volume of gas per start provided by the manufacturer or for a similar compressor engine started may be used in place of the EF_j and t_j variables.

- (iii) Both CH_4 and CO_2 volumetric and mass emissions shall be calculated from volumetric natural gas emissions using calculations in paragraphs (a)(13) and (a)(14) of this section.
- (5) **Blowdown vent stacks.** The person required to report pursuant to this quantification method shall calculate blowdown vent stack emissions from depressurizing equipment to reduce system pressure for planned or emergency shutdowns or to take equipment out of service for maintenance (excluding depressurizing to a flare, over-pressure relief, operating pressure control venting and blowdown of non GHG gases) as follows:
 - (i) Calculate the total physical volume (including, but not limited to, pipes, compressor case or cylinders, manifolds, suction and discharge bottles and vessels) between isolation valves determined by engineering estimates based on best available data.
 - (ii) If the total physical volume between isolation valves is greater than or equal to 1.42 m^3 , retain logs of the number of blowdowns for each equipment system (including, but not limited to pipes, compressors and vessels). Physical volumes smaller than 1.42 m^3 are exempt from reporting under subparagraph (iii) below.
 - (iii) Calculate the venting emissions for each equipment system j using Equation 350-7 of this section:

$$E = V_j \left[\frac{(273.15 + T_s)(P_{a,1} - P_{a,2})}{(273.15 + T_a) P_s Z_a} \right]$$

Equation 350-7

Where:

- E_s = Natural gas venting volumetric emissions from blowdown of equipment system (Sm^3).
- V_j = Total physical volume of blowdown equipment chambers (including, but not limited to, pipes, compressors and vessels) between isolation valves for the equipment system (m^3).
- T_s = Temperature at standard conditions ($^{\circ}\text{C}$).
- T_a = Temperature at actual conditions in the equipment system ($^{\circ}\text{C}$).
- P_s = Absolute pressure at standard conditions (kPa).

- $P_{a,1}$ = Absolute pressure at actual conditions in the equipment system (kPa) prior to depressurization.
- $P_{a,2}$ = Absolute pressure at actual conditions in the equipment system after depressurization; 0 if equipment is purged using non-GHG gases (kPa).
- Z_a = Compressibility factor at actual conditions for natural gas. Use a default compressibility factor of 1, or a site-specific compressibility factor based on actual temperature and pressure conditions.

- (iv) Calculate both CH₄ and CO₂ volumetric and mass emissions from volumetric natural gas emissions using calculations in paragraphs (a)(13) and (a)(14) of this section.
- (v) Blowdowns that are directed to flares use the Flare stacks calculation method under paragraph (a)(7) rather than the Blowdown vent stacks calculation method under this section.
- (6) Damage Events. The person required to report pursuant to this quantification method shall calculate fugitive emissions from damage events as follows:
- (i) For Transmission (ON.350) systems only. Use company gas release data used for regulatory purposes.
- (ii) For Distribution systems only: Use emission factors and quantification methods in the CEPEI Methodology Manual.
- (7) Flare stacks. The person required to report pursuant to this quantification method shall calculate CO₂, CH₄, and N₂O emissions from a flare stack as follows:
- (i) If there is a continuous flow measurement device on the flare, measured flow volumes can be used to calculate the flare gas emissions. If all of the flare gas is not measured by the existing flow measurement device, then the flow not measured can be estimated using engineering calculations based on best available data or company records. If there is no continuous flow measurement device on the flare, use engineering calculations based on process knowledge, company records, and best available data.
- (ii) If there is a continuous gas composition analyzer on the gas stream to the flare, these compositions shall be used in calculating emissions. If there is no continuous gas composition analyzer on the gas stream to the flare, use the gas compositions for each stream of hydrocarbons going to the flare. If there is no gas composition for the stream of hydrocarbon going to the flare, use the gas composition of the processed natural gas.

- (iii) Determine flare combustion efficiency from manufacturer. If not available, assume that flare combustion efficiency is 98 per cent.
- (iv) Calculate GHG volumetric emissions at actual conditions using Equations 350-12, 350-13, 350-14, and 350-15 of this section.

$$E_{s,CH_4}(noncombusted) = Q_s \times (1 - \eta) \times Y_{CH_4}$$

Equation 350-12

$$E_{s,CO_2}(noncombusted) = Q_s \times Y_{CO_2}$$

Equation 350-13

$$E_{s,CO_2}(combusted) = \sum_i \eta \times Q_s \times Y_i \times n_i$$

Equation 350-14

$$E_{s,CO_2}(total) = E_{s,CO_2}(combusted) + E_{s,CO_2}(noncombusted)$$

Equation 350-15

Where:

- $E_{s,CH_4}(noncombusted)$ = Contribution of annual noncombusted volumetric CH₄ emissions from flare stack (Sm³).
- $E_{s,CO_2}(noncombusted)$ = Contribution of annual volumetric CO₂ emissions from CO₂ in the inlet gas passing through the flare noncombusted (Sm³).
- $E_{s,CO_2}(combusted)$ = Contribution of annual volumetric CO₂ emissions from combustion from flare stack (Sm³).
- Q_s = Volume of natural gas sent to flare during the year (Sm³).
- η = Fraction of natural gas combusted by flare (default combustion efficiency is 0.98). For gas sent to an unlit flare, η is zero.
- Y_{CH_4} = Mole fraction of CH₄ in gas to the flare.
- Y_{CO_2} = Mole fraction of CO₂ in gas to the flare.
- Y_i = Mole fraction of hydrocarbon constituents i (i.e., methane, ethane, propane, butane, pentanes, hexane, and pentane plus) in natural gas to the flare.
- n_i = Number of carbon atoms in the hydrocarbon constituent i ; (e.g., 1 for methane, 2 for ethane, 3 for propane, 4 for butane, 5 for pentanes, 6 for hexanes and 7 for pentanes plus) in natural gas to the flare.

- (v) Calculate both CH₄ and CO₂ mass emissions from volumetric CH₄ and CO₂ emissions as determined in subparagraph (7)(iv) of this section using the calculation in paragraph (a)(14) of this section.
- (vi) Calculate N₂O emissions using Equation 350-16.

$$E_{N_2O} = Q_s \times HHV \times EF \times 0.001$$

Equation 350-16

Where:

- E_{N_2O} = Annual N₂O mass emissions from flaring (tonnes/y).
 Q_s = Volume of gas combusted by the flare in the reporting period (Sm³/y).
HHV = High heat value of the flared gas from subparagraph (7)(ii)
EF = N₂O emission factor. Use 9.52×10^{-5} kg N₂O/GJ.
0.001 = Conversion factor from kilograms to tonnes.

(vii) To avoid double-counting, this emissions source excludes any emissions calculated under other emissions sources in this section. Where gas to be flared is manifolded from multiple sources in ON.353 to a common flare, report all flaring emissions under this section.

- (8) Centrifugal compressor venting. The person required to report pursuant to this quantification method shall calculate emissions from all centrifugal compressor vents as follows. Where venting emissions are sent to a common flare, calculate emissions using ON.353(a)(7).

Dry seal and wet seal centrifugal compressors can enter the following operating modes: “operating, pressurized”, “stand-by, pressurized” or “not-operating, depressurized”.

- (i) The person shall calculate CO₂, and CH₄, and N₂O (when flared) emissions from both wet seal and dry seal centrifugal compressor vents (including wet seal oil degassing vent lines, but excluding dry seal gas vent lines) for all compressors using the following.
- (A) temporary or permanent flow measurement meter such as, but not limited to, portable utility grade meter (bellows meter), high-flow sampler or vane anemometer according to methods set out in ON.354((a)(2) and (a)(4)).
- (B) A continuous monitoring device according to methods set out in ON.354(a)(5). If a continuous monitoring device is used, the volumetric gas emissions can be estimated using engineering calculations and appropriate parameter recordings from the continuous monitoring device. If the continuous monitoring device has an alarm, the volumetric gas emissions can be estimated using the flow rate at which the alarm is set. Parameter recordings must be available at a minimum frequency of monthly.

- (C) For through-valve leakage to open-ended vents, such as unit isolation valves on not-operating, depressurized compressors and blowdown valves on pressurized compressors, an acoustic detection device may be used according to methods set out in ON.354(a).
- (ii) Estimate annual emissions using flow meter measurement using Equation 350-17 of this section.

$$E_{s,i} = \sum_m Q_{s,m} \times t_m \times Y_i \times (1 - CF)$$

Equation 350-17

Where:

- $E_{s,i}$ = Annual GHG i (either CH₄ or CO₂) volumetric emissions from all compressor venting modes (Sm³).
- $Q_{s,m}$ = Measured volumetric gas emissions during operating mode m described in subparagraph (8)(v) of this section (Sm³/h).
- t_m = Total time the compressor is in operational mode m during the calendar year (h)
- Y_i = Annual average mole fraction of GHG i in the degassing vent gas; use the appropriate gas compositions in subparagraph (13)(ii) of this section.
- CF = Fraction of centrifugal compressor vent gas sent to vapour recovery or fuel gas or other beneficial use as determined by keeping logs of vent gas that is directed to the fuel gas system.
- m = The operational mode of a centrifugal compressor.

- (iii) To ensure that emissions for modes not found during the annual measurement are included in reported estimates, Equation 350-17a shall be used to calculate total emissions

$$E_{s,i,c} = E_{s,i} + E_{m,nf}$$

Equation 350-17a

Where:

- $E_{s,i,c}$ = Total estimate of emissions from all operating modes
- $E_{s,i}$ = Output of Equation 350-17
- $E_{m,nf}$ = Estimate of emissions for the modes not found during the annual measurement as calculated from emissions for mode not found for the compressor during previous years and prorated for the time in the year for the mode not found. If the mode not found did not occur in previous years, estimates from a similar compressor, CEPEI Methodology Manual or manufacturer emission factors may be used.

- (iv) An engineering estimate approach based on similar equipment specifications, CEPEI Methodology Manual or manufacturer's data may be used to determine the $Q_{s,m}$ variable in place of actual measured values for centrifugal compressors that are operated for no more than 1,314 hours during three consecutive calendar years immediately prior to the calendar year in place of metered gas volumes if an applicable meter is not present on the compressor. Alternatively, a source-specific emissions factor can be established by measuring the emissions from relevant sources during each operational mode.
- (v) Conduct an annual measurement for each compressor in the mode in which it is found (see below) during the annual measurement. As applicable, measure emissions from (including emissions manifolded to common vents) degassing vents and unit blowdown vents. If there is a safety risk that cannot be (reasonably) mitigated with measuring emissions from a specific vent line, the person may use an emission factor or optical gas imaging (OGI) measurement approach instead. Winter safety is not a valid safety risk unless the site can only be accessed during the winter. The operational modes and measurements are:
- (A) Operating pressurized mode, measure unit blowdown leakage through the unit blowdown vent stack for wet seal and dry seal compressors and wet seal degassing vent (if applicable);
- (B) Standby pressurized mode; measure unit blowdown valve leakage through the unit blowdown vent stack for wet and dry seal compressors;
- (C) Not operating, depressurized mode; measure unit isolation-valve leakage through the unit blowdown vent stack for wet and dry seal compressors.
- (C.1) Notwithstanding subparagraph (v) above, for the not operating, depressurized mode, each compressor shall be measured at least once in any three consecutive calendar years if this mode is not found in the annual measurement (if the compressor enters the not operating depressurized mode during normal service (i.e., excluding maintenance)).
- (C.2) A compressor is exempt from this requirement to measure in the not operating, depressurized mode if,
- During normal service, it remains pressurized and the only time the unit is depressurized is for maintenance or as a result of an emergency shutdown; or

- The compressor has blind flanges in place.

(C.3) If a compressor unit is exempt from the 3-year measurement requirement in C.1, use Equation 350-17a to calculate emissions for that unit for the not operating, depressurized mode.

- (vi) Calculate both CH₄ and CO₂ mass emissions from volumetric CH₄ and CO₂ emissions as determined in subparagraphs (8)(i) through (8)(iv) of this section using calculations in paragraph (a)(14) of this section.
- (vii) Calculate emissions from degassing vent vapours to flares as follows:
- (A) Use the degassing vent vapour volume and gas composition as determined in subparagraphs (8)(i) through (8)(iv) of this section.
- (B) Use the calculation methodology of flare stacks in paragraph (7) of this section to determine degassing vent vapour emissions from the flare.
- (viii) Emissions from centrifugal compressor dry seal gas vent lines may be determined following the procedures set out in paragraphs (a)(5) and (a)(7), engineering estimates or other industry standard method, as appropriate.

- (9) Reciprocating compressor venting. The person required to report pursuant to this quantification method shall calculate annual CH₄ and CO₂ emissions from all reciprocating compressor vents as follows.

Where venting emissions are sent to a common flare, calculate emissions using ON.353(7).

A reciprocating compressor's operational modes include "operating, pressurized", "standby, pressurized mode" and "not operating, depressurized".

- (i) Calculate annual emissions using the flow measurement in subparagraphs (9)(iii) or (9)(iv) below and Equation 350-18.

$$E_{s,i} = \sum_m Q_{s,m} \times t_m \times Y_i(1 - CF)$$

Equation 350-18

Where:

- $E_{s,i}$ = Annual volumetric emissions of GHG i (either CH₄ or CO₂) from all compressor venting modes (Sm³/y).
- $Q_{s,m}$ = Measured volumetric gas emissions during operating mode m described in subparagraph (9)(v) (Sm³/h).

- t_m = Total time the compressor is in operational mode m during the calendar year (h).
- Y_i = Annual average mole fraction of GHG i in the vent gas; use the appropriate gas compositions in subparagraph (13)(ii) of this section.
- CF = Fraction of reciprocating compressor vent gas sent to vapour recovery or fuel gas or other beneficial use as determined by keeping logs of the vent gas that is directed to the fuel gas system.
- m = The operational mode of a reciprocating compressor.

- (ii) Calculate total emissions, including modes not found during the annual measurement, using Equation 350-18a.

$$E_{s,i,c} = E_{s,i} + E_{m,nf}$$

Equation 350-18a

Where:

- $E_{s,i,c}$ = Total estimate of emissions from all operating modes
- $E_{s,i}$ = Output of Equation 350-18
- $E_{m,nf}$ = Estimate of emissions for the modes not found during the annual measurement as calculated from emissions for operational mode not found for the compressor during previous years and prorated for the time in the year for the mode not found. If the operational mode not found did not occur in previous years, estimates from a similar compressor, CEPEI Methodology Manual or manufacturer emission factors may be used.

- (iii) If the reciprocating rod packing and blowdown vent is connected to an open-ended vent line then use one of the following methods to calculate emissions.
- (A) Measure emissions from all vents (including emissions manifolded to common vents) including rod packing, and unit blowdown vents (leakage pass the unit blowdown or unit isolation valves using either calibrated bagging or High-flow Sampler according to methods set out in ON.354(a)(3) and (a)(4).
- (B) Use a temporary meter such as a portable utility grade meter (bellows meter) a vane anemometer or a permanent meter such as an orifice meter to measure emissions from all vents (including emissions manifolded to a common vent) including rod packing vents, unit isolation valves, and blowdown valves according to methods set out in ON.354(a)(2). If you do not have

a permanent flow meter, you may install a temporary meter or a permanent flow meter on the vents,

- (C) Use a continuous monitoring device, according to methods set out in ON.354(a)(5). If a continuous monitoring device is used in place of a temporary or permanent flow measurement meter, the volumetric gas emissions can be estimated using engineering calculations and appropriate parameter recordings from the continuous monitoring device, or if the continuous monitoring device has an alarm, the volumetric gas emissions can be estimated using the flow rate at which the alarm is set. Parameter recordings must be available at a minimum frequency of monthly.
 - (D) For through-valve leakage to open-ended vents, such as unit isolation valves on not-operating, depressurized compressors and blowdown valves on pressurized compressors, you may use an acoustic detection device according to methods set out in ON.354(a).
- (iv) If the rod packing case is not equipped with a vent line, use the following method to estimate emissions:
- (A) Use the methods described in ON.354(a)(1) to conduct a progressive leak detection of fugitive equipment leaks from the packing case into an open distance piece, or from the compressor crank case breather cap or vent with a closed distance piece.
 - (B) Measure emissions using a High-flow Sampler, or calibrated bag, or appropriate meter according to methods set out in ON.354(a)(2), (3), or (4).
- (v) An engineering estimate approach based on a similar compressor, CEPEI Methodology Manual, or manufacturer's data may be used to determine the $Q_{s,m}$ variable in place of actual measured values for reciprocating compressors that are operated for no more than 1,314 hours during the three consecutive calendar years immediately prior to the calendar year.
- (vi) Conduct an annual measurement for each compressor in the operational mode in which it is found during the annual measurement. Measure emissions from (including emissions manifolded to common vents) reciprocating rod-packing vents, unit isolation-valve vents, and unit blowdown-valve vents. If there is a safety risk that cannot be reasonably mitigated with measuring emissions from a specific vent line, the Person may use an emission factor or OGI approach instead. Given that there is not a requirement

to measure in the winter months, winter safety is not an applicable safety risk unless the site is only accessible in the winter.

The operational modes and measurements are:

- (A) Operating pressurized mode, measure unit blowdown valve leakage through the blowdown vent stack and reciprocating rod packing emissions.
- (B) Standby pressurized mode, measure unit blowdown-valve leakage through the unit blowdown vent stack and reciprocating rod packing emissions.
- (C) Not operating, depressurized mode, measure unit isolation-valve leakage through the unit blowdown vent stack.
 - (C.1) Notwithstanding subparagraph (vi) above, for the not operating, depressurized mode, each compressor shall be measured at least once in any three consecutive calendar years if this mode is not found in the annual measurement (if the compressor enters the not operating depressurized mode during normal service (i.e., excluding maintenance)).
 - (C.2) A compressor is exempt from this requirement to measure in the not operating, depressurized mode if,
 - During normal service, it remains pressurized and the only time the unit is depressurized is for maintenance or as a result of an emergency shutdown; or
 - The compressor has blind flanges in place.
 - (C.3) If a compressor unit is exempt from the 3-year measurement requirement identified in clause (C.1), use Equation 350-18a in subparagraph (9)(ii) to calculate emissions for that unit for the not-operating depressurized mode.
- (vii) Estimate CH₄ and CO₂ volumetric and mass emissions from volumetric natural gas emissions using the calculations in paragraphs (a)(13) and (a)(14) of this section.
- (viii) Adjust the emissions from reciprocating compressor vent vapors as follows if they are sent to a vapor recovery system.
 - (A) Adjust the emissions estimated in subparagraph (9)(i) of this section for the emissions recovered using a vapor recovery system as determined by using engineering estimate based on best available data, equipment or design specifications, manufacturer's data, operating data.

- (10) Leak detection and leaker emission factors. The person required to report pursuant to this calculation method shall use sampling methods (described in ON.354(a)) to conduct a leak detection survey of fugitive equipment leaks. All sources listed in ON.352(b)(2), (c)(2) (excluding the wellheads and underground piping that connect to the compression units), (d)(2), and (e)(2) where total emissions for the site is 10,000 tonnes of CO_{2e} or greater shall use this calculation method. If the total emissions from the site are less than 10,000 tonnes of CO_{2e}, the person may use this calculation method or the calculation method in paragraph (a)(11) of this section.

The calculation in paragraph (10) applies to emissions sources in streams with gas containing greater than 10 per cent CH₄ plus CO₂ by weight. Emissions sources in streams with gas containing less than 10 per cent CH₄ plus CO₂ by weight need to be reported instead under paragraph (15) of this section.

If fugitive equipment leaks are detected for sources listed in this paragraph, calculate equipment leak emissions per source using Equation 350-19 (for volumetric emission factor [Sm³/h/component]) or Equation 350-20 (for mass emission factors [t/h/component]) of this section, as appropriate, for each source with fugitive equipment leaks.

$$E_i = EF_s \times Y_i \times t \times \rho_{s,i} \times 0.001$$

Equation 350-19

$$E_{s,j} = EF_s \times Y_i \times t$$

Equation 350-20

Where:

- $E_{s,i}$ or $E_{s,j}$ = Annual total mass emissions of GHG_i (CH₄ or CO₂) from each fugitive equipment leak source (tonnes/year).
- EF_s = Leaker emission factor for specific sources listed in Table 350-1 through Table 350-5 of this section or facility/company-specific emission factors (see Note (a)) used in place of Tables 350-1 to 350-5 (Sm³/component/year for Equation 350-19 and tonnes/component/year for Equation 350-20).
- Y_i = For volumetric emissions in Equation 350-19, use 0.975 for CH₄ for natural gas transmission, compression and underground natural gas storage and 1.1×10^{-2} for CO₂; for LNG storage and LNG import and export equipment, Y_i equals 1 for CH₄ and 0 for CO₂; or use the experimentally determined gas composition for CO₂ and CH₄. For mass emissions in Equation 350-20, use mass fractions of CH₄

- and CO₂ from each unit of a distribution or transmission company within a jurisdiction that has similar gas composition or the CEPEI Methodology Manual.
- t = Total time the component was found leaking and operational, in hours. If one leak detection survey is conducted, assume the component was leaking from the start of the year or the date of the last survey until the leak was repaired and then zero for the remainder of the interval between leak surveys. If the leak was not repaired, assume the component was leaking for the entire year or the entire leak survey interval. If multiple leak detection surveys are conducted, assume that the component found to be leaking has been leaking since the last survey during which it was determined to be not leaking, or the beginning of the calendar year. For the last leak detection survey in the calendar year or leak survey interval, assume that all leaking components continue to leak until the end of the calendar year or leak survey interval and until the component was repaired and then zero until the end of the year or leak survey interval.
- $\rho_{s,i}$ = Density of GHG *i* (1.861 kg/m³ for CO₂ and 0.678 kg/m³ for CH₄ at standard conditions of 15 °C and 1 atmosphere).
- 0.001 = Conversion factor from kilograms to tonnes.
- (i) Onshore natural gas transmission compression stations shall use the appropriate default leaker emission factors listed in Table 350-1 of this section for fugitive equipment leaks detected from connectors, valves, pressure relief valves, meters, and open ended lines (see Note (a)).
 - (ii) Underground natural gas storage stations shall use the appropriate default leaker emission factors listed in Table 350-2 of this section for fugitive equipment leaks detected from connectors, valves, pressure relief valves, meters, and open-ended lines (see Note (a)).
 - (iii) LNG storage stations shall use the appropriate default leaker emission factors listed in Table 350-3 of this section for fugitive equipment leaks detected from valves, pump seals, connectors, and other equipment (see Note (a)).
 - (iv) LNG import and export stations shall use the appropriate default leaker emission factors listed in Table 350-4 of this section for fugitive equipment leaks detected from valves; pump seals; connectors; and other (see Note (a)).

Note (a): The Person may use component-specific emission factors quantified using ON.354(a)(1)(ii)(A), (a)(3) or (a)(4) during leak detection surveys.

- (11) Population count and emission factors. The person required to report pursuant to this quantification method shall use the following calculation for sites with total emissions that are less than 10,000 tonnes per year, for sources listed in ON.352 (b)(2), (c)(2), (d)(2), and (e)(2).

The person shall also use the following calculation method for sources listed in ON.352, (f)(1), (f)(2).

The calculation in paragraph (11) applies to emissions sources on streams with gas containing greater than 10 per cent CH₄ plus CO₂ by weight. Emissions sources in streams with gas containing less than 10 per cent CH₄ plus CO₂ by weight do not need to be reported.

Emission sources at which a leak detection survey has been conducted and reported under paragraph (a)(10) in this section (either voluntarily or required under paragraph (a)(10)) are exempt from the requirements under paragraph (a)(11) in this section.

Calculate emissions from all sources listed in this paragraph using

Equation 350-21 (for volumetric emission factor [m³/h/component]) or Equation 350-22 (for mass emission factors [kg/h/component]) of this section, as appropriate.

$$E_i = N \times EF_s \times Y_i \times t \times p_{s,i} \times 0.001$$

Equation 350-21

$$E_i = N \times EF_s \times X_i \times t \times 0.001$$

Equation 350-22

Where:

- E_i = Annual total mass emissions of GHG i (CH₄ or CO₂) from each fugitive source (tonnes/year).
- N = Total number of this type of component at the site. The average component counts from the CEPEI Methodology Manual, other relevant Canadian Gas Association (CGA) or Canadian Association of Petroleum Producers (CAPP) documentation may be used, as appropriate and required by (i) through (v), or if station or company-specific component count data is available and meets or exceeds the quality of the relevant default count data, they shall be used in its place. Current processing and instrumentation drawings (P&ID) may be used for the source of component counts.

EF_s	=	Population emission factor for specific components listed in Table 350-1 through Table 350-5 of this section ($\text{Sm}^3/\text{component}/\text{hour}$ for Equation 350-21 and tonnes/component/hour for Equation 350-22). Direction on the use of Tables 350-1 through 350-5, provided prior to the tables, shall be followed and indicates that if the person's company specific emission factors are available, the person's company specific emission factors shall be used (see Note (b)).
Y_i	=	For volumetric emissions in Equation 350-21, use 0.975 for CH_4 for natural gas transmission, compression and underground natural gas storage and 1.1×10^{-2} for CO_2 ; for LNG storage and LNG import and export equipment, Y_i equals 1 for CH_4 and 0 for CO_2 ; and for natural gas distribution, Y_i equals 1 for CH_4 and 1.1×10^{-2} for CO_2 or use the volume fractions of CO_2 and CH_4 from the company specific data or the CEPEI Methodology Manual.
X_i	=	For mass emissions in Equation 350-22, use mass fractions of CH_4 and CO_2 from the company specific data or the CEPEI Methodology Manual.
t	=	Total time the specific source was operational in the calendar year (hours).
$\rho_{s,i}$	=	Density of GHG i ($1.861 \text{ kg}/\text{m}^3$ for CO_2 and $0.678 \text{ kg}/\text{m}^3$ for CH_4 at standard conditions of $15 \text{ }^\circ\text{C}$ and 1 atmosphere).
0.001	=	Conversion factor from kilograms to tonnes.

Note (b): The person's company specific emission factors may be developed based on leak rates quantified, following ON.354(3) or (4), during leak detection surveys or those emission factors calculated for the purposes of ON.356 – Directions for the use of Tables 350-1 to 350-5.

- (i) Transmission stations shall use the appropriate default population emission factors listed in Table 350-1 of this section for fugitive equipment leaks from connectors, valves, pressure relief valves, and open-ended lines.
- (ii) Underground natural gas storage stations shall use the appropriate default population emission factors listed in Table 350-2 of this section for fugitive equipment leaks from connectors, valves, pressure relief valves, and open-ended lines.
- (iii) LNG storage stations shall use the appropriate default population emission factors listed in Table 350-3 of this section for fugitive equipment leaks from vapour recovery compressors (except storage at LNG import and export facilities which is covered in subparagraph (iv) below).

- (iv) LNG import and export stations shall use the appropriate default population emission factor listed in Table 350-4 of this section for fugitive equipment leaks from vapour recovery compressors.
- (v) Natural gas distribution facilities shall use the CEPEI Methodology Manual methods and default or company-specific emission factors.
 - (A) Below grade metering-regulating stations; distribution mains; and distribution services, shall be estimated using the CEPEI Methodology Manual methods and the appropriate default population emission factors listed in Table 350-5 of this section.
 - (B) Above grade meter-regulating stations and all other above-grade stations including customer meters shall be estimated using the CEPEI Methodology Manual methods and default or company specific component emission factors.
- (12) Volumetric emissions. The person required to report pursuant to this quantification method shall calculate volumetric emissions at standard conditions as specified in subparagraph (12)(i) or (12)(ii), with actual pressure and temperature of this section determined by engineering estimate based on best available data unless otherwise specified.
 - (i) Calculate natural gas volumetric emissions at standard conditions by converting actual temperature and pressure to standard temperature and pressure (15 °C and 1 atmosphere) using Equation 350-23 of this section.

$$E_s = \frac{E_a \times (273.15 + T_s) \times P_a}{(273.15 + T_a) \times P_s}$$

Equation 350-23

Where:

- E_s = Natural gas volumetric emissions at standard temperature and pressure (STP) conditions (Sm^3).
- E_a = Natural gas volumetric emissions at actual conditions (m^3).
- T_s = Temperature at standard conditions (15C °).
- T_a = Temperature at actual emission conditions (°C).
- P_s = Absolute pressure at standard conditions (101.325 kPa).
- P_a = Absolute pressure at actual conditions (kPa).

- (ii) Calculate GHG volumetric emissions at standard conditions by converting actual temperature and pressure of GHG emissions to standard temperature and pressure using Equation 350-24 this section.

$$E_{s,i} = \frac{E_{a,i} \times (273.15 + T_s) \times P_a}{(273.15 + T_a) \times P_s}$$

Equation 350-24

Where:

- $E_{s,i}$ = GHG_i volumetric emissions at standard temperature and pressure (STP) conditions (Sm³).
- $E_{a,i}$ = GHG_i volumetric emissions at actual conditions (m³).
- T_s = Temperature at standard conditions (15°C).
- T_a = Temperature at actual emission conditions (°C).
- P_s = Absolute pressure at standard conditions (101.325 kPa).
- P_a = Absolute pressure at actual conditions (kPa).

- (13) GHG volumetric emissions. The person required to report pursuant to this quantification method shall calculate the volumetric emission using the following calculations.

If the GHG volumetric emissions at actual conditions are known, follow the method in paragraph (13)(ii) to calculate their emissions at standard conditions.

If the GHG volumetric emissions are not yet known, use engineering estimate based on best available data unless otherwise specified and the methods below to calculate GHG volumetric emissions at standard conditions as specified in subparagraphs (13)(i) and (13)(ii) of this section determined by.

- (i) Estimate CH₄ and CO₂ emissions from natural gas emissions using Equation 350-25 of this section

$$E_{s,i} = E_s \times Y_i$$

Equation 350-25

Where:

- $E_{s,i}$ = GHG_i (either CH₄ or CO₂) volumetric emissions at standard conditions.
- E_s = Natural gas volumetric emissions at standard conditions.
- Y_i = Mole fraction of GHG_i in the natural gas.

- (ii) For Equation 350-25 of this section, the mole fraction, Y_i , shall be the annual average mole fraction for each unit of a natural gas distribution, natural gas transmission, LNG storage, LNG import or export, or underground natural gas storage company within a jurisdiction that has similar gas composition as sampled within the current (required if available) or previous (if current data are not available) reporting period, using the methods set out in ON.354(a(2)), and specified in paragraphs below.

- (A) GHG mole fraction in transmission pipeline natural gas that passes through the onshore natural gas transmission compression stations.
 - (B) GHG mole fraction in natural gas stored in underground natural gas storage.
 - (C) GHG mole fraction in natural gas stored in LNG storage station.
 - (D) GHG mole fraction in natural gas stored in LNG import and export station.
 - (E) GHG mole fraction in local distribution pipeline natural gas that passes through the natural gas distribution system.
- (14) GHG mass emissions. The person required to report pursuant to this quantification method shall calculate GHG mass emissions in tonnes by converting the GHG volumetric emissions at standard conditions into mass emissions using Equation 350-26 of this section.

$$E_i = E_{s,i} \times \rho_{s,i} \times 0.001$$

Equation 350-26

Where:

- E_i = GHG_i (either CH₄, CO₂, or N₂O) mass emissions (tonnes).
- $E_{s,i}$ = GHG_i (either CH₄, CO₂ or N₂O) volumetric emissions at standard conditions (Sm³).
- $\rho_{s,i}$ = Density of GHG *i* (1.861 kg/m³ for CO₂ and 0.678 kg/m³ for CH₄ at standard conditions of T_S = 15°C and P_S = 101.325 kPa).

$$\rho_{s,i} = \frac{P_s \times MW_i}{R_u \times (T_s + 273.15)}$$

- MW_i = Molecular weight for GHG_i (kg/kmole).
- R_u = Universal gas constant (8.31434 kJ/kmole K)
- 0.001 = Conversion factor from kilograms to tonnes

- (15) Other venting or fugitive emissions. The person required to report pursuant to this quantification method shall determine all venting or fugitive emissions not covered by quantification methods in ON.353 using methodologies consistent with those presented in the CEPEI Methodology Manual, or in other relevant documents published by any other industry association.
- (16) Transmission storage tanks. The person required to report pursuant to this quantification method shall determine emissions from transmissions storage tanks using the following.

For condensate storage tanks, either water or hydrocarbon, without vapour recovery or thermal control devices in onshore natural gas transmission compression facilities the operator shall calculate CH₄, CO₂ and N₂O (when flared) annual emissions from compressor scrubber dump valve leakage as follows.

- (i) Monitor the tank vapour vent stack annually for emissions using an optical gas imaging instrument according to methods set out in ON.354(a)(1) or by directly measuring the tank vent using a flow meter, calibrated bag, or High-flow Sampler according to methods in ON.354(a)(2) through (4) for a duration of 5 minutes. Or the person may annually monitor leakage through compressor scrubber dump valve(s) into the tank using an acoustic leak detection device according to methods set out in ON.354(a)(1)(D).
- (ii) If the tank vapours are continuous for 5 minutes, or the acoustic leak detection device detects a leak, then use one of the following two methods.
 - (A) Use a meter, such as a turbine meter, calibrated bag, or High-flow Sampler to estimate tank vapour volumes according to methods set out in ON.354(a)(2) through (4). If the vent is directly measured for five minutes under subparagraph (16)(i) of this section to detect continuous leakage, this serves as the measurement.
 - (B) Use an acoustic leak detection device on each scrubber dump valve connected to the tank according to the method set out in ON.354(a).
 - (C) Use the appropriate gas composition in paragraph (13) of this section.
- (iii) If the leaking dump valve(s) is fixed following leak detection, the annual emissions shall be calculated from the beginning of the calendar year to the time the valve(s) is repaired. If the leak is not repaired, assume the dump valve is leaking for the entire year or until the dump valve is repaired.
- (iv) Calculate annual emissions from storage tanks to flares as follows:
 - (A) Use the storage tank emissions volume and gas composition as determined in subparagraphs (13)(i) through (13)(iii) of this section.
 - (B) Use the calculation methodology of flare stacks in paragraph (7) of this section to determine storage tank emissions sent to a flare.

ON.354 Sampling, Analysis, and Measurement Requirements

- (a) The person required to report pursuant to this quantification method shall ensure instruments used for sampling, analysis and measurement shall be operated and calibrated according to regulatory, manufacturer's, or other written specifications or requirements. All sampling, analysis and measurement shall be conducted only by, or under the direct supervision of personnel or individuals with demonstrated understanding and experience in the application (and principles related) of the specific sampling, analysis and measurement technique in use.
- (1) The person required to report pursuant to this quantification method shall undertake the following Leak Detection program
- (i) If a documented leak detection or integrity management standard or requirement that is required by Ontario or federal legislation or regulation (e.g., CSA Z662-07 Oil & Gas Pipeline Systems) or by a standard or method from CEPEI, the documented standard or requirement shall be followed – including service schedules for different components and/or facilities - with reporting as required for input to the calculation methods herein. A maximum of 36 months is allowed between leak detection surveys.
 - (ii) If there is no such legal requirement (as specified in the previous paragraph), then representative sampling is required using one of the methods outlined below in combination with best industry practices for use of the method– including service schedules for different components - to determine the count of leaks (and time leaking) required in ON.353 (a)(10), as applicable. Representative sampling means establishing the most valid or credible sample of leaks that accurately characterizes the number of fugitive equipment leaks required per sample interval, under operating conditions. A baseline representative sample of leaks shall be established under normal operating conditions for the 2017 calendar years or upon acquisition of previously operated equipment or within the first year of operation of newly constructed or acquired equipment. Subsequent representative sampling shall be based on random or stratified sampling, modeling, detection or measurement of leaks under normal operating conditions. After establishing the baseline representative sample of leaks per sample interval, a maximum of 36 months is allowed between sampling. The interval is determined based on whether there are leaks. If a leak is found and immediately repaired, the existing schedule may be maintained. If a leak is found and not repaired the maximum interval between sampling is 18 months and the leak shall be monitored (and optionally measured) on a regular basis until repaired. If the equipment is replaced the maximum

sampling interval is 18 months until a baseline representative sample of leaks has been established under normal operating conditions.

Leak detection for fugitive equipment leaks shall be performed for all identified equipment in operation or on standby mode using one of the following.

- (A) Optical gas imaging (OGI) instrument. Use an optical gas imaging instrument for fugitive equipment leaks detection in accordance with 40 CFR part 60, subpart A, §60.18(i)(1) and (18)(i)(2) Alternative work practice for monitoring equipment leaks. In addition, the optical gas imaging instrument shall be operated to image the source types required by this proposed reporting rule in accordance with the instrument manufacturer's operating parameters. The optical gas imaging instrument shall comply with the following requirements:
 - (A.1) Provide the person with an image of the potential leak points for each piece of equipment at both the detection sensitivity level and within the distance used in the daily instrument inspection described in the relevant best practices. The detection sensitivity level depends upon the frequency at which leak monitoring is to be performed.
 - (A.2) Provide a date and time stamp for video records of every monitoring event.
 - (B) Bubble tests. Uses soap or other types of bubbles on equipment to visually detect the leak of gases from the equipment.
 - (C) Portable organic vapour analyzer. Use a portable organic vapour analyzer in accordance with US EPA Method 21 or as outlined in CEPEI methodologies or the CAPP Best Management Practices for Fugitive Emissions (as amended from time to time)
 - (D) Other methods as outlined in CEPEI methodologies or the CAPP Best Management Practices for Fugitive Emissions (as amended from time to time) may be used as necessary for operational circumstances. Other methods based on an engineering assessment may also be used as necessary for operational circumstances provided there is documentation on the method used, results of tests, and the method's reliability and accuracy is maintained and updated at regular intervals.
- (2) All flow meters, composition analyzers and pressure gauges that are used to provide data for the GHG emissions calculations shall use appropriate QA/QC procedures, including measurement methods, maintenance practices, and calibration methods by 2018 and in each

subsequent calendar year according to an appropriate standard published by a consensus standards organization. If a consensus-based standard is not available, industry standard practices such as manufacturer instructions shall be used.

- (3) Use calibrated bags (also known as vent bags) only where the emissions are at or near atmospheric pressures and hydrogen sulphide levels are such that it is safe to handle and can capture all the emissions, below the maximum temperature specified by the vent bag manufacturer, and the entire emissions volume can be encompassed for measurement.
 - (i) Hold the bag in place enclosing the emissions source to capture the entire emissions and record the time required for completely filling the bag. If the bag inflates in less than one second, assume one second inflation time.
 - (ii) Perform three measurements of the time required to fill the bag, report the emissions as the average of the three readings.
 - (iii) Correct the natural gas volumetric emissions to standard conditions using the calculations in ON.353(a)(12).
 - (iv) Estimate CH₄ and CO₂ volumetric and mass emissions from volumetric natural gas emissions using the calculations in ON.353(a)(13) and (a)(14).
- (4) Use a high-flow sampler to measure emissions within the capacity of the instrument.
 - (i) Calibrate the instrument at 2.5 per cent methane with 97.5 per cent air and 100 per cent CH₄ by using calibrated gas samples and by following manufacturer's instructions for calibration.
 - (ii) Conduct measurements, using equipment manufacturer operating procedures and relevant measurement methodologies, by positioning the instrument for complete capture of the fugitive equipment leaks without creating backpressure on the source.
 - (iii) If the High-flow Sampler, along with all attachments available from the manufacturer, is not able to capture all the emissions from the source then you shall use anti-static wraps or other aids to capture all emissions without violating operating requirements as provided in the instrument manufacturer's manual.
 - (iv) Estimate CH₄ and CO₂ volumetric and mass emissions from volumetric natural gas emissions using the calculations in ON.353(a)(13) and (a)(14).
- (5) All continuous monitoring devices used to provide data for the GHG emissions calculations shall use appropriate QA/QC procedures,

including operating methods, maintenance practices, and calibration methods according to an appropriate standard published by a consensus based standards organization. If a consensus based standard is not available, industry standard practices such as manufacturer instructions shall be used.

ON.355 Procedures for Estimating Missing Data

- (a) The person required to report pursuant to this quantification method shall retain a complete record of all estimated and/or measured parameters used in the GHG emissions calculations.
- (b) If data are lost or an error occurs during annual emissions estimation or measurements, the estimation or measurement activity for those sources shall be repeated as soon as possible, including in the subsequent calendar year if missing data are not discovered until after December 31 of the calendar year, until valid data for reporting is obtained.
- (c) Data developed and/or collected in a subsequent calendar year to substitute for missing data cannot be used for that subsequent year's emissions estimation.
- (d) Where missing data procedures are used for the previous year, at least 30 days shall separate emissions estimation or measurements for the previous year and emissions estimation or measurements for the current year of data collection.
- (e) For missing data that are continuously monitored or measured (for example flow meters), or for missing temperature and pressure data, the person may use best available data for use in emissions determinations. The person shall record and report the basis for the best available data in these cases.

ON.356 Tables

Directions for the use of Tables 350-1 to 350-5:

- (a) For each component listed in the Tables 350-1 to 350-5 or otherwise required by the quantification method referencing Tables 350-1 and 350-2:
 - (1) The person may use the default emission factors specified below.
 - (2) If statistically valid company-specific emission factors for a component type are available they may be used.
- (b) If an emission factor required by the quantification method referencing Tables 350-1 through 350-5 is not provided in the tables, emission factors from the CEPEI Methodology Manual or U.S. EPA 40 CFR Part 98.230 Tables W-3 through W-7 (in order of preference), may be used (as converted for use in the relevant equation).

- (c) Documentation on the method used to update emission factors, input data, sampling methodology and other relevant information shall be kept by the person and provided to the jurisdiction or verifier upon request.
- (d) Updated emission factors can only be incorporated for reporting purposes at the start of a reporting period and not during a calendar year.
- (e) All emission factors or data collection for emission factors shall be developed using the CEPEI Methodology Manual, or other methods if the CEPEI Methodology Manual methods are not available or applicable. Company-specific emission factors that have been developed using existing company leak quantification data shall be updated at a minimum on a three year cycle, with the first update to the original facility and company-specific emission factors for the 2020 reporting period, at the latest.

Table 350-1 –Default Emission Factors for Transmission

All Components, Natural Gas Service	Population Emission Factor^{1a} (tonnes/hr/component)	Leaker Emission Factor^{1b} (tonnes/hr/component)
Connector	4.471E-7	4.848E-5
Block valve	4.131E-6	1.275E-4
Control valve	1.650E-5	8.205E-5
Station or pressurized compressor blowdown valve	3.405E-3	5.691E-3
Pressure relief valve	1.620E-4	5.177E-4
Orifice meter	4.863E-5	2.076E-4
Other flow meter	9.942E-9	3.493E-7
Regulator	7.945E-6	1.125E-4
Open-ended line	9.183E-5	1.580E-4

1. Clearstone Engineering Ltd. *Methodology Manual: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System*. Prepared for Canadian Energy Partnership for Environmental Innovation (CEPEI). 2018, as amended from time to time.
 - a. Table 9, p58
 - b. Table 12, p87.

**Table 350-2
Default Methane Emission Factors for Underground Storage***

Underground Storage	Emission Factor (Sm³/hour/component) Direct conversion of EF's in EPA Subpart W Table¹ W-4 (scf to Sm³)
Leaker Emission Factors - Storage Station, Gas Service -Valve ²	4.268 E-1
Leaker Emission Factors - Storage Station, Gas Service – Connector	1.60 E-1
Leaker Emission Factors - Storage Station, Gas Service - Open-ended line	4.967 E-1
Leaker Emission Factors - Storage Station, Gas Service - Pressure relief valve	1.140
Leaker Emission Factors - Storage Station, Gas Service - Meter	5.560 E-1
Population Emission Factors - Storage Wellheads, Gas Service – Connector	2.8 E-4
Population Emission Factors - Storage Wellheads, Gas Service – Valve	2.8 E-3
Population Emission Factors - Storage Wellheads, Gas Service - Pressure relief valve	4.8 E-3
Population Emission Factors - Storage Wellheads, Gas Service - Open-ended line	8.5 E-4

¹.Emission factors are conversions of those contained in the U.S. EPA Subpart W Table W-4.

².Valves include control valves, block valves and regulator valves

**Table 350-3
Default Methane Emission Factors For Liquefied Natural Gas (LNG) Storage²**

LNG Storage	Emission Factor (Sm³/hour/component) Direct conversion of EF's in EPA Subpart W Table W-5 (scf to Sm³)
Leaker Emission Factors - LNG Storage Components, LNG Service - Valve	3.43 E-2
Leaker Emission Factors - LNG Storage Components, LNG Service - Pump seal	1.15 E-1
Leaker Emission Factors - LNG Storage Components, LNG Service - Connector	9.9 E-3
Leaker Emission Factors - LNG Storage Components, LNG Service - Other ¹	5.10 E-2
Population Emission Factors - LNG Storage Compressor, Gas Service -Vapour Recovery Compressor	1.20 E-1

¹The “other” equipment type should be applied for any equipment type other than connectors, pumps, or valves.

² Emission factors are conversions of those contained in the U.S. EPA Subpart W Table W-5.

Table 350-4–Default Methane Emission Factors for LNG Terminals¹

LNG Terminals	Emission Factor (Sm³/hour/component) Direct conversion of EF's in EPA Subpart W Table W-6 (scf to Sm³)
Leaker Emission Factors - LNG Terminals Components, LNG Service - Valve	3.43 E-2
Leaker Emission Factors - LNG Terminals Components, LNG Service - Pump seal	1.15 E-1
Leaker Emission Factors - LNG Terminals Components, LNG Service - Connector	9.9 E-3
Leaker Emission Factors - LNG Terminals Components, LNG Service - Other	5.10 E-2
Population Emission Factors - LNG Terminals Compressor, Gas Service - Vapour recovery compressor	1.20 E-1

¹Emission factors are conversions of those contained in the U.S. EPA Subpart W Table W-6.

**Table 350-5
Default Emission Factors for Distribution**

	CEPEI ¹	CEPEI ¹
Components	Population Emission Factor^{*a} (tonnes/hr/source)	Leaker Emission Factor^{*b} tonnes/hr/source
Connector	8.227E-8	6.875E-6 ^b
Block valve	5.607E-7	1.410E-5 ^b
Control valve	1.949E-5	7.881E-5 ^b
Pressure relief valve	3.944E-6	3.524E-5 ^b
Orifice meter	3.011E-6	8.091E-6 ^b
Other flow meters	7.777E-9	2.064E-7 ^b
Regulator	6.549E-7	2.849E-5 ^b
Open-ended line	6.077E-5	1.216E-4 ^b
Below Grade M&R Station Components, Natural Gas Service	Population Emission Factor (Sm³/hr/Station)	
Below grade M&R station, inlet pressure > 300 psig	3.681E-2 or value from CEPEI Manual	
Below grade M&R station, inlet pressure 100 to 300 psig	5.663E-3 or value from CEPEI Manual	
Below grade M&R station, inlet pressure < 100 psig	2.832E-3 or value from CEPEI Manual	
Distribution Mains, Natural Gas Service	Population Emission Factor (Sm³/hr/km)	
Unprotected steel	or 2.427E-1 or value from CEPEI Manual	
Protected steel	6.829E-3 or value from CEPEI Manual	
Plastic	7.969E-3 or value from CEPEI Manual	
Distribution Services, Natural Gas Service	Population Emission Factor (Sm³/hr/service)	
Unprotected steel	5.953E-3 or value from CEPEI Manual	
Protected steel	6.270E-4 or value from CEPEI Manual	
Plastic	4.036E-5 or value from CEPEI Manual	
Copper	8.829E-4 or value from CEPEI Manual	

¹. CEPEI Methodology Manual. (2018), as amended from time to time.
A typical natural gas density is considered to be 0.70772 kg/m³.

- a—Table 9 Average emission factors for estimating fugitive equipment leaks at gas transmission and distribution facilities.
 - b—Table 12 leaker emission factors for estimating fugitive equipment leaks at Canadian natural gas transmission and distribution facilities,
- ². US EPA, Mandatory Reporting of greenhouse Gases – Rules and Regulations, Subpart W Table 7, Nov. 30, 2016.
- * The distribution emission factors in Table 350-5 should be used for equipment in odourized service and the transmission factors in Table 350-1 should be used for equipment in unodourized service, regardless of the actual classification or functionality of the station.

Table 350-6 Average bleed rates for pneumatic controllers, intermittent bleed devices and pumps (or their equivalents as listed) in the table below

Pneumatic Device	Average Bleed Rate (m³/hr)	Coefficients (supply pressure, injection pressure, strokes per min)	Equivalent Device
Generic High Bleed Controller	0.2605	0.0012	-
Generic High Bleed Intermittent Controller	0.2476	0.0012	-
Generic Low Bleed Intermittent Controller	0.0665	-	-
Generic Low Bleed (Continuous) Controller	0.0388	-	-
Pressure Controllers - Fisher 4150	0.4209	0.0019	4150
Pressure Controllers - Fisher C1	0.0649	-	-
Pressure Controllers - Fisher 4660	0.0151	0.0003	4660A
Level Controllers Fisher 2500	0.3967	0.0011	2500S, 2503, L3
Level Controllers Fisher 2680	0.2679	0.0014	2680A
Level Controllers Fisher 2900	0.1447	-	2900A, 2901, 2901A
Level Controllers Fisher L2	0.2641	0.0012	-
Level Controllers Murphy LS1200	0.2619	0.0012	LS1100, LS1200N, LS1200DVO
Level Controllers Norriseal 1001	0.1868	-	1001A, 1001XL
Level Controllers SOR 1530	0.0531	-	-
Positioners - Fisher Fieldvue DVC6000	0.2649	0.0011	6030, 6020, 6010
Temperature Controllers - Kimray HT-12	0.0351	-	-
Transducers - Fairchild TXI7800	0.1543	0.0009	TXI7850
Transducers - Fisher 546	0.3547	0.0017	546S
Transducers - Fisher i2P-100	0.2157	0.0009	-
Generic Piston Pump	0.5917	0.00202, 0.000059, 0.0167	-
Generic Diaphragm Pump	1.0542	0.0005, 0.000027, 0.0091	-
Pumps - Morgan HD312	1.1292	0.00418, 0.000034, 0.0073	HD312-3K, HD312-5K
Pumps - Texsteam 5100	0.9670	0.0003, 0.000034, 0.0207	5100LP, 5100H
Pumps - Williams P125	0.4098	0.00019, 0.000024, 0.0076	-
Pumps - Williams P250	0.8022	0.00096, 0.000042, 0.0079	-
Pumps - Williams P500	0.6969	0.00224, -0.000031, 0.0046	-

- 1- this table provides a list of equivalent pneumatic controllers. If a controller is listed in the equivalents column, then the emission factor or coefficient(s) for the equivalent manufacturer and model provided shall be used
 2 – Controllers that do not have a coefficient should use the mean bleed rate instead of the bleed rate equation
 3 - All data (excluding low bleed devices) in Table 350-6 from Final Report – For Determining Bleed Rates for Pneumatic Devices in British Columbia. The Prasino Group. December 2013.

Table 350-7 Nomenclature (subscripts, variables and their descriptions)

Variable Name	Description
A	Variable – Area
A	Subscript – Actual condition for temperature and pressure
CF	Variable – Control factor (fractional)
D	Variable – Diameter
E	Variable – Greenhouse Gas release rate
E	Subscript – exit point
EF	Variable – Emission factor
GOR	Variable – Gas to oil ratio
GWP	Variable – Global warming potential
HHV	Variable – Higher (gross) heating value
I	Subscript - Chemical compound
J	Subscript - Individual device, equipment, meter or well
K	Variable – Specific heat ratio for gases
K	Subscript - Service type (e.g., fuel gas, process gas, liquid, etc.)
L	Variable - Length
L	Subscript - Individual equipment components
M	Variable – Mach number
MW	Variable – Molecular weight
M	Subscript – Operating mode
N	Variable – Count of devices, equipment, meters, wells, events, etc.
N	Variable – Number of carbon atoms in a molecule of a specified
P	Variable – Pressure
R	Variable – Universal Gas Constant
S	Subscript – Standard condition for temperature (15 °C) and pressure (101.325 kPa)
T	Variable – Time duration of event
T	Variable – Temperature (°C)
Q	Variable – Volumetric flow rate
V	Variable - Volume
X	Variable - Mass fraction
Y	Variable - Mole fraction
<i>P</i>	Variable - density

η	Variable – efficiency (fractional)
--------	------------------------------------

ON.190 Other Emissions

ON.191 Activity Definition

For the purposes of this standard quantification method (SQM):

“Other Emissions” are those described in subsection 12 (1.1) of the Regulation which are not reported under another SQM, and exclude CO₂ from biomass decomposition.

“Person” means a person that engages in one or more activities listed in Column 1 of Schedule 2 of the Regulation and that is required by the regulation to report GHG emissions resulting from those activities.

ON.192 Greenhouse Gas Reporting Requirements

- (a) Where the person has GHG emissions resulting from engaging in one or more activities listed in Column 1 of Schedule 2 of the Regulation that are not quantified using the standard quantification method for that activity, the person shall set out the following information, calculated for the calendar year using this SQM ON.190 – ON.194, in an emission report prepared for a calendar year in respect of a facility:
- (b) total annual quantity of CO₂ emissions for each category of emission, expressed in tonnes (t);
- (c) total annual CH₄ emissions for each category of emission, expressed in tonnes (t);
- (d) total annual N₂O emissions for each category of emission, expressed in tonnes (t);
- (e) total annual CO₂ emissions from biomass combustion, expressed in tonnes (t)
- (f) total annual CH₄ and N₂O emissions from biomass combustion, expressed in tonnes (t);
- (g) Total annual emissions of SF₆, and each HFC and PFC, expressed in tonnes (t);
- (h) the source category of the emissions
 - (1) stationary fuel combustion,
 - (2) industrial process,
 - (3) industrial product use,
 - (4) venting,
 - (5) flaring,
 - (6) leakage,

- (7) on-site transportation,
 - (8) waste, and
 - (9) waste water.
- (i) The method used to calculate the emissions (e.g., monitoring or direct measurements, mass balance, emission factors, or engineering estimates)

ON.193 Calculation of GHG Emissions

The person shall quantify emissions from each source category listed in ON.192

(h) using one of the following:

- (a) A method that is consistent with the 2006 Intergovernmental Panel on Climate Change (IPCC) Guideline;
- (b) A method that is consistent with a calculation method(s) in another SQM in this Guideline.

ON.194 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance with the following:

- (a) Direct measurements or estimates derived from direct measurements of the parameters required for the calculations;
- (b) Quantities of material, energy, production or any other parameters from invoices, shipping records, purchase records, financial records, or data used for accounting purposes;
- (c) Measurement and other data from suppliers;
- (d) Engineering estimates of parameters required for the calculations;
- (e) Literature values of parameters.

ON.300 Petrochemical Production

ON.301 Activity Definition

For the purposes of this standard quantification method (SQM):

“Petrochemical production” has the same meaning as in the Regulation.

“Person” means a person that engages in petrochemical production.

ON.302 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.300 – ON.305, in an emission report prepared for a calendar year in respect of petrochemical production at a facility.
- (b) CO₂, N₂O, and CH₄ emissions from flares or other combustion devices in tonnes using methods ON.303(a)(1), ON.303(a)(2) or ON.303(c).
- (c) CO₂, N₂O, and CH₄ process emissions from vents in tonnes using method ON.303(a)(3).
- (d) CO₂, N₂O, and CH₄ process emissions from equipment leaks in tonnes using method ON.303(a)(4).
- (e) CO₂ process emissions in tonnes using method ON.303(b).
- (f) CO₂, N₂O, and CH₄ process emissions from ethylene production facilities in tonnes using method ON.303(c).
- (g) Annual consumption of feedstock by type for all feedstocks that result in GHG emissions in standard cubic meters for gases; kilolitres for liquids and tonnes for solid fuels.
- (h) N₂O, and CH₄ process emissions from waste water emissions in tonnes using method ON.203(g).

ON.303 Calculation of GHG Emissions

Calculate GHG emissions using one of the calculation methodologies in subsection (a), (b), or (c):

- (a) Calculation Methodology 1: Calculate the GHG emissions from petrochemical production processes using the methods specific in paragraphs (a)(1) through (a)(3) of this section.
 - (1) For flares, calculate CO₂, CH₄ and N₂O emissions using the methods specified in ON.203(e) or ON.23(c).
 - (2) For combustion devices other than flares, calculate CO₂, CH₄ and N₂O emissions resulting from the combustion of fuels and process off-gas as specified in subparagraphs (a)(2)(i) through (a)(2)(iii):

- (i) Calculate CO₂ emissions from fuels and process off-gas in accordance with the methods in specified in ON.23.
 - (ii) Calculate CH₄ and N₂O emissions from combustion of fuels using the applicable methods in ON.24.
 - (iii) Calculate CH₄ and N₂O emissions from process off-gas using the applicable methods in ON.24 and the default emission factors of 2.8 x 10⁻³ kg/GJ for CH₄ and 5.7 x 10⁻⁴ kg/GJ for N₂O.
- (3) Calculate the emissions from process vents using the method specified in ON.203(b) for each process vent that can be reasonably expected to contain greater than 2 per cent by volume CO₂ or greater than 0.5 per cent by volume of CH₄ or greater than 0.01 per cent by volume (100 parts per million) of N₂O.
- (4) Calculate the emissions from equipment leaks using the method specified in ON.203(i)(1).
- (b) Calculation Methodology 2: Calculate the emissions of CO₂ from each process unit, for each calendar month as described in paragraphs (b)(1) through (b)(5) of this section.
 - (1) For each gaseous and liquid feedstock and product, measure the volume or mass used or produced each calendar month with a flow meter. Alternatively, for liquids, the person may calculate the volume used or collected in each month based on measurements of the liquid level in a storage tank at least once per month (and just prior to each change in direction of the level of the liquid). Fuels used for combustion purposes are not considered to be feedstocks. The emissions from the combustion of fuels (other than process off-gas) shall be calculated in accordance with the methods specified in ON.23 for CO₂ and the methods specified in ON.24 for CH₄ and N₂O.
 - (2) For each solid feedstock and product, measure the mass used or produced each calendar month.
 - (3) Collect a sample of each feedstock and product at least once per month and determine the carbon content of each sample. Alternatively, the person may use the results of analyses conducted by a fuel or feedstock supplier, provided the sampling and analysis is conducted at least once per month. If multiple valid carbon content measurements are made during the monthly measurement period, average them arithmetically.
 - (4) If the person determines that the monthly average concentration of a specific compound in a feedstock or product is greater than 99.5 per cent by volume (or mass for liquids and solids), then as an alternative to the sampling and analysis specified in paragraph (b)(3) of this section, the person may calculate the carbon content assuming 100 per cent of

that feedstock or product is the specific compound during periods of normal operation. The person shall maintain records of any determination made in accordance with this paragraph (b)(4) along with all supporting data, calculations, and other information. This alternative may not be used for products during periods of operation when off-specification product is produced. The person shall re-evaluate determinations made under this paragraph (b)(4) after any process change that affects the feedstock or product composition. The person shall keep records of the process change and the corresponding composition determinations. If the feedstock or product composition changes so that the average monthly concentration falls below 99.5 per cent, the person is no longer permitted to use this alternative method.

- (5) Calculate the CO₂ mass emissions for each petrochemical process unit using Equations 300-1 through 300-5 of this section.
 - (i) Gaseous feedstocks and products. Use Equation 300-1 of this section to calculate the net annual carbon input or output from gaseous feedstocks and products. Note that the result will be a negative value if there are no gaseous feedstocks in the process but there are gaseous products.

$$C_g = \sum_{n=1}^{12} \left[\sum_{i=1}^{j \text{ or } k} \left[(F_{gf})_{i,n} * (CC_{gf})_{i,n} * \frac{(MW_f)_i}{MVC} - (P_{gp})_{i,n} * (CC_{gp})_{i,n} * \frac{(MW_p)_i}{MVC} \right] \right]$$

Equation 300-1

Where:

- C_g = Annual net contribution to calculated emissions from carbon (C) in gaseous materials (kg/yr).
- $(F_{gf})_{i,n}$ = Volume of gaseous feedstock i introduced in month “n” (Rm³) at reference temperature and pressure conditions as used by the facility. If a mass flow meter is used, measure the feedstock introduced in month n in kg and replace the term “(MW_f)_i/MVC” with “1”.
- $(CC_{gf})_{i,n}$ = Average carbon content of the gaseous feedstock i for month “n” (kg C per kg of feedstock).
- $(MW_f)_i$ = Molecular weight of gaseous feedstock i (kg/kg-mole).
- MVC = Molar volume conversion factor at the same reference conditions as the above $(F_{gf})_{i,n}$ (Rm³/kg-mole).
= 8.3145 * [273.16 + reference temperature in °C] / [reference pressure in kilopascal]
- $(P_{gp})_{i,n}$ = Volume of gaseous product i produced in month “n” (Rm³) at the same reference conditions as the above $(F_{gf})_{i,n}$. If a mass flow meter is used, measure the gaseous product produced

in month “n” in kg and replace the term “(MW_p)_i/MVC” with “1”.

- (CC_{gp})_{i,n} = Average carbon content of gaseous product i, including streams containing CO₂ recovered for sale or use in another process, for month “n” (kg C per kg of product).
 (MW_p)_i = Molecular weight of gaseous product i (kg/kg-mole).
 j = Number of feedstocks.
 k = Number of products.

- (ii) Liquid feedstocks and products. Use Equation 300-2 of this section to calculate the net carbon input or output from liquid feedstocks and products. Note that the result will be a negative value if there are no liquid feedstocks in the process but there are liquid products.

$$C_l = \sum_{n=1}^{12} \left[\sum_{i=1}^{j \text{ or } k} [(F_{lf})_{i,n} * (CC_{lf})_{i,n} - (P_{lp})_{i,n} * (CC_{lp})_{i,n}] \right]$$

Equation 300-2

Where:

- C_l = Annual net contribution to calculated emissions from carbon in liquid materials, including liquid organic wastes (kg/yr).
 (F_{lf})_{i,n} = Volume or mass of liquid feedstock i introduced in month “n” (m³ of feedstock). If a mass flow meter is used, measure the liquid feedstock in month “n” introduced in kg and measure the carbon content of feedstock in kg of C per kg of feedstock.
 (CC_{lf})_{i,n} = Average carbon content of liquid feedstock i for month “n” (kg of C per m³ of feedstock when feedstock usage is measured in m³, or kg of C per kg of feedstock when feedstock usage is measured in kg).
 (P_{lp})_{i,n} = Volume or mass of liquid product i produced in month “n” (m³). If a mass flow meter is used, measure the liquid product produced in kg and measure the carbon content of liquid product in kg of C per kg of product.
 (CC_{lp})_{i,n} = Average carbon content of liquid product i, including organic liquid wastes, for month “n” (kg of C per m³ of product when liquid product is measured in m³, or kg of C per kg of product when product is measured in kg)
 j = Number of feedstocks.
 k = Number of products.

- (iii) Solid feedstocks and products. Use Equation 300-3 of this section to calculate the net annual carbon input or output from solid feedstocks and products. Note that the result will be a negative value if there are no solid feedstocks in the process but there are solid products.

$$C_s = \sum_{n=1}^{12} \left\{ \sum_{i=1}^{j \text{ or } k} \left[(F_{sf})_{i,n} * (CC_{sf})_{i,n} - (P_{sp})_{i,n} * (CC_{sp})_{i,n} \right] \right\}$$

Equation 300-3

Where:

- C_s = Annual net contribution to calculated emissions from carbon in solid materials (kg/yr).
 $(F_{sf})_{i,n}$ = Mass of solid feedstock i introduced in month “n” (kg).
 $(CC_{sf})_{i,n}$ = Average carbon content of solid feedstock i for month “n” (kg C per kg of feedstock).
 $(P_{sp})_{i,n}$ = Mass of solid product i produced in month “n” (kg).
 $(CC_{sp})_{i,n}$ = Average carbon content of solid product i in month “n” (kg C per kg of product).
j = Number of feedstocks.
k = Number of products.

- (iv) Annual emissions. Use the results from Equations 300-1 through 300-3 of this section, as applicable, in Equation 300-4 of this section to calculate annual CO₂ emissions.

$$CO_2 = 0.001 * 3.664 * (C_g + C_i + C_s)$$

Equation 300-4

Where:

- CO₂ = Annual CO₂ mass emissions from process operations and process off-gas combustion (tonnes/year).
0.001 = Conversion factor from kg to tonnes.
3.664 = Ratio of molecular weight, carbon dioxide to carbon.

- (c) Calculation Methodology 3: (Optional combustion methodology for ethylene production processes) For ethylene production processes, calculate CO₂, CH₄, and N₂O emissions as specified in paragraphs (c)(1) and (c)(2):

- (1) For each flare, calculate CO₂, CH₄, and N₂O emissions using the methodology for flares specified in ON.203(e).
- (2) For all other combustion units, calculate the CO₂ emissions from combustion of fuel that contains ethylene process off-gas using either Calculation Methodologies 3 or 4 in ON.23. Calculate CH₄ and N₂O emissions using the applicable method in ON.24 and the emission factors of 2.8 x 10⁻³ kg/GJ for CH₄ and 5.7 x 10⁻⁴ kg/GJ for N₂O. The person is not required to use the same calculation methodology for each stationary combustion unit that burns ethylene process off-gas.

ON.304 Sampling, Analysis, and Measurement Requirements

- (a) If the person calculates emissions using the method specified in ON.303(a):

- (1) Flares. The person shall comply with the monitoring requirements for flares specified in ON.204(e). The person may monitor the carbon content or the high heat value of the flare gas of flares in a petrochemical production facility on a quarterly basis.
 - (2) Process Vents. The person shall comply with the monitoring requirements for process vents specified in ON.204(b).
- (b) If the person calculates emissions using the method specified in ON.303(b):
- (1) Feedstock Consumption. The person shall measure the feedstock consumption using the same plant instruments used for accounting purposes, such as weigh hoppers, belt weigh feeders, or flow meters.
 - (2) EPS Parameter. The person shall measure the amount of an EPS parameter using the same plant instruments used for accounting purposes. Equipment used to measure the amount of an EPS parameter shall be:
 - (i) calibrated according to the manufacturer's instructions; or, where not available calibrate according to practices used for accounting purposes; and
 - (ii) maintained with an accuracy of plus or minus 5 per cent.
 - (3) Carbon Content. Except as allowed by ON.303(b)(4), the carbon content of each feedstock and product shall be measured at least once per month using one or more of the methods in section 4 of this Guideline.

ON.305 Procedures for Estimating Missing Data

Unavailable analytical data:

- (a) Whenever analytical data relating to sampling are unavailable, the person shall, using the methods prescribed in ON.304, re-analyze the original sample, a backup sample or a replacement sample for the same measurement and sampling period.

Determination of quantity:

- (b) Whenever sampling and measurement data required by ON.304 for the calculation of emissions are missing the person shall ensure that the data are replaced using the following missing data procedures:
 - (1) When the missing data concern carbon content, temperature, pressure or gas concentration, the person shall,
 - (i) Determine the sampling or measurement rate using the following Equation 300-5:

$$R = \frac{Q_{SAct}}{Q_{SRequired}}$$

Equation 300-5

Where:

- R = Sampling or measurement rate that was used, expressed as a percentage
- Q_{SAct} = Quantity of actual samples or measurements obtained by the person
- $Q_{SRequired}$ = Quantity of samples or measurements required under ON.304

- (ii) Replace the missing data as follows,
- (A) If $R \geq 0.9$: replace the missing data by the arithmetic mean of the sampling or measurement data from immediately before and after the missing data period. If no data is available from before the missing data period, the person shall use the first available data from after the missing data period;
- (B) If $0.75 \leq R < 0.9$: replace the missing data by the highest data value sampled or analyzed during the reporting period for which the calculation is made;
- (C) If $R < 0.75$: replace the missing data by the highest data value sampled or analyzed during the 3 preceding years;
- (2) When the missing data generated from best estimates based on all of the data relating to the processes concern coke burn, volumetric gas flow, gas volume, number of hours of operation, quantity of raw materials, quantity of product, quantity of steam or quantity of waste water treated, the replacement data shall be estimated on the basis of all the data relating to the processes used.
- (3) For all units subject to the requirements of ON.20 that monitor and report emissions using a CEMS, the missing data backfilling procedures in “Reference method for source testing quantification of carbon dioxide releases by continuous emission monitoring systems from thermal power generation” shall be followed for CO₂ concentration, stack gas flow rate, fuel flow rate, high heating value, and fuel carbon content.

ON.200 Petroleum Refining

ON.201 Activity Definition

For the purposes of this standard quantification method (SQM):

“Petroleum refining” has the same meaning as in the Regulation.

“Person” means a person that engages in petroleum refining.

“CAN-CWB Methodology” means the calculation methodology described in “The CAN-CWB Methodology for Regulatory Support: Public Report” dated January 2014, prepared by Solomon Associates.

ON.202 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.200 – ON.205, in an emission report prepared for a calendar year in respect of petroleum refining at a facility with the exception of information related to hydrogen production emissions, which the person shall report using ON.130 of this Guideline:
- (b) Report the total annual quantity of CO₂, CH₄, and N₂O emissions from catalyst regeneration, expressed in tonnes (t).
- (c) Report the total annual quantity of CO₂, CH₄, and N₂O emissions from process vents, expressed in tonnes (t).
- (d) Report the total annual quantity of CO₂, CH₄, and N₂O emissions from asphalt production, expressed in tonnes (t).
- (e) Report the total annual quantity of CO₂ emissions from sulphur recovery units, expressed in tonnes (t) and shall provide documentation of the methodology if they are using a source-specific molar fraction of CO₂ in sour gas in ON.203(d).
- (f) Report the total annual quantity of CH₄ emissions from above-ground storage tanks, expressed in tonnes (t).
- (g) Report the total annual quantity of CH₄ and N₂O emissions from waste water treatment plants, expressed in tonnes (t).
- (h) Report the total annual quantity of CH₄ emissions from oil-water separators, expressed in tonnes (t).
- (i) Report the total annual quantity of CH₄ emissions from equipment leaks at refineries, expressed in tonnes (t).
- (j) Report the total annual quantity of CO₂, CH₄, and N₂O emissions from coking calcining units, expressed in tonnes (t).
- (k) Report the total annual quantity of CO₂, CH₄, and N₂O emissions from uncontrolled blowdown systems, expressed in tonnes (t).

- (l) Report the total annual quantity of CH₄ emissions from loading operations, expressed in tonnes (t).
- (m) Report the total annual quantity of CH₄ emissions from delayed coking units, expressed in tonnes (t).
- (n) Report, for each of crude oil, propane, butane and ethanol brought into the facility for input into the refining process, report the
 - (1) total annual quantities
 - (i) of crude oil and ethanol expressed in kilolitres (kl), and
 - (ii) of propane and butane expressed in cubic metres(m³);
 - (2) annual higher heating value of each, expressed in megajoules (MJ) per unit; and
 - (3) annual average carbon content of each, expressed in kilograms (kg)of carbon per unit.
- (o) For each feedstock used under subsections (b) through (m) report the total annual
 - (1) gaseous quantities, expressed in cubic metres (m³);
 - (2) solid quantities, expressed in tonnes (t);
 - (3) liquid quantities, expressed in kilolitres (kL); and
 - (4) biomass-derived solid quantities, expressed in bone-dry tonnes (t).
- (p) Any person who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions and production information under subsections (b) through (m). This shall not include the emissions information specified for a CEMS in ON.20 of this notice. The person shall indicate where emissions calculations use a CEMS.
- (q) The following Complexity weighted barrel (CWB) parameters:
 - (1) The Direct Only CAN-CWB_(without cogeneration), in units of complexity weight barrel per calendar day (CWB/CD) and in units of complexity weight barrel per calendar year (CWB/year).
 - (2) The throughput for each of the Standard Refining Process units, offsites and non-energy utilities, non-crude sensible heat, sales and exports of steam and electricity identified in the CAN-CWB Methodology.
 - (3) The Total CO_{2e} emissions in the calendar year associated with the petroleum refinery, including emissions associated with Hydrogen Generation units (listed in Appendix B of the CAN-CWB Methodology), indirect emissions but excluding cogeneration emissions expressed in tonnes if present inside the refinery and if the ratio of electricity output (in

- GJ) to the total energy input (in GJ) of the cogeneration system is greater than 5 per cent.
- (4) The Direct-only CO₂ emissions in the calendar year from the petroleum refinery including Hydrogen Generation units emissions but excluding cogeneration emissions expressed in tonnes if present inside the refinery and if the ratio of electricity output (in GJ) to the total energy input (in GJ) of the cogeneration system is greater than 5 per cent.
 - (5) The Total Input Barrels described in the CAN-CWB Methodology expressed in barrels per calendar day.
 - (6) The Non-Crude Input Barrels described in the CAN-CWB Methodology (expressed in barrels per calendar day).
 - (7) The Imported Steam to the refinery, including steam originating from a cogeneration system located inside the refinery expressed in million BTU per calendar day.
 - (8) The Imported Electricity to the refinery, including electricity originating from a cogeneration system located inside the refinery expressed in megawatt hour per calendar day.
 - (9) The Exported Steam from the refinery, net of steam originating from a cogeneration system located inside the refinery expressed in thousand BTU per calendar day.
 - (10) The Exported Electricity from the refinery, net of electricity originating from a cogeneration system located inside the refinery expressed in kilowatt hour per calendar day.

ON.203 Calculation of Greenhouse Gas Emissions

The person shall calculate GHG emissions using the methods in subsections (a) through (m) of this section. If a CEMS is used to measure CO₂ emissions from process vents, asphalt production, sulphur recovery, or other control devices then the person may calculate the CO₂ emissions from these processes using a CEMS as specified in ON.23.

When the flue gas from two or more processes or fuel combustion sources are discharged through a common stack or duct before exiting to the atmosphere and if a CEMS as specified in ON.23 is used to continuously monitor the CO₂ emissions, the person may report the combined emissions from the processes or stationary combustion sources sharing the common stack or duct instead of separately reporting the GHG emission from individual processes or stationary combustion sources.

- (a) Calculate CO₂, CH₄, and N₂O emissions from catalyst regeneration using the GGQM in section 11.A of the GGQR.

- (b) Calculate CO₂, CH₄, and N₂O emissions from process vents using the GGQM in section 11.B of the GGQR.
- (c) Asphalt Production. Calculate CO₂ and CH₄ process emissions from asphalt production activities using the GGQM in section 11.C of the GGQR.
- (d) Calculate CO₂ and CH₄ process emissions from sulphur recovery using the GGQM in section 11.D of the GGQR.
- (e) Calculate CO₂ and CH₄ process emissions from flares and other control devices using the GGQM in section 11.E of the GGQR.
- (f) Calculate CH₄ emissions from storage tanks using the GGQM in section 11.F of the GGQR.
- (g) Calculate CH₄ and N₂O process emissions from industrial waste water processing using the GGQM in section 11.G of the GGQR.
- (h) Calculate CH₄ emissions from oil-water separators using the GGQM in section 11.H of the GGQR.
- (i) Calculate CH₄ emissions from equipment leaks using the GGQM in section 11.I of the GGQR.
- (j) Calculate GHG emissions from petroleum coke calcining using the GGQM in section 11.J of the GGQR.
- (k) For uncontrolled blowdown systems, the person shall use the methods for process vents in subsection (b) of this section.
- (l) Calculate CH₄ emissions from loading operations using the GGQM in section 11.L of the GGQR.
- (m) Calculate CH₄ emissions from delayed coking units using the GGQM in section 11.M of the GGQR.
- (n) Calculate CAN-CWB_(direct no cogen) using the following steps.
 - (1) Calculate the Complexity Weight Barrel (CWB_{ref}) per day using the CAN-CWB Methodology for all Standard Refining Process Units. The value of the “CWB factor” for hydrogen generation for all process types is 5.70. Exclude CWB adjustments associated with Sales and Exports of steam and electricity resulting from the presence of a cogeneration system inside the refinery.
 - (2) Calculate the Petroleum Refinery ‘direct-only emissions’ (Emission_{direct}) expressed in tonnes of CO_{2e} per year including Hydrogen Generation units emissions (reported under ON.132), if that process unit is present. Exclude from these emissions the cogeneration system emissions, if present inside the refinery and if the ratio of electricity output (in GJ) to the total energy input (in GJ) of the cogeneration system is greater than 5 per cent.

- (3) Calculate the Petroleum Refinery ‘indirect emissions’ ($Emission_{indirect}$) using the CAN-CWB Methodology expressed in tonnes of CO₂e per year. Use an emission factor of 0.521 tonnes of CO₂e per MWh for calculating indirect emissions from electricity obtained from outside the refinery and from a cogeneration system located inside the refinery if the cogeneration system emissions were excluded from paragraph (n)(2) of this section. Use an emission factor of 0.059 tonne CO₂e per million Btu/d for calculating indirect emissions from steam imported from outside the refinery and from a cogeneration system located inside the refinery if the cogeneration system emissions were excluded from paragraph (n)(2) of this section.
- (4) Calculate the Direct Only CAN-CWB without cogeneration ($CWB_{direct\ no\ Cogen}$) for the refinery as per the CAN-CWB Methodology expressed in CAN-CWB per calendar day, by taking the value from paragraph (n)(1) of this section times the value from paragraph (n)(2) of this section, divided by the sum of paragraphs (n)(2) and (n)(3) of this section, or using equation 200-1.

$$CAN - CWB_{(direct\ no\ cogen)} = \frac{CWB_{ref} \times Emission_{direct}}{Emission_{direct} + Emission_{indirect}}$$

Equation 200-1

Where:

- | | | |
|---------------------------|---|--|
| $CWB_{direct\ no\ Cogen}$ | = | complexity weight barrel direct without cogeneration, expressed in complexity weighted barrels per day |
| CWB_{ref} | = | reference complexity weighted barrel, expressed in complexity weighted barrels per day. |
| $Emission_{direct}$ | = | petroleum refinery direct emissions, expressed in tonnes of CO ₂ e per year. |
| $Emission_{indirect}$ | = | petroleum refinery indirect emissions, expressed in tonnes of CO ₂ e per year. |

- (5) Calculate the annual Direct Only CAN-CWB($_{direct\ no\ cogen}$) by multiplying the value from ON.203(n)(4) with the number of days in the year, expressed in complexity weighted barrels per calendar year.

ON.204 Sampling, Analysis, and Measurement Requirements

(a) Catalyst Regeneration.

- (1) For FCCUs and fluid coking units, the person shall measure the parameters required in section 11.N.1 of the GGQR.
- (2) For periodic catalyst regeneration, the person shall measure the following parameters.

- (i) The mass of catalyst regenerated in each regeneration cycle.
 - (ii) The weight fraction of carbon on the catalyst prior to and after catalyst regeneration.
- (3) For continuous catalyst regeneration in operations other than FCCUs and fluid cokers, the person shall measure the following parameters.
 - (i) The hourly catalyst regeneration rate.
 - (ii) The weight fraction of carbon on the catalyst prior to and after catalyst regeneration.
 - (iii) The number of hours of operation.
- (b) Process vents. The person shall measure the parameters required in section 11.N.2 of the GGQR.
- (c) Asphalt Production. The person shall measure the mass of asphalt blown, as required in section 11.N.3 of the GGQR.
- (d) Sulphur Recovery. The person shall measure the volumetric flow rate of acid gas to the SRU in accordance with section 11.N.4 of the GGQR.
- (e) Flares and Other Control Devices. The person shall measure the parameters in accordance with section 11.N.5 of the GGQR (or ON.25.o).
- (f) Storage Tanks. The person shall determine the annual throughput of crude oil, naphtha, distillate oil, asphalt, and gas oil for each storage tank in accordance with section 11.N.6 of the GGQR.
- (g) Waste water Treatment. The person shall measure the parameters in accordance with section 11.N.7 of the GGQR.
- (h) Oil-Water Separators. The person shall measure the daily volume of waste water treated by the oil-water separators as required under section 11.N.8 of the GGQR.
- (i) Petroleum Coke Calcining. Determine the mass of petroleum coke as required using measurement equipment used for accounting purposes including purchase records or direct measurement. Determine the carbon content of petroleum coke using any one of the following methods.
 - (1) Any of the analytical methods listed in the Technical Reference Document section of this Guideline (section 4).
 - (2) The most appropriate method published by a consensus-based standards organization or, if no appropriate method is published by a consensus-based standards organization, use industry standard methods, noting where such methods are used and what methods are used.
- (j) CAN-CWB. Determine the following parameters through measurements.

- (1) “Throughput” for each of the Standard Refining Process Units identified in Appendix B of the CAN-CWB Methodology.
 - (2) “Total Input Barrels” described in Section 2.4.2 of the CAN-CWB Methodology.
 - (3) “Non-Crude Input Barrels” described in Section 2.4.3 of the CAN-CWB Methodology.
 - (4) “Exported Steam” from the refinery, net of steam originating from a cogeneration system located inside the refinery.
 - (5) “Exported Electricity” from the refinery, net of electricity originating from a cogeneration system located inside the refinery.
 - (6) “Imported steam” to the refinery, including steam originating from a cogeneration system located inside the refinery.
 - (7) “Imported Electricity” to the refinery, including electricity originating from an outside source or from a cogeneration system located inside the refinery.
- (k) Equipment used to measure the CAN-CWB parameters shall be:
- (1) calibrated according to the manufacturer’s instructions and
 - (2) maintained to achieve an accuracy of plus or minus 5 per cent.

ON.205 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 11.O of the GGQR.

ON.340 Phosphoric Acid Production

ON.341 Activity Definition

For the purposes of this standard quantification method (SQM):

“Phosphoric acid production” has the same meaning as in the Regulation.

“Person” means a person that engages in phosphoric acid production.

ON.342 Greenhouse Gas Reporting Requirements

The person shall set out the following information, calculated for the calendar year using SQM ON.340 – ON.345, in an emission report prepared for a calendar year in respect of phosphoric acid production at a facility:

- (a) CO₂ process emissions from each wet-process phosphoric acid process line (tonnes).
- (b) Annual phosphoric acid production (tonnes)

ON.343 Calculation of GHG Emissions

- (a) Quantify emissions in accordance with U.S. EPA 40 CFR 98 Subpart Z Section 98.263.

ON.344 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance with U.S. EPA 40 CFR 98 Subpart Z Section 98.264.

ON.345 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with U.S. EPA 40 CFR 98 Subpart Z Section 98.265.

ON.210 Pulp and Paper Production

ON.211 Activity Definition

For the purposes of this standard quantification method (SQM):

“Pulp and paper production” has the same meaning as in the Regulation.

“Person” means a person that engages in pulp and paper production.

ON.212 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.210 – ON.215, in an emission report prepared for a calendar year in respect of pulp and paper production at a facility.
- (b) Any person subject to this SQM shall report the following:
 - (1) total annual quantity of CO₂ emissions from the addition of carbonates in the chemical recovery of chemical pulp mills, expressed in tonnes (t);
 - (2) total annual CH₄ and N₂O emissions from on-site waste water treatment plants, expressed in tonnes (t);
 - (3) total annual quantity of pulp, expressed in tonnes (t) of air dried pulp;
 - (4) total annual quantity of input carbonate material, by carbonate type, expressed in tonnes (t);
 - (5) annual weighted average carbon content of input carbonate material, by carbonate type, expressed in tonne of carbon per tonne of carbonate material, if using equation 12-2 in section 12 of the GGQR;
 - (6) total annual quantity of carbon-containing process output material, by material type, expressed in tonnes (t), if using equation 12-2 in section 12 of the GGQR;
 - (7) annual weighted average carbon content of carbon-containing process output material, by material type, expressed in tonne of carbon per tonne of material, if using equation 12-2 in section 12 of the GGQR; and
 - (8) annual weighted average of fraction of calcination achieved, by type of carbonate used, if using equation 12-3 in section 12 of the GGQR and if not using the default value, the method for determining the calcination fraction used must be provided.
- (c) Any person subject to this SQM who operates a facility with stacks monitored by a CEMS may use the annual emissions data from the CEMS to report the emissions information under paragraphs (b)(1) and (b)(2). This shall not include the emissions information specified for a CEMS in ON.20. The person shall indicate where a CEMS is being used to calculate emissions.

- (d) N₂O, and CH₄ process emissions from waste water emissions in tonnes using method ON.203(g).

ON.213 Calculation of GHG Emissions

- (a) Calculate CO₂, CH₄ and N₂O combustion and flaring emissions (i.e., kraft or soda chemical recovery furnace, sulfite chemical recovery combustion unit, stand-alone semichemical recovery combustion unit, or kraft or soda pulp mill lime kiln) using the calculation methods in ON.23, ON.24.
- (b) For make-up chemical use, calculate CO₂ emissions by using the GGQM in section 12.A.2 of the GGQR.
- (c) For waste water emissions, calculate CO₂ emissions by using the GGQM in section 12.A.3 of the GGQR.

ON.214 Sampling, Analysis, and Measurement Requirements

- (a) The person shall follow the sampling, analysis and measurement requirement in accordance with section 12.B of the GGQR.

ON.215 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with section 12.C of the GGQR.

ON.220 Soda Ash Production

ON.221 Activity Definition

For the purposes of this standard quantification method (SQM):

“Soda ash production” has the same meaning as in the Regulation.

“Person” means a person that engages in soda ash production.

ON.222 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using SQM ON.220 – ON.225, in an emission report prepared for a calendar year in respect of soda ash production at a facility.
- (b) CO₂ process emissions from soda ash manufacturing line (tonnes).
- (c) Annual soda ash production (tonnes)

ON.223 Calculation of GHG Emissions

- (a) Quantify emissions in accordance with EPA 40 CFR part 98.293.

ON.224 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance with U.S. EPA 40 CFR 98 Subpart CC Section 98.294.

ON.225 Procedures for Estimating Missing Data

Missing data requirements for this activity shall be estimated in accordance with U.S. EPA 40 CFR 98 Subpart CC Section 98.295.

ON.270 Waste Water Processing

ON.271 Activity Definition

For the purposes of this standard quantification method (SQM):

“Waste water processing” has the same meaning as in the Regulation.

“Person” means a person that engages in waste water processing.

ON.272 Greenhouse Gas Reporting Requirements

- (a) The person shall set out the following information, calculated for the calendar year using this SQM ON.273 – ON.274, in an emission report prepared for a calendar year in respect of a facility.
- (b) Any person subject to this method shall report N₂O, and CH₄ process emissions from waste water emissions in tonnes using method ON.203(g).

ON.273 Calculation of GHG Emissions

- (a) Quantify emissions using method ON.203(g) in this Guideline.

ON.274 Sampling, Analysis, and Measurement Requirements

Sampling, analysis and measurement requirements for this activity shall be done in accordance ON.204(g) in this Guideline.

ON.275 Procedures for Estimating Missing Data

The missing data procedures shall be done in accordance with ON.205.

